

UNCLASSIFIED

Defense Technical Information Center
Compilation Part Notice

ADP022457

TITLE: Michelle Code Usage and Validation at CPI

DISTRIBUTION: Approved for public release, distribution unlimited

This paper is part of the following report:

TITLE: 2006 IEEE International Vacuum Electronics Conference held jointly with 2006 IEEE International Vacuum Electron Sources Held in Monterey, California on April 25-27, 2006

To order the complete compilation report, use: ADA453924

The component part is provided here to allow users access to individually authored sections of proceedings, annals, symposia, etc. However, the component should be considered within the context of the overall compilation report and not as a stand-alone technical report.

The following component part numbers comprise the compilation report:
ADP022420 thru ADP022696

UNCLASSIFIED

Michelle Code Usage and Validation at CPI*

J. Atkinson, R. Begum and M. Chee

Communications and Power Industries
811 Hansen Way, Palo Alto, CA 94303-0750
Tel. (650) 846-3051 E-Mail: john.atkinson@cpii.com

B. Levush

Naval Research Laboratory
4555 Overlook Ave.
Washington, D.C. 20375-5000

J. Petillo

Science Applications International Corp.
Suite 130, 20 Burlington Mall Rd.
Burlington, MA 01803

Abstract: Two Michelle¹ models are described and results compared to practical measurements. The two models are of a gridded electron gun and a two stage depressed collector with secondary emission included.

Keywords: Michelle; Gridded Gun; Depressed Collector; Thermionic Correction; Secondaries

Intercepting Gridded Gun Model

A 3D model (fig 1) of this intercepting gridded gun was initiated in 2004. The model took advantage of the symmetry of the gun geometry, a 90 degree wedge was modeled.

The gun has been in production at CPI for many years, so extensive history of performance was available, coupled with measurements of grid spacings while at operating temperature. The gun typically operates at low perveance, and has a simple square mesh grid. In preparation for the modeling, various measurements of the hot grid spacing were reviewed and appeared consistent.

Beam current for typical Egk voltages was only about 65% of measured values using the cold geometry, as might be expected. However after including the best estimates of hot geometry current only increased to 84%. Beam interception also appeared higher than measured at 18% vs 12%

Subsequently it was realized that a correction to the Childs law emission algorithm within Michelle should be used. It applies for cases where the mesh close to the cathode is very fine, as is the case for gridded guns.

With this option selected results now give a better match to the measured values. Further refinements to this thermionic correction have been made. Predicted beam current is still low by about 8%, however it is suspected that the hot grid spacing may be smaller than prior measurements indicate.




Fig 1 Intercepting Gridded Gun Model

Two stage depressed collector model

The initial Michelle model was set up in 3D. The modeling included two generations of secondary electrons, and various combinations of secondary angles and energies were investigated. This early model used a simulated DC beam with no transverse energy.




Fig 2 2 Stage Depressed Collector Model in 3D

Due to the large number of cells required in 3D to represent the geometry (fig 2), the number of particles used was restricted to prevent excessive run time. Results from the case did not agree well with real measurements, primarily due to the idealized primary beam that was used.

Subsequently, the model was redone in 2D axisymmetric form to take advantage of higher mesh densities, and quad meshing. This was particularly important in the beam entry region, and allowed many more particles to be used.

The simulated DC beam has also been replaced with a spent beam (no RF modulation) generated from a Christine 3D² model of the amplifier.

* This work was partially supported by ONR and IR&D

References

- ¹ J. Petillo, K. Eppley, D. Panagos, P. Blanchard, E. Nelson, N. Dionne, J. DeFord, B. Held, Li Chernyakova, W. Krueger, S. Humphries, T. McClure, A. Mondelli, J. Burdette, M. Cattelino, R. True, K. T. Nguyen, and B. Levush, "Michelle 3-D Electron Gun And Collector Modeling Tool: Theory And Design," *IEEE Trans. Plasma Science*, vol. 30, no. 30, June 2002.
- ² David Chernin, Thomas M. Antonsen, Jr., Baruch Levush, *Senior Member, IEEE*, and David R. Whaley "A Three-Dimensional Multifrequency Large Signal Model for Helix Traveling Wave Tubes", *IEEE Transactions on Electron Devices*, vol. 48, no. 1, January 2001

For comparison, practical measurements were made on the real device with an axisymmetric magnetic field. The magnetic field for the production device contains some non-axisymmetric features, which were left out to provide a valid comparison with the 2D model.

Collector stage currents and body current were measured and plotted versus stage voltages to provide a comparison with the Michelle work. The 3D surface plot (fig 3) shows one set of these measurement results, with stage 1 current depicted on the vertical axis and stage voltages on the other axes.




Fig 3 Measured Collector Stage 1 Current