

NRL/1001.1/MR—2023/1

**THE NAVAL RESEARCH LABORATORY
AND ITS
MISSION OF A CENTURY
1923 - 2023**

*100 Science and Engineering Contributions
to
Sea Power and National Security*



DON J. DEYOUNG

*Executive Assistant to the Director of Research
Executive Directorate*

August 21, 2023

DISTRIBUTION STATEMENT A: Approved for public release; distribution is unlimited.

| REPORT DOCUMENTATION PAGE | | | | Form Approved OMB No. 0704-0188 | |
|---|------------------|---|-------------------------------------|---|---|
| Public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing this collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden to Department of Defense, Washington Headquarters Services, Directorate for Information Operations and Reports (0704-0188), 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302. Respondents should be aware that notwithstanding any other provision of law, no person shall be subject to any penalty for failing to comply with a collection of information if it does not display a currently valid OMB control number. PLEASE DO NOT RETURN YOUR FORM TO THE ABOVE ADDRESS. | | | | | |
| 1. REPORT DATE (DD-MM-YYYY) 21-08-2023 | | 2. REPORT TYPE NRL Memorandum Report | | 3. DATES COVERED (From - To) 1923 – 2023 | |
| 4. TITLE AND SUBTITLE The Naval Research Laboratory and its Mission of a Century: 100 Science and Engineering Contributions to Sea Power and National Security | | | | 5a. CONTRACT NUMBER | |
| | | | | 5b. GRANT NUMBER | |
| | | | | 5c. PROGRAM ELEMENT NUMBER | |
| 6. AUTHOR(S) Don J. DeYoung | | | | 5d. PROJECT NUMBER | |
| | | | | 5e. TASK NUMBER | |
| | | | | 5f. WORK UNIT NUMBER | |
| 7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) Naval Research Laboratory 4555 Overlook Avenue, SW Washington, DC 20375-5320 | | | | 8. PERFORMING ORGANIZATION REPORT NUMBER NRL/1001.1/MR--2023/1 | |
| 9. SPONSORING / MONITORING AGENCY NAME(S) AND ADDRESS(ES) Naval Research Laboratory 4555 Overlook Avenue, SW Washington, DC 20375-5320 | | | | 10. SPONSOR / MONITOR'S ACRONYM(S) NRL | |
| | | | | 11. SPONSOR / MONITOR'S REPORT NUMBER(S) | |
| 12. DISTRIBUTION / AVAILABILITY STATEMENT DISTRIBUTION STATEMENT A: Approved for public release; distribution is unlimited. | | | | | |
| 13. SUPPLEMENTARY NOTES | | | | | |
| 14. ABSTRACT This report was written to accomplish three goals. The first is to commemorate the centennial of the Naval Research Laboratory (NRL) by featuring 100 achievements that illustrate its extraordinary impact on American naval power and national security. The second goal is to collect and preserve NRL's corporate memory — a fundamental resource vital to an organization's sense of purpose, direction, and pride. Finally, as an agency of the United States Government, the third goal is to deliver an account of what the Laboratory has accomplished with public funds, which is basic to good governance in a healthy democracy. | | | | | |
| 15. SUBJECT TERMS | | | | | |
| 16. SECURITY CLASSIFICATION OF: | | | 17. LIMITATION OF ABSTRACT U | 18. NUMBER OF PAGES 104 | 19a. NAME OF RESPONSIBLE PERSON Don J. DeYoung |
| a. REPORT U | b. ABSTRACT U | c. THIS PAGE U | | | 19b. TELEPHONE NUMBER (include area code) (202) 767-2445 |

This page intentionally left blank.

PREFACE

This report was written to accomplish three goals. The first is to commemorate the centennial of the Naval Research Laboratory (NRL) by featuring 100 achievements that illustrate its extraordinary impact on American naval power and national security. The second goal is to collect and preserve NRL's corporate memory — a fundamental resource vital to an organization's sense of purpose, direction, and pride. Finally, as an agency of the United States Government, the third goal is to deliver an account of what the Laboratory has accomplished with public funds, which is basic to good governance in a healthy democracy.

The project to produce this document began in 2018, though it benefited greatly from a solid base of information published in two older documents. These were the “75th Anniversary Awards for Innovation” (1998) and “The U.S. Naval Research Laboratory: Fulfilling the Roosevelts' Vision for American Naval Power” (2006). The latter used the content of a nomination submitted to the Navy League's New York Council for consideration of NRL as a recipient of the Roosevelts Gold Medal for Science. The Laboratory received the Medal in 2006 for its “extraordinary scientific contributions to the security of America.”

Material for achievements occurring after 2006 were gathered in several ways. In 2018, NRL was preparing for a series of briefings to the Naval Research Advisory Committee, which provided an opportunity to collect information on noteworthy work performed over the prior 15 years. Other resources were also consulted, such as division histories written in response to a directive from the director of research in 2009 to preserve corporate memory. Together, these and other sources added 43 recent achievements to the previously published material, yielding a total of 133 candidate narratives for this centennial publication.

Where appropriate, older achievements were merged with recent achievements in related areas of science and technology. A total of 112 candidate achievements remained after infusing the narratives of older achievements with the more recent work. In a final step of the process, 12 narratives showing a greater degree of future promise relative to current use were removed to be highlighted separately in a compilation of “25 Technologies for the Next 25 Years.” The final roster of 100 accomplishments was then complete.

At its most fundamental, the idea behind NRL's creation 100 years ago was to help build American sea power and to protect national security through continual technological innovation. The record shows that NRL has helped make the U.S. Navy and the U.S. Marine Corps the most formidable naval fighting force in the world. The 100 unclassified innovations described in this report are only representative of thousands, many of them still classified, that NRL has produced since 1923. Even so, these 100 by themselves confirm that NRL exerts a powerful influence on our Navy and our republic through the creative work of dedicated government scientists, engineers, and support personnel who serve the nation's interest.

Don J. DeYoung

Executive Assistant to the Director of Research
U.S. Naval Research Laboratory

May 2023

This page intentionally left blank.

ACKNOWLEDGEMENTS

This report could not have reached completion without the time and effort invested by a great many individuals, especially given the persistent disruptions of a national public health emergency.

Subject-matter experts from NRL's research divisions updated older, previously published material on NRL's achievements with recent information, fact-checked all 100 narratives, and identified primary sources to firmly establish the origins of the work. Their participation was critical and much appreciated.

The attention to detail and business efficiency provided by the publications staff of NRL's Corporate Communications Office was also vital, particularly the contributions made by Jonna Atkinson, Benjamin Bateman, and Cynthia Allen, who moved the report into timely review and production on a tight schedule.

Dr. Peter Matic, associate director of research for materials science and component technology, provided keen advice and high-level sponsorship that helped keep this project well supported by technical personnel, support staff, and Laboratory leadership.

Dr. Angelina Callahan, NRL's former historian (now the Navy Secretariat historian), researched historical sources and mined technical literature to update and tell a fuller story for a number of the achievements.

Above all, the greatest credit belongs to the generations of men and women who dedicated themselves to the mission of the U.S. Navy and the security of our nation over the course of a century. This report may commemorate 100 achievements, but they are only representative of many thousands contributed after the Laboratory first opened its gates on July 2, 1923. And of course, far more than a few are classified.

NRL's centennial is just a moment in time to reflect on and celebrate the Laboratory's enormous cumulative impact made through a world war, a long cold war, and a multitude of regional conflicts and crises. This moment, however, can and must inspire resilience in the decades ahead. Serious threats remain, and unforeseen challenges will arise.

NRL's mission continues.

This page intentionally left blank.

TABLE OF CONTENTS

| | |
|---|----|
| Gamma-Ray Radiography..... | 1 |
| First Operational Fathometer | 2 |
| Development of High-Frequency Radio Equipment..... | 3 |
| Radio Propagation and the “Skip-Distance” Effect..... | 4 |
| Invention of U.S. Radar..... | 5 |
| First Operational U.S. Sonar | 6 |
| Liquid Thermal Diffusion Process | 7 |
| Aircraft Radio Homing System | 8 |
| First Proposal of a Nuclear Submarine..... | 9 |
| Plan-Position Indicator..... | 10 |
| Identification Friend-or-Foe Systems | 11 |
| Monopulse Radar | 12 |
| First American Airborne Radar | 13 |
| First Far-Ultraviolet Spectrum of the Sun..... | 14 |
| First Detection of X-Rays from the Sun | 15 |
| Principles of Fracture Mechanics..... | 16 |
| Molecular Structure Analysis and the Nobel Prize..... | 17 |
| The Viking Sounding Rocket Program..... | 18 |
| Synthetic Lubricants..... | 19 |
| Radar Absorbing Materials and Anechoic Chambers..... | 20 |
| Over-the-Horizon Radar | 21 |
| High-Resolution Radar..... | 22 |
| Vanguard Program — The Rocket | 23 |
| Vanguard Program — Minitrack and Space Surveillance..... | 24 |
| Vanguard Program — the Satellites and the Science..... | 25 |
| First Operational Satellite Communication System — “Communication Moon Relay” | 26 |
| X-Ray Astronomy..... | 27 |
| High-Frequency Direction Finding..... | 28 |
| Solar Radiation (SOLRAD) I | 29 |
| America’s First Operational Intelligence Satellite..... | 30 |
| High-Power Neodymium Glass Lasers | 31 |
| Improved Aircraft Canopy and Window Materials | 32 |
| Purple-K-Powder | 33 |
| Polytetrafluoroethylene for the Navy..... | 34 |
| Quantitative X-Ray Fluorescence Analysis..... | 35 |
| Improved Boiler Water Treatment | 36 |
| Fracture Test Technology | 37 |
| Deep-Ocean Search..... | 38 |
| TIMATION and NAVSTAR GPS..... | 39 |
| Radiation Detection | 40 |
| Nuclear Reactor Safety..... | 41 |
| Remote Sensing of the Upper Atmosphere..... | 42 |
| Secure Voice Communication | 43 |
| Submarine Habitability..... | 44 |
| Flux-Corrected Transport | 45 |
| High-Power, High-Current Pulsed Power Generators..... | 46 |
| Marine Surface Monolayers | 47 |
| Wind Speed Measurement Using Microwave Imaging..... | 48 |
| Spaceborne Solar Coronagraphs | 49 |
| Fiber-Optic Interferometric Acoustic Sensors | 50 |

| | |
|---|-----|
| Semi-Insulating Gallium Arsenide Crystals | 51 |
| Super Rapid-Blooming Offboard Chaff..... | 52 |
| Ion-Implantation Metallurgy..... | 53 |
| Fluorinated Network Polymers | 54 |
| Excimer Laser Technology | 55 |
| Specific Emitter Identification | 56 |
| Inverse Synthetic Aperture Radar | 57 |
| Key Distribution and Management for Cryptographic Equipment | 58 |
| Infrared Threat Warning | 59 |
| Optical Fiber Gyroscope | 60 |
| Permanent Magnet Materials..... | 61 |
| NOGAPS/NAVGEM Global Weather Prediction..... | 62 |
| Generalized Near-field Acoustical Holography..... | 63 |
| Fixed-Wing Airborne Gravimetry | 64 |
| Acoustic Matched-Field Processing..... | 65 |
| Magnetic Materials and Semiconductor Technology | 66 |
| Maritime Domain Awareness | 67 |
| Deep-Space Program Science Experiment (Clementine) | 68 |
| Decadal Impact of El Niño..... | 69 |
| Optical Immunoassays and Sensors | 70 |
| Interferometry at Optical Wavelengths | 71 |
| Mesoscale Prediction Systems | 72 |
| Surface Acoustic Wave Chemical Sensors..... | 73 |
| AN/ALE-50 Towed Countermeasures..... | 74 |
| Anti-Ship Missile Defense Radar | 75 |
| CT-Analyst | 76 |
| Mountain Wave Forecast..... | 77 |
| Low-Solar-Absorbance Ship Paint | 78 |
| Tactical Communications | 79 |
| Hyperspectral Imager for Tactical and Environmental Uses..... | 80 |
| Dragon Eye..... | 81 |
| Pulsed X-ray Radiography | 82 |
| Silent Guardian: DNA Microarray Technology..... | 83 |
| Tactical Satellite (TACSAT)..... | 84 |
| Personal Protective Equipment and Injury Biomechanics | 85 |
| Rapid-Cure Corrosion-Control Coatings | 86 |
| Structural Acoustics | 87 |
| Free Space Optics Communications..... | 88 |
| Global Ocean Forecast System | 89 |
| Regional Tropical Cyclone Prediction Systems | 90 |
| WindSat Spaceborne Polarimetric Microwave Radiometer | 91 |
| Hydrogen Fuel Cells for Unmanned Systems..... | 92 |
| Topside Camouflage and Nonskid Deck Coatings | 93 |
| Flying Squirrel..... | 94 |
| High-Temperature Nonskid Decking..... | 95 |
| NULKA Offboard Countermeasure System | 96 |
| Onion Routing, Tor, and Onion Services..... | 97 |
| Transparent Armor | 98 |
| Gallium Nitride Transistor Development | 99 |
| First Operational Shipboard Laser Weapon | 100 |

GAMMA-RAY RADIOGRAPHY

ACHIEVEMENT

NRL's development of gamma-ray radiography was an important contribution to the nondestructive testing (NDT) of metal castings and welds. The method, devised by R.F. Mehl in the 1920s, entailed the use of gamma-ray radiation as a shadow-graphic technique to detect flaws in cast or welded steels. Using radium as a source of gamma rays and exposure times measured in hours, Mehl and his team were able to image and measure internal cracks in bad castings and welds before the parts failed. This prevented their installation into new vessels.

This technique was first used to ascertain the extent of suspected flaws in the sternpost castings of the U.S. Navy's new 10,000-ton heavy cruisers.¹ The integrity of these post castings was vital to the successful operation of the vessels. Such failures could leave a ship at sea and unable to steer, a potentially fatal situation. Upon examination, the sternpost castings of these vessels were found to be faulty, and all 10 cruisers of the affected class subsequently had to be repaired to avoid operational failure. During the five-year period before World War II, this NDT technique facilitated the development of improved steel casting processes. By trial and nondestructive examination, the methods used in all stages of the molding, casting, and testing of steel were improved.

IMPACT

Mehl's work on the Navy's cruiser sternpost castings established gamma-ray radiography as an NDT technique in this country.² It also contributed to American sea power by improving the production of high-quality steel for armor, ship frames, and fittings.

In 1941, the American Society for Nondestructive Testing originated the biannual Mehl Honor Lecture series to honor R.F. Mehl for his pioneering work in gamma-ray radiography. The selected speaker is chosen for having made an outstanding contribution to the field of NDT.³ In the years since, gamma-ray radiography has found use in numerous industrial applications such as inspection of the internal structure and integrity of welds on pipelines and pressure vessels.

PRIMARY REFERENCE DOCUMENTS

- Mehl, R.F., Doan, G.E., and Barrett, C.S., "Radiography by the Use of Gamma Rays," *Transactions of the American Society for Steel Treating*, Chicago, 1930.
- Barrett, C.S., Gezelius, R.A., and Mehl, R.F., "The Technique of Radiography by Gamma Rays," *Metals and Alloys*, December 1930.
- Mehl, R.F., "Report on Use of Gamma Rays for Radiographic Inspection of Sternpost and Keel Knuckle Casting," NRL Report, June 30, 1931.
- Mehl, R.F., "Radiography Inspection with Gamma Rays," *American Machinist*, Vol. 75, 278-80 (1931).

Manuscript approved August 15, 2023.

¹ Taylor, A.H., *The First Twenty-Five Years of the Naval Research Laboratory* (NAVEXOS P-549), April 1948, 26.

² *Materials Science and Technology Division History*, NRL/PU-6300-93-240 (May 1993), 91.

³ Lambert, R.H., VADM, "A Tribute to Robert F. Mehl," *Materials Evaluation*, March 1972, 15.

FIRST OPERATIONAL FATHOMETER

ACHIEVEMENT

One of NRL's earliest accomplishments was the development of the first operational depth finder. Today, this device is called a fathometer. The depth finder used two transducers (U.S. Navy MV type hydrophones), one for transmissions in the frequency range near 1,000 Hz and the second as a receiver. The measured time interval between the transmitted and received signals, combined with the sound speed, was used to calculate the distance to the sea floor. Use of a directional hydrophone provided the added benefit of determining the slope of the sea floor.⁴

The first acoustic depth finder placed into the U.S. fleet for routine service was installed in the destroyer USS *Stewart* just prior to its departure for Manila via Gibraltar and the Suez Canal in June 1922. Between the U.S. and the Strait of Gibraltar, approximately 900 soundings were recorded, documenting the ocean's depth.⁵ Throughout the trip, soundings were taken at least every 20 minutes and at times as often as every minute. The depths encountered were up to 3,200 fathoms (5,900 m). Based on the success of the echo sounding demonstration on the *Stewart*, depth finders were installed on the destroyers USS *Hull* and USS *Corey* in 1923 and 1924. The destroyers proceeded to make a 35,000-square-mile survey along the coast of Southern California, covering about 1,000 square miles per day. This was followed by installation of the equipment in several more Navy ships.⁶ In 1934, improved depth-finding equipment using the QB transducer was installed in the fleet.⁷

Development of the first operational depth finder began in 1919 and was led by H.C. Hayes, who moved his group to NRL upon its opening in 1923. Among the numerous awards received by Hayes was the Navy Distinguished Civilian Service Award (bestowed in 1945 by Secretary of the Navy James Forrestal) and the first Pioneers of Underwater Acoustics Award from the Acoustical Society of America (1959).⁸

IMPACT

NRL's Sonic Depth Finder was the first ocean depth-sounding fathometer to be installed for routine service in surface vessels and submarines of the U.S. Navy fleet. Its use resulted in greatly enhanced surface and subsurface navigation and surveying capabilities, which improved ship safety.

PRIMARY REFERENCE DOCUMENTS

- Hayes, H.C., "The Sonic Depth Finder," *Proceedings of the American Philosophical Society*, Vol. LXIII, No. 1 (1924).
- Stephenson, E.B., "Instructions for Echo Detection Equipment Model XQB," NRL Report RA55A227, August 1934.

⁴ Hayes, H.C., "The Sonic Depth Finder," *Proceedings of the American Philosophical Society*, Vol. LXIII, No. 1 (1924).

⁵ National Oceanic and Atmospheric Administration (NOAA) Ocean Exploration and Research: Historical Timeline, [<https://oceanexplorer.noaa.gov/history/timeline/welcome.html?page=3>]

⁶ Hayes, H.C., "The Sonic Depth Finder."

⁷ Stephenson, E.B., "Instructions for Echo Detection Equipment Model XQB," NRL Report RA55A227, August 1934.

⁸ Erskine, F.T., "Harvey C. Hayes: First Superintendent of the NRL Sound Division," *Proceedings of Meetings on Acoustics*, Acoustical Society of America, March 2016.

DEVELOPMENT OF HIGH-FREQUENCY RADIO EQUIPMENT

ACHIEVEMENT

NRL's development of radio equipment in the 1920s, such as quartz-crystal frequency control, and high-power transmitters and receivers, led to the adoption and extensive utilization of high-frequency (HF) communications by the U.S. Navy. Many of these NRL developments were adopted Navy-wide. For example, the quartz crystal oscillator circuit became the Navy standard oscillator circuit (1924),⁹ and the Model RG receiver was the first to reach the fleet in large numbers, becoming the Navy's principal receiver (1925) for over a decade and continuing in service during World War II.¹⁰

NRL's HF radio equipment enabled the following achievements that, in turn, facilitated Navy-wide adoption of HF communications.

- An important factor in the Navy's adoption of HF was the performance of the NRL-developed HF transmitter and receiver carried by the Navy's dirigible USS *Shenandoah* during its transcontinental trip in 1924. This equipment accomplished the unusual feat of remaining in communication with NRL throughout the entire trip.¹¹
- An NRL HF crystal-controlled transmitter communicated directly with the flagship USS *Seattle* during the cruise of the fleet to Australia in 1925, a demonstration that contributed importantly to the Navy's adoption of HF.
- NRL maintained regular communications with the Antarctic base and support ships of Commander R.E. Byrd's expedition to the South Pole in 1929. The base and ships were equipped with NRL-designed and fabricated radio gear.¹²

IMPACT

NRL's advances in radio equipment made possible the Navy's adoption of that part of the radio-frequency spectrum known as the HF band (2 to 30 MHz). That technological advance had a profound effect on naval communications for the next 50 to 60 years.

PRIMARY REFERENCE DOCUMENTS

- Crossley, A., "Piezo-Electric Crystal-Controlled Transmitters," *Institute of Radio Engineers*, January 1927.
- Model RG Receiver, *Naval Radio and Sound Reports*, Project V-6E-26 (1925) and Project V-6E-27 (1927 and 1933).
- "Report of the Shenandoah Flight," *Naval Radio and Sound Reports*, December 1924.

⁹ Gebhard, L.A., *Evolution of Naval Radio-Electronics and Contributions of the Naval Research Laboratory*, NRL Report 8300, 1979, 51.

¹⁰ Ibid., 60.

¹¹ Ibid., 46.

¹² Taylor, A.H., *Radio Reminiscences: A Half Century* (NRL, Washington, DC, 1948), 134-135.

RADIO PROPAGATION AND THE “SKIP-DISTANCE” EFFECT

ACHIEVEMENT

In 1925, NRL discovered the principles governing the “skip-distance” effect, which could not be explained at the time by the prevailing wave-propagation theory. The effect refers to radio signals that disappear after the “ground wave” dissipates but reappear at a considerable distance, varying with frequency, time of day, and even by season, due to reflection off of something high in the atmosphere. This reflecting layer was the ionosphere, a section of the atmosphere that contains charged atoms and ions created by the Sun’s energy. Building upon the work of Anglo-Irish mathematician and physicist Sir Joseph Larmor, NRL’s A. Hoyt Taylor and E.O. Hulburt jointly published in 1926 a modification of the theory that adequately explained the high-frequency “skip-distance” effect and that agreed with the experimental data.¹³

NRL’s work in this area further demonstrated that around-the-world HF transmissions could be obtained through successive reflections from the Earth’s ionosphere with the proper choice of frequency, time of day, and season. Encirclement of the globe as many as three times in the same transmission and in both directions was observed in 1926. At the same time, reflections of the pulsed HF transmissions from Earth surface prominences, currently called “backscatter,” were first observed. These HF “backscatter” observations generated the first concept of detecting and ranging on targets over very long distances.¹⁴ This concept led to the later development of over-the-horizon radar by NRL.

In connection with this high-frequency-propagation work, NRL was also the first to determine the frequency above which radio waves would penetrate the Earth’s atmosphere and propagate to outer space, making radio communication in space possible. Taylor and Hulburt determined that “for radio communication over longer distances, of the interplanetary order, waves shorter than 40 meters would appear to be best able to pierce our own electron atmosphere [ionosphere] as well as that of another planet.”¹⁵ NRL would later develop the world’s first satellite communication system using the Moon as a relay, which was facilitated by the work of Taylor and Hulburt.

IMPACT

NRL’s seminal work in the field of radio propagation laid the foundation for modern HF wave-propagation theory, led to the Navy’s acceptance of HF radio frequencies, which had a profound effect upon naval communications for the next 50 to 60 years, led to the Laboratory’s development of over-the-horizon radar, and led to NRL’s development of the world’s first satellite communication system.

PRIMARY REFERENCE DOCUMENTS

- Taylor, A.H. and Hulburt, E.O., “Wave Propagation Phenomena at High Frequencies,” *Naval Radio and Sound Reports*, September 1925.
- Taylor, A.H., “An Investigation of Transmission on the Higher Radio Frequencies,” *Institute of Radio Engineers*, December 1925.
- Taylor, A.H. and Hulburt, E.O., “The Propagation of Radio Waves Over the Earth,” *Physical Review*, Vol. 27, February 1926.

¹³ Gebhard, L.A., *Evolution of Naval Radio-Electronics and Contributions of the Naval Research Laboratory*, NRL Report 8300, 1979, 43-45.

¹⁴ *Ibid.*, 44.

¹⁵ Taylor, A.H. and Hulburt, E.O., “The Propagation of Radio Waves over the Earth,” 215.

INVENTION OF U.S. RADAR

ACHIEVEMENT

Prior to the development of radar, Navy ships could track other ships or aircraft only by using optical techniques, sound ranging, or primitive radio direction finding. New methods of detection and ranging were necessary. In 1922,¹⁶ while working on radio direction finders for aircraft, A.H. Taylor and L.C. Young noted a distortion of “phase shift” in radio signals reflected from a steamer on the Potomac River. In short, NRL had detected a moving ship by radio waves and, as a result, had discovered the radar principle.¹⁷ Eight years after the initial discovery of the radar principle, NRL scientists observed that reflections of radio waves from an airplane could also be detected.

From 1930 to 1940, NRL explored the use of radio for detection and ranging. In 1933, the use of a pulse technique to detect aircraft and ships was proposed by Young. R.M. Page made major advances over the next few years in the area of transmitters and receivers, eventually developing the highly important “duplexer” in 1936. The duplexer permitted the use of the same antenna for both transmitting and receiving. The pulse technique combined with the duplexer did away with the separate receiving and transmitting antennas that most of the other early radar developers employed. Page and Young received the patents for the duplexer, an invention that dramatically changed the nature of radar in the U.S. and abroad.

IMPACT

NRL invented, developed, and installed the first operational U.S. radar, the XAF, on the battleship USS *New York* in 1939. It was rapidly transferred to industry for production. By the time of the attack on Pearl Harbor, 20 radar units were in operation. Radar of this type contributed to the victories in the Battle of the Coral Sea, the Battle of Midway, and the Battle of Guadalcanal.¹⁸ Among the lessons learned at Coral Sea was that every carrier should be equipped with two long-range radars.¹⁹

The invention of radar and the developments that flowed from it (e.g., monopulse radar and over-the-horizon radar) are among the foundations of modern military power. And, as a sensor for navigation and surveillance, radar plays a major role in the operation of civilian transportation systems, weather forecasting, astronomy, and automation, among other uses.

PRIMARY REFERENCE DOCUMENTS

- U.S. Patents: No. 1,981,884 to Taylor, A.H., Hyland, L., Young L.C., “System for Detecting Objects by Radio,” 1934; No. 2,512,673 to Page, R.M., “Radio Pulse Duplexing System,” 1950; No. 2,688,746 to Page, R.M. and Young, L.C., “Impedance Control Coupling and Decoupling Systems,” 1954.
- R.M. Page, Laboratory Notebook 171, Vol. III, March 1934; letter from NRL to the Bureau of Engineering, June 11, 1936, in File S-S67-5 #1, National Archives Building.

¹⁶ The discovery was made by researchers working for NRL’s predecessor organization, the Naval Aircraft Radio Laboratory (NARL). When the facilities of the new Laboratory became available, the personnel and activities of NARL were transferred to become the major component of NRL’s Radio Division.

¹⁷ For this work, Taylor has been called the “Father of Radar.” [Howeth, L.S., 1963, *History of Communications-Electronics in the United States Navy*, Washington (Chapter XXXVIII, Sec 4) Library of Congress Catalogue Number: 64-62870.

¹⁸ King, E.J., ADM, *U. S. Navy at War: 1941-1945* (Navy Department, Washington, DC, 1946), 226.

¹⁹ *The Battle of the Coral Sea*, Office of Naval Intelligence, Washington, DC, 1943.

FIRST OPERATIONAL U.S. SONAR

ACHIEVEMENT

The submarine came into its own during World War I, most notably in anti-commerce warfare. Ever since, the world's navies have had a keen interest in undersea warfare. The German U-boats, though primitive by even World War II standards, were a deadly new technology. Given the state of knowledge about sound propagation, there was little that could detect or counter them while submerged. The U-boat fleet destroyed an estimated 5,708 merchant and fishing vessels with a loss of about 15,000 sailors by the war's end.²⁰ The sinking of the RMS *Lusitania*, which claimed 1,198 lives, including 123 American civilians, would play a role in the U.S. declaration of war on Germany in April 1917.

Underwater acoustic research was started by the U.S. Navy in 1917 with a small group at the U.S. Naval Experimental Station in New London, Connecticut. This group, headed by H.C. Hayes, was eventually moved to NRL on its opening in 1923.

Hayes and his colleagues decided that the passive sonic devices used in World War I were seriously limited in the detection of enemy submarines. It was their belief that *active* echo-ranging sonar would provide the best antisubmarine warfare system for surface ships. This approach was taken from the start of the new Sound Division at NRL, where practically all of the U.S. Navy's R&D in sonar prior to World War II was carried out.²¹

NRL's first effort was to develop an improved quartz-steel transducer. Extensive effort was placed on each of the components of the new sonar system, from the transducers and signal processing to the mechanical mounting and housing functions. Of particular significance was the development of the streamlined sonar dome to house the transducer. The dome enabled surface ships to make attacks at speeds up to 15 knots.

In 1927, a number of U.S. naval vessels conducted tests with the NRL quartz-steel echo-ranging sonar. This was the first practical sonar based on the 1918 demonstration by P. Langevin, a French physicist, of the possibility of echo-ranging or "pinging" at supersonic frequencies.²² A later system, the Echo Detection Equipment Model QB, became the first operational sonar used by the U.S. Navy.²³

IMPACT

Sonar transformed naval warfare by improving the ability of surface ships and submarines to detect and track enemy submarines.

PRIMARY REFERENCE DOCUMENTS

- U.S. Patent No. 2,005,741 to Hayes, H., "Magnetostrictive Sound Generator," June 25, 1935.
- Klein, E., "Notes on Underwater Sound Research and Applications Before 1939," ONR Report ACR-135, September 1967.

²⁰ Clodfelter, M., *Warfare and Armed Conflicts: A Statistical Encyclopedia*, (2017, 4th edition), 428.

²¹ Sonar Detector, OPNAV P413-104, Navy Department, Chief of Naval Operations, Washington, DC, 1946; and "Notes on Underwater Sound Research and Applications Before 1939," by E. Klein, ONR Report ACR-135, September 1967.

²² Baxter, III, J.P., *Scientists Against Time* (Little, Brown & Co., Boston, 1946), 171. This book is the brief official wartime history of the Office of Scientific Research and Development.

²³ Stephenson E.B., "Instructions for Echo Detection Equipment Model XQB," NRL Report RA55A227, August 1934.

LIQUID THERMAL DIFFUSION PROCESS

ACHIEVEMENT

NRL was the first research center that General Leslie Groves visited when he took charge of the Manhattan Project in September 1942.²⁴ At that time, the Laboratory had the distinction of being the first U.S. government agency to support uranium research in 1939.²⁵ One result of that support was the first successful separation of uranium isotopes by the *liquid thermal diffusion process*.

The liquid thermal diffusion process was one of the three methods that the Manhattan Project used to obtain the enriched uranium necessary to form the first atomic bombs. In its early stages, the project employed two enrichment methods, but in 1944, the project hit a technical impasse. When the project's technical director, Dr. Robert Oppenheimer, became aware of NRL's research in using liquid thermal diffusion as a method of separating uranium isotopes, he ensured its use in the Manhattan Project.²⁶ In June 1944, the blueprints of NRL's liquid thermal diffusion plant were sent to Oak Ridge, Tennessee, and within three months, the first columns of the Oak Ridge uranium separation plant were in operation. In the spring of 1945, Oak Ridge was producing uranium-235 for the Hiroshima weapon.²⁷

The Laboratory's contribution was accomplished by a team led by P. Abelson at NRL's main site and later at a larger pilot plant built at the Philadelphia Naval Shipyard in 1943.²⁸ Abelson had invented the process earlier with NRL funding while he was employed by the Carnegie Institution of Washington. But by 1941, he had become an NRL employee hired to investigate the scaling up of the process. Abelson also invented the first practical method for making uranium hexafluoride, a key material needed for the process of U-235 separation.²⁹ He would be recognized with the National Medal of Science in 1987 for his "path-breaking contributions in radiochemistry, physics, geophysics, biophysics, and biochemistry and for his vigorous and penetrating counsel on national matters involving science and technology."³⁰

IMPACT

The liquid thermal diffusion process was a significant contribution to the success of the Manhattan Project.

PRIMARY RESEARCH DOCUMENTS

- Ruskin, R.E., "Separation of Isotopes," *NRL Progress Report* (September 1947).
- NRL memorandum, Subj. "Early History of Uranium Power for Submarines," May 1, 1946.

²⁴ Rhodes, R., *The Making of the Atomic Bomb* (Simon & Schuster, Inc., New York, 1988), 551-553.

²⁵ Hewlett, R.G. and Duncan, F., *Nuclear Navy: 1946-1962* (University of Chicago Press, Chicago, 1974), 17; Bowen, H.G. VADM, *Ships, Machinery, and Mossbacks*, (Princeton University Press, 1954), p. 187; Joseph-James Ahern, "'We Had the Hose Turned on Us!' Ross Gunn and The Naval Research Laboratory's Early Research into Nuclear Propulsion, 1939-1946," *International Journal of Naval History*, 2, no.1, 2003.

²⁶ Rhodes, R., *op. cit.*

²⁷ Hewlett and Duncan, 21.

²⁸ Smyth, H.D. "Atomic Energy for Military Purposes," cited in R.E. Ruskin, "Separation of Isotopes," *NRL Progress Report*, September 1947.

²⁹ Rhodes, 550.

³⁰ National Science Foundation data base: "The President's National Medal of Science: Recipient Details," [located at https://www.nsf.gov/od/nms/recipient_details.jsp?recipient_id=11].

AIRCRAFT RADIO HOMING SYSTEM

ACHIEVEMENT

When the first aircraft carriers — the USS *Langley* (CV-1) in 1922, and the USS *Lexington* (CV-2) and USS *Saratoga* (CV-3) in 1928 — became available, there was need for a suitable means of navigating carrier-based planes to and from carriers and air facilities ashore.³¹

To solve this problem, NRL developed an aircraft radio homing system that was installed on all Navy aircraft carriers and their aircraft and that provided the primary means for aircraft to navigate back to their carriers during World War II. NRL's experimental model was installed on the carrier USS *Saratoga*, the flagship of the commander, Aircraft Battle Force, then Admiral E.J. King, in May 1938. After witnessing its performance, King, in a letter to the Navy Department dated August 29, 1938, recommended, "Adopt the (Model YE) system for primary means of homing radio aircraft." As a result, the system was installed on all aircraft carriers and was used extensively in the Pacific during World War II.³²

The homing system had a dual frequency that confused the Japanese admirals, who realized that U.S. aircraft were successful in returning to their carriers but did not understand how this was accomplished. In one reported incident during a battle in the Marianas, in the waning hours of daylight, when American planes followed the stricken enemy nearly to the limit their fuel would permit, most of the planes and their pilots were saved by homing back to their carriers in the dark with this equipment.³³

IMPACT

This system had a major impact upon Pacific combat operations during World War II. The many glowing reports received from combat units and individual pilots whose lives were saved under trying circumstances attested to the importance and value of this NRL development. The British also eventually adopted this system for their carrier aircraft. The system continued in use until it was replaced by the TACAN (Tactical Air Navigation) system in 1960.³⁴

PRIMARY REFERENCE DOCUMENTS

- "Homing Devices for Aircraft," NRL File F42-1/25, 1935-1938, National Archives.
- "Aircraft Homing Devices," NRL File F42-1/69H, National Archives; NRL CRMO.

³¹ Gebhard, L.A., *Evolution of Naval Radio-Electronics and Contributions of the Naval Research Laboratory*, NRL Report 8300 (1979), 271.

³² Ibid, 273

³³ Ibid, 274; Taylor, A.H., *Radio Reminiscences: A Half Century* (Naval Research Laboratory, Washington, DC, 1948), 171.

³⁴ Gebhard, 274.

FIRST PROPOSAL OF A NUCLEAR SUBMARINE

ACHIEVEMENT

The use of nuclear power to propel submarines under water was first proposed by an NRL physicist, R. Gunn, soon after fission was discovered by German researchers in 1939.³⁵ In March 1939, Navy officials, one of whom was Gunn, met with several civilian scientists who felt the military should be made aware of the vast possibilities of nuclear fission. Among the civilian scientists was Enrico Fermi, winner of the 1938 Nobel Prize in Physics. While most of the Navy personnel present at the meeting concentrated their attention on a nuclear weapon, Gunn was conceiving the idea of using nuclear power to drive the world's first nuclear submarine.³⁶

Within a few days after this historic meeting, Gunn had requested and received \$2,000 for preliminary work on the possibility of developing nuclear power for ship propulsion.³⁷ Later, in June 1939, in a memo to the NRL Director, Gunn stated:

“Under certain special circumstances of bombardment by neutrons, the heavy element uranium dissociates into two other elements with the evolution of tremendous amounts of energy which may be converted directly into heat and used in a flash boiler steam plant. Such a source of energy does not depend on the oxidation of organic material and therefore does not require that oxygen be carried down in the submarine if uranium is used as a power source. This is a tremendous military advantage and would enormously increase the range and military effectiveness of a submarine.”

In April 1946, NRL forwarded a report to the Bureau of Ships entitled “The Atomic Energy Submarine,” which concluded that it was considered feasible to construct atomic power plants of a size and output suitable for ship propulsion. This report also marks the first interest in liquid metal coolants for reactors.³⁸

IMPACT

NRL was first to conceive, propose, and investigate the use of nuclear power in submarine propulsion, and through subsequent efforts, the Laboratory contributed to the planning and development of the world's first atomic-powered submarine, the USS *Nautilus*. The nuclear submarine is one of the most formidable weapons systems ever developed.

PRIMARY REFERENCE DOCUMENTS

- Gunn, R., Memorandum for the Director, Subj. “Submarine Submerged Propulsion — Uranium Power Source,” June 1, 1939.
- Abelson, P.H., Ruskin, R.E., and Raseman, C.J., NRL Memorandum to Director, Subj. “Atomic Energy Submarine,” March 28, 1946.

³⁵ Pegram, G.B., to Hooper, Admiral S.C., 16 March 1939, quoted in L. Fermi, *Atoms in the Family: My Life with Enrico Fermi* (University of Chicago Press: Chicago, 1954; H.W. Graf, memorandum for file, 17 March 1939, *AEC*.

³⁶ Hewlett, R.G. and Duncan, F., *Nuclear Navy: 1946-1962* (University of Chicago Press, Chicago, 1974), 16.

³⁷ NRL Memorandum, “Early History of Uranium Power for Submarines,” 1 May 1946.

³⁸ Address by Honorable James H. Wakelin, Jr., Assistant Secretary of the Navy for Research and Development, before the 22nd Annual Meeting of the American Power Conference in Chicago, Illinois, 29 March 1960, 9.

PLAN-POSITION INDICATOR

ACHIEVEMENT

When NRL demonstrated the first U.S. radar, the XAF, during fleet exercises in 1939, it was observed that the radar's use could be facilitated by a display presenting a polar-coordinate map. Such a map would indicate the range and bearing of all objects "visible" to the radar. To provide a polar-coordinate map-like display of targets, between 1939 and 1940, NRL originated the radar plan position indicator (PPI) — the well-known radar scope with the round face and the sweeping hand.³⁹ It was developed independently in England and in the U.S. when neither country knew of the work in the other country.⁴⁰

The PPI was an efficient means of display for many reasons, not least because many radar antennae were large, slow turning structures and the phosphorescent flashes of radar reflections were quickly there and gone again. As NRL's R.M. Page wrote, it "was not possible for the eye or the mind to retain or remember all the flashes in their correct positions for one complete rotation."⁴¹ As is necessary for any such sensor readout, the data needed to be usable by a human, so NRL deployed a colored filter with a mix of phosphor types on the PPI screen. With this system, the radar blips persisted from sweep to sweep of the antenna.

NRL's PPI was first utilized in the experimental model of the SG radar, which was installed and demonstrated on the destroyer USS *Semmes* in April 1941. The Model SG (developed by The Radiation Lab and Raytheon) became the fleet's first radar to be equipped with the NRL-developed PPI display. Nearly 1,000 Model SG radars were produced during World War II and many remained in service for nearly two decades.⁴² The PPI would become particularly useful when "combat information centers" were established aboard command vessels in the fleet.⁴³

IMPACT

The PPI is now universally used by military and commercial interests of the world for the display of radar information for such functions as air and surface detection, navigation, aircraft traffic control, air intercept, and object identification.

PRIMARY REFERENCE DOCUMENTS

- "Report of Progress Problem W5-2S," NRL letter to Bureau of Engineering, S-S67/36, ser. 135, February 26, 1940, National Archives.
- U.S. Patent No. 2,779,939 to Page, R.M., "Indicating Systems," January 1957.

³⁹ Gebhard, L.A., *Evolution of Naval Radio-Electronics and Contributions of the Naval Research Laboratory*, NRL Report 8300, (1979), 193.

⁴⁰ Page, R.M., *The Origin of Radar* (Doubleday & Company, Inc, New York, 1962), 156.

⁴¹ Page, 155. For more about Page, see: Merrill I. Skolnik, "Robert Morris Page [Obituary], *Physics Today*, v. 46, no. 4, 1993, 76; doi: 10.1063/1.2808883.

⁴² Gebhard, 187.

⁴³ Taylor, A.H., *The First Twenty-Five Years of the Naval Research Laboratory* (NAVEXOS P-549), 68.

IDENTIFICATION FRIEND-OR-FOE SYSTEMS

ACHIEVEMENT

In the 1930s, neither the Army nor the Navy had a device that could adequately identify targets on the ground, at sea, or in the air, particularly in overcast weather and at night. Identifying friendly planes returning to carriers under poor visibility was an especially serious problem.

NRL developed the first U.S. radio recognition identification friend-or-foe (IFF) system, the Model XAE, in 1937. This system provided coded transmissions from aircraft, which were received for identification aboard ship and transmitted back to aircraft for verification. In 1939, NRL devised the first U.S. IFF system in which radar pulses received by a target ship or aircraft were repeated back to the radar and displayed as a pulse associated with the echo pulse on the scope. As part of this system, NRL's R.M. Page developed the first U.S. pulse transponder, basic to pulse IFF systems and pulse beacon systems.⁴⁴

In 1940, NRL developed the Mark IV IFF system, the first to provide a means for target isolation in azimuth as well as range. The Mark IV was used operationally in the Pacific theater.⁴⁵ In 1942, NRL was designated leader of the U.S.-U.K.-Canadian scientific effort to develop the next-generation Mark V IFF.⁴⁶ The Mark V incorporated many important NRL features, greatly reducing the time needed to identify a target, increasing transponder range, and improving isolation of targets in azimuth. After the war, NRL adapted the Mark V to track jet aircraft. This became known as the Mark X, essential because it reduced fratricide when using beyond-visual-range weapons.

By 1958, the Federal Aviation Administration established the Air Traffic Control Radar Beacon System, essentially the civilian version of the Mark X. The International Civil Air Organization later adopted the system, making the Mark X the basis of the world's air traffic control system. NRL's work, as well as the work of institutions such as the Air Force Cambridge Lab, led to the Mark XII IFF system in 1960.⁴⁷ This was the first system to use cryptographic techniques to prevent deception in which an enemy appears as a friend by using a captured transponder (the device giving the "yes" answer to interrogations).

IMPACT

NRL's successive IFF systems met urgent operational requirements for the U.S. and Allies' armed forces to discriminate friendly units from enemy units. In subsequent developments, the Mark X impacted U.S. and allied armed forces, as well as national and world civil airways, and the cryptographic Mark XII essentially nullified the threat of deception by an enemy using captured IFF transponders.

PRIMARY REFERENCE DOCUMENTS

- U.S. Patent No. 3,143,733 to Page, R.M., "Automatic Range and Bearing Follow-up System," August 1964.
- Cleeton, C.E., "Proposed System of Electronic Recognition," NRL P-3131, June 1947, National Archives.
- Cleeton, C.E., "Coding and Security of Electronic Recognition and Identification Systems," NRL Report 2972, September 12, 1946.

⁴⁴ Gebhard, L.A., *Evolution of Naval Radio-Electronics and Contributions of the Naval Research Laboratory*, NRL Report 8300, (1979), 251.

⁴⁵ *Ibid.*, 254-55; and Brown, L. *A Radar History of World War II: Technical and Military Imperatives*, (Institute of Physics Publishing, Washington, D.C., 1999), 131-132.

⁴⁶ Gebhard, 256.

⁴⁷ *Ibid.*, 259.

MONOPULSE RADAR

ACHIEVEMENT

To overcome the angle measurement limitations of existing radars, NRL developed the first monopulse radar in 1943. As the name implies, the monopulse technique makes angle measurements on each received pulse. This new type of radar provided a tenfold improvement in angular accuracy over prior systems.⁴⁸ Ideal for tracking maneuvering targets, monopulse radar is now the basis for all modern tracking and missile-control radars. While the concept for monopulse radar was also independently developed elsewhere, the Laboratory's R.M. Page holds the U.S. patent on this technique.

The monopulse technique was first applied to the Nike-Ajax missile system, which was the nation's continental air defense system. The radar of this system was patterned after NRL's experimental model. NRL's work eventually led to the AN/FPS-16, developed jointly by NRL and RCA, which was the first radar designed to support test missile tracking. As part of this work, NRL researchers achieved another first, feeding AN/FPS-16 tracking data directly into an IBM 709 computer, which, in turn, drove plotting boards in Central Control.⁴⁹ In this manner, they tracked the launches of the first U.S. space satellites, *Explorer I* and *Vanguard I*, at Cape Canaveral in 1958.

After additional improvements to provide a more compact and efficient monopulse antenna feed and lobe comparison waveguide circuitry, monopulse tracking radar became the generally accepted tracking radar system for military and civilian agencies, such as the National Aeronautics and Space Administration (NASA) and the Federal Aviation Administration (FAA), and remains in wide use today.

IMPACT

The invention of monopulse (simultaneous lobing) tracking radar was a breakthrough in precision target tracking. Monopulse radar performance is critical to gunfire control, missile guidance, missile-range precision launch, range safety, space vehicle tracking, FAA civil aircraft landing systems, Navy aircraft carrier landing systems, and target recognition.

PRIMARY REFERENCE DOCUMENTS

- Page, R.M., "Accurate Angle Tracking by Radar," NRL Report RA-3A-222A, December 28, 1944.
- U.S. Patent No. 2,929,056 to Page, R. M., "Simultaneous Lobing Tracking Radar," March 1960.

⁴⁸ Gebhard, L.A., *Evolution of Naval Radio-Electronics and Contributions of the Naval Research Laboratory*, NRL Report 8300, (1979), 200.

⁴⁹ Green, C. M. and Lomask, M. *Project Vanguard: The NASA History*, NASA SP-4202, 161-162.

FIRST AMERICAN AIRBORNE RADAR

ACHIEVEMENT

Prior to the entry of the U.S. into World War II, and in anticipation of having to contend with the German submarine menace, NRL developed the U.S.'s first operational airborne radar (the Model ASE) followed by what became the first widely used U.S. airborne radar (the Model ASB). For the ASE, NRL modified the UK Model ASV Mark II radar, replacing its cumbersome antenna system with an NRL design, greatly increasing potential airspeed. Hundreds of NRL ASE radars were used as standard equipment on PBY flying boats, yet were ill-suited for the torpedo bomber TBF Avengers.

By the time the ASE was adopted for use, NRL already had its own 60-cm air-surface radar, the ASB, in development. When completed, the Model ASB became the first radar used in carrier-based aircraft.⁵⁰ It proved far superior to the ASE, in part because it featured a higher frequency and an even smaller, lighter antenna system.

The ASB became known as the radar that fought the war from the air in the Pacific. It was the first operational U.S. airborne radar widely used for bombing, detection of ships and surfaced submarines, and airborne interception. As the first radar to be used in carrier-based aircraft, the ASB was employed in attacking and destroying Japanese ship convoys in the Pacific.⁵¹ It was also very effective against submarines because it tremendously widened the area that could be covered by patrol planes.⁵²

IMPACT

The ASB radar saw extensive use during World War II, not just by the U.S. Navy and the Army Air Corps, but also by the British military. It was installed almost universally in U.S. naval aircraft and became known as the “workhorse of naval aviation.” Between 1942 and 1944, more than 26,000 units were procured, the largest procurement of any model radar during the war.⁵³ Experience with this type of radar led to NRL's involvement in the UHF E2 Airborne Early Warning Radar, microwave interception radar, and antisubmarine warfare periscope detection radars.

PRIMARY REFERENCE DOCUMENTS

- “Airborne Radar,” NRL File S-F42-5, May 1941-December 1942, National Archives.
- Taylor, A.H., *The First Twenty-Five Years of the Naval Research Laboratory* (NAVEXOS P-549).

⁵⁰ Brown, L. *A Radar History of World War II: Technical and Military Imperatives*, (Institute of Physics Publishing, Washington, D.C., 1999), 371.

⁵¹ Page, R.M., *The Origin of Radar* (Doubleday & Company, Inc, New York, 1962), 173.

⁵² Taylor, A.H., *The First Twenty-Five Years of the Naval Research Laboratory* (NAVEXOS P-549), 215.

⁵³ Gebhard, L.A., *Evolution of Naval Radio-Electronics and Contributions of the Naval Research Laboratory*, NRL Report 8300, (1979), 201.

FIRST FAR-ULTRAVIOLET SPECTRUM OF THE SUN

ACHIEVEMENT

In September 1945, one leading astronomer confided in another, “If anyone asked you what technological development could, at one stroke, make obsolete almost all of the textbooks written in astronomy, I am sure your answer and mine would be the same, namely, the spectroscopy of the sun outside the earth’s atmosphere.”⁵⁴

With their wartime experience in research areas as varied as optics, atmospheric scattering, night vision, and optical reconnaissance, NRL physicists such as R. Tousey were prepared to become world leaders in the design of high-altitude spectrographic equipment.⁵⁵ In 1946, using a captured German V-2 rocket, NRL scientists obtained the first far-ultraviolet spectrum of the Sun from beyond the Earth’s atmospheric boundary. NRL was not alone in the early attempts to measure the solar ultraviolet spectrum, as Johns Hopkins University’s Applied Physics Laboratory obtained excellent results only six months after NRL.⁵⁶

The successful flight of October 10, 1946, carried cosmic ray detectors, pressure and temperature gauges, radio transmitters, and antennae to measure propagation through the ionosphere, as well as a spectrograph.⁵⁷ Although earlier flights had returned scientific data revealing cosmic-ray counts and pressure and temperature information, the successful retrieval of an ultraviolet spectrum of the Sun captured the attention of both the scientific and popular press. The *Washington Post* heralded the discovery of the “new ultraviolet” and reproduced samples of two spectra on page one. The *New York Times*, the *Times Herald*, and the *Washington Star* all followed suit.⁵⁸

IMPACT

Scientifically, NRL had extended the known spectrum of the Sun and produced spectra revealing the degree of ozone absorption in the UV. This achievement also marked the birth of space-based astronomy and the U.S. Navy’s space program.

PRIMARY REFERENCE DOCUMENTS

- Baum, W.A., Johnson, F.S., Oberly, J.J., Rockwood, C.C., Strain, C.V., and Tousey, R., “Solar Ultraviolet Spectrum to 88 Kilometers”, *Physical Review*, vol. 70, Issue 9-10, pp. 781-782 (1946).
- Durand, E., Oberly, J.J., and Tousey, R., “Solar Absorption Lines Between 2950 and 2200 Angstroms”, *Physical Review*, Vol. 71 (1947).
- Tousey, R., “Solar Spectroscopy from Roland to SOT,” *Vistas in Astronomy*, Vol. 29 (1986).

⁵⁴ Goldberg, L. to Menzel, D., quoted in DeVorkin, D.H., *Science with a Vengeance* (Springer-Verlag, New York, 1992), 207.

⁵⁵ DeVorkin, 207; Hufbauer, K. *Exploring the Sun: Solar Science since Galileo* (Johns Hopkins University Press, Baltimore, 1991), 139.

⁵⁶ Friedman, H., “Reminiscences of 30 Years of Space Research,” NRL Report 8113, August 1977.

⁵⁷ Newell, H.E. and Siry, J.W., eds., “Upper Atmosphere Research Report No. II,” NRL Report R-3030, 30 December 1946.

⁵⁸ DeVorkin,, 143-144.

FIRST DETECTION OF X-RAYS FROM THE SUN

ACHIEVEMENT

With the launch of an experiment aboard a V-2 rocket on September 29, 1949, NRL directly confirmed that X-rays from the Sun are a principal cause of ionization in the E region of the Earth's ionosphere.⁵⁹ Additional experiments, aboard a Viking rocket flight and two Aerobee firings, later indicated that the solar X-ray spectrum is adequate to account for all of E-layer ionization.⁶⁰ This pioneering research opened the field of solar X-ray astronomy that the Laboratory explored so extensively in the 1950s and thus contributed profoundly to the understanding of the physical processes in the solar atmosphere. A practical benefit of this research includes the improved understanding of the effects of solar disturbances on radio communication and an improved ability to predict the influence of solar particle emissions on the radiation environment of manned spaceflight.

NRL's H. Friedman led the Laboratory's pioneering efforts in X-ray astronomy. In 1969, he received the National Medal of Science, the U.S.'s highest honor for scientific achievement, for "pioneering work in rocket and satellite astronomy and in particular for his contributions to X-ray astronomy." Later, in honor of this work, he received the coveted Wolf Foundation Prize for Physics in 1987. The Wolf Prize committee recognized Friedman and the other two co-recipients of the award as:

"... the principal founders of X-ray astrophysics, a new field of astronomical science which has proven to be a prolific source of fundamental discoveries and deeper physical understanding about high-energy processes in the universe. Their work has profoundly influenced every area of astronomical research."

IMPACT

The first detection of X-rays from the Sun⁶¹ marked a major milestone in NRL's continuing endeavor — beginning with E.O. Hulburt's theoretical efforts in the late 1920s, continuing through the SOLRAD satellite series and other satellite programs — to determine the source of the radio-reflecting layer.⁶² Observations of solar X-ray emissions are now used to predict the state of the ionosphere and its effect on radio propagation, especially at the HF frequencies. NRL's increasingly refined understanding of the ionosphere has aided in naval communications on Earth and in space, has improved missile and satellite tracking, has improved telemetering of data from rockets and satellites, played a crucial role in the operation of high-frequency direction finder systems used to track Soviet submarines, and helps to predict the effects of ionospheric scintillation on GPS satellites.

PRIMARY REFERENCE DOCUMENTS

- Tousey, R., Watanabe, K., and Purcell, J.D., "Measurements of Solar Extreme Ultraviolet and X-Rays from Rockets by Means of a CoSO₄:Mn Phosphor", *Physical Review*, 83, 792-797 (1951).
- Friedman, H., Lichtman, S.W., and Byram, E.T., "Photon Counter Measurements of Solar X-Rays and Extreme Ultraviolet Light," *Physical Review*, Vol. 83, 1025-1030 (1951).
- Byram, E.T., Chubb, T.A., and Friedman, H., "The Contributions of Solar X-Rays to E-layer Ionization," *Physical Review*, Vol. 92, 1066-1067 (1953).

⁵⁹ DeVorkin, D.H., *Science with a Vengeance* (Springer-Verlag, New York, 1992), 240.

⁶⁰ Hevly, B.W., *Basic Research Within a Military Context: The Naval Research Laboratory and the Foundations of Extreme Ultraviolet and X-Ray Astronomy* (Johns Hopkins University, 1987), 224.

⁶¹ "Minutes of the Meeting at Washington, April 28-30, 1949", *Physical Review*, Vol. 76, 165 (1949).

⁶² Hulburt, E.O., "Ionization in the Upper Atmosphere of the Earth," *Physical Review*, Vol. 31, 1018 (1928).

PRINCIPLES OF FRACTURE MECHANICS

ACHIEVEMENT

Fracture mechanics is a field that recognizes that all structures are manufactured with, or will ultimately contain, flaws that govern the eventual failure of the structure. The study of the stresses caused by the flaws, and the material's resistance to failure from them, forms the basis for the field of fracture mechanics. Fracture mechanics permitted, for the first time, the capability to calculate the strength of structures containing defects, which inevitably occur in fabrication or during service operation. The net result of these new design principles increased the reliability of structures due to improved design capability and an improved predictive capability of in-service damage.

NRL's G.R. Irwin is recognized as the pioneer of modern fracture mechanics.⁶³ He developed the scientific principles for understanding the relationships between applied stresses and cracks or other defects in metallic materials. About 1947, Irwin developed the concept that fracture toughness should be measured in terms of resistance to crack propagation. Critical values of the stress intensity describing the onset of fracture, the commencement of environmental cracking, and the rate of fatigue crack growth were established later. Using these principles, NRL assisted in the solution of critical military and commercial problems, such as catastrophic failures in commercial jet aircraft in 1953 and fracture problems experienced by the Polaris and Minuteman missile programs in 1957.⁶⁴

A more recent example arose in 1996 when a titanium alloy was considered for the USS *Seawolf*'s muzzle and breech doors instead of the usual steel. Scientists from NRL and the Office of Naval Research were tasked to investigate. They determined that the proposed titanium alloy posed a "risk of unstable, catastrophic failure at the pressure hull boundary."⁶⁵ NRL's early work in the 1960s that quantified the sensitivity of titanium alloys to stress-corrosion cracking in seawater formed a basis for the panel's findings.⁶⁶ The Navy implemented the panel's proposals.⁶⁷

IMPACT

As a consequence of NRL's pioneering work, fracture mechanics is taught in many graduate schools and remains an active field of R&D today. The principles of this scientific field has been applied throughout the world for the design of any structures where sudden, catastrophic failure would cause loss of life or other serious consequences. Examples include nuclear reactor pressure vessels, submarines, aircraft and missiles, and tanks for storage of toxic or flammable materials.

PRIMARY REFERENCE DOCUMENTS

- Irwin, G.R., "Fracture Dynamics," *Fracturing of Metals* (ASM, Cleveland, 1948), 147-166.
- Irwin, G.R., Kies, J.A., and Smith, H.L., "Fracture Strength Relative to Onset and Arrest of Crack Propagation," *Proceedings of the ASTM*, Vol. 58, 640 (1958).
- Irwin, G.R., "Fracture Mechanics," in *Structural Mechanics* (Pergamon Press, 1960), 560-574.

⁶³ Rossmanith, H.P., "George Rankin Irwin - The Father of Fracture Mechanics," presented at the George R. Irwin Symposium on Cleavage Fracture, *The Minerals, Metals & Materials Society*, 1997.

⁶⁴ *Ibid.*, 19-20; and Irwin, G.R., "Fracture Mechanics," *Report of NRL Progress*, NRL (1973), 36.

⁶⁵ ONR Report, "Use of Titanium for SEAWOLF Torpedo Tube Breech and Muzzle Doors," 28 May 1996.

⁶⁶ Judy, R.W. and Goode, R.J., *Stress-Corrosion Cracking Characteristics of Alloys of Titanium in Sea Water*, NRL Report 6564 (21 July 1967).

⁶⁷ ASN (RDA) Memorandum, "Use of Titanium for SEAWOLF Torpedo Tubes," 19 September 1996.

MOLECULAR STRUCTURE ANALYSIS AND THE NOBEL PRIZE

ACHIEVEMENT

NRL has produced two Nobel Laureates, J. Karle and H. Hauptman, who each received the Nobel Prize for Chemistry in 1985 for devising direct methods employing X-ray diffraction analysis in the determination of crystal structures. The seminal research paper, “The Phases and Magnitudes of the Structure Factors,” was published in 1950. The major events leading to the development and adoption of these new methods were: quantitative molecular structure analysis in 1948, foundation mathematics for the X-ray phase problem in 1949, and the first general procedure for solving crystal structure problems in 1963.⁶⁸ As experience with applications developed, I. Karle made a major contribution to the development of analytical techniques of broad applicability to all types of crystals, whether they had a center of symmetry or not. It was a considerable step to bridging the gap between theory and practical application.

X-ray diffraction analysis involves the determination of the arrangement of atoms in crystals from which the molecular formula is derived directly. Determination of the molecular structure is important in that once the structural arrangement is understood, the substance can then be synthesized to produce useful products. This research occupies an almost unique position in science because the information it provides is used continuously in other fields. In fact, many phenomena in the physical, chemical, metallurgical, geological, and biological sciences are interpretable in terms of the arrangements of atoms.

In 2009, President Obama congratulated Drs. I. and J. Karle on their combined 127 years of federal service:

“The reputation of the Naval Research Laboratory, as one of the preeminent research facilities in the world, was certainly enhanced by your work even as its strong creative environment nurtured your efforts. That relationship testifies to the idea that the pursuit of fundamental knowledge lies at the heart of technological progress, national security, and international leadership, and it exemplifies the importance of the Defense Department’s cadre of career civilian scientists.”⁶⁹

IMPACT

Methodologies for determining molecular structures are major contributions to science and technology. For example, they form the basis for the computer packages used worldwide for the analysis of more than 10,000 new substances each year. They have applications to public health, including the identification and characterization of potent toxins found in animals and plants, antitoxins, heart drugs, antibiotics, antiaddictive substances, anticarcinogens, etc. And they support the Navy’s energetic materials program, which focuses on making explosives and propellants that are safer, more powerful, or both.

PRIMARY REFERENCE DOCUMENTS

- Karle, J. and Hauptman, H., “The Phases and Magnitudes of the Structure Factors,” *Acta Crystallographica*, Vol. 3, 181 (1950). (The mathematical foundation.)
- Karle, J. and Karle, I.L., “The Symbolic Addition Procedure for Phase Determination for Centrosymmetric and Noncentrosymmetric Crystals,” *Acta Crystallographica*, Vol. 21, 849 (1966). (The foundation for practical application.)
- Karle, J., “Recovering Phase Information from Intensity Data,” (Nobel Lecture), *Chemica Scripta*, Vol. 26, 261 (1986).

⁶⁸ Karle, I.L. and Karle, J., “Recollections and Reflections,” in *Crystallography in North America*, D. McLachlan, Jr., and J.P. Glusker, eds., 1983.

⁶⁹ Letter from President Barack Obama to Drs. I. and J. Karle, 20 July 2009.

THE VIKING SOUNDING ROCKET PROGRAM

ACHIEVEMENT

In 1946, NRL undertook design of a sounding rocket in close collaboration with their contractor, Glenn L. Martin Company. The Viking sounding rocket was the first rocket designed for essentially research purposes, and it was the first to use attitude control provided by an NRL-designed gimbaled motor for steering and intermittent gas jets for stabilizing the vehicle after the main power cutoff.⁷⁰ These attributes are now used extensively in large steerable rockets and space vehicles. The Viking engine was one of the first large liquid-propelled rocket engines produced in the U.S.

NRL launched a total of fourteen Viking rockets between 1949 and 1957. Viking 4 demonstrated that such a rocket could be handled operationally and was launched from a ship, the USS *Norton Sound*, achieving an altitude of 106.4 miles.⁷¹ Launching such a large rocket from the deck of a ship had very important national security ramifications in that it was a step toward the eventual deployment of missiles at sea. In fact, *Life* magazine reported that Navy officials had “proved for the first time that big rockets, capable of carrying A-bombs several hundred miles, could be launched from the deck of a ship.”⁷²

Viking 7 achieved the highest measurement of atmospheric density and atmospheric winds (136 miles peak altitude). Viking 10 took the then-highest measure of positive ion composition and the highest exposure of cosmic ray emulsions (superseded by Viking 11, which reached a record peak altitude of 158 miles).⁷³ In 1954, Viking 12 (on display at the Smithsonian Air and Space Museum) reached an altitude of 144 miles and took the then-highest-altitude photographs of the Earth.

IMPACT

Methods for tracking, telemetering data, and rocket design had all been honed in NRL’s decade of sounding rocket research. In many ways, Viking paved the way for the historic Vanguard project, America’s first satellite program. Today, sounding rockets remain a critical platform used to establish the space readiness of satellite instruments and critical platforms for upper atmospheric research.

PRIMARY REFERENCE DOCUMENTS

- Rosen, M. W. and Bridger, J. M., “Rocket Research Report No. 1: the Viking No. 1 Firings,” NRL Report 3583, 1949.
- Rosen, M.W., *The Viking Rocket Story* (Harper & Brothers, New York, 1955).
- Newell, H. E., *Sounding Rockets* (McGraw-Hill Book Co., New York, 1959).

⁷⁰ Caiden, M., *Vanguard!* (E.P. Dutton & Co. New York, 1957), 138.

⁷¹ Glaeser, “Space: A New Dimension in Naval Warfare,” *U.S. Naval Institute Proceedings*, Vol 113, 132 (May 1987).

⁷² “Seagoing Rocket,” *Life* (26 June 1950)

⁷³ “Table 1 Performance Data,” Record Number 006624 Stewart Committee Vanguard, NASA Historical Records Center, NASA Headquarters, Washington, D.C. and Rosen, *The Viking Rocket Story* (Harper & Brothers, New York, 1955), 234-236, and Newell, H. E., *Sounding Rockets* (McGraw-Hill, New York, 1959), 235-242.

SYNTHETIC LUBRICANTS

ACHIEVEMENT

Soon after the introduction of gas turbine-powered aircraft in World War II, it became evident that new and better lubricants were required to take advantage of the potential capabilities of these engines. The new lubricants would have to retain sufficient viscosity to support bearing loading at 280° to 300° F and to be stable enough oxidatively and thermally to withstand heat “soak back” temperatures of from 400° to 500°F. Because of NRL’s previous success in developing synthetic lubricants for instrument bearings, the Navy Bureau of Aeronautics requested in 1947 that it undertake the development of lubricating oils for turbojet and gas turbines.

Responding to this request, W.A. Zisman, C.M. Murphy, and their colleagues conducted fundamental studies that related molecular structure to lubricating and temperature/viscosity properties. Structural guides derived from those fundamental studies permitted extending the useful temperature range of the oils.⁷⁴ As a result, NRL developed the first hydrocarbon ester fluids as lubricants that would perform acceptably at the high bearing operating temperatures in jet engines.

By the early 1950s, diester lubricants developed at NRL were in use in Navy turbine engine aircraft and soon were used by nearly all military and civilian turbine-powered aircraft. As turbine engine power requirements and operational temperatures increased, NRL was active in developing lubricants and lubricant additives to meet these more stringent conditions as well.

In addition to extending the high temperature range, instrument oils were developed for service at -65°F to overcome the problem of aircraft cannon freezing at the high altitudes that were newly reachable by jet aircraft at the time of the Korean War.⁷⁵

IMPACT

The U.S. military needed new lubricants to be able to utilize turbine aircraft at their maximum performance, especially in combat. NRL research met this requirement. Essentially all turbine engines now used by military and civilian aircraft are lubricated with ester oils whose development was based on early research and development at NRL.

PRIMARY REFERENCE DOCUMENTS

- Bried, E.H., Kidder, H.F., Murphy, C.M., and Zisman, W.A., “Synthetic Lubricant Fluids from Branched-Chain Diesters, Physical and Chemical Properties of Pure Diesters,” *Industrial and Engineering Chemistry*, Vol. 39 (1947).
- Murphy, C.M. and Zisman, W.A., “Structural Guides for Synthetic Lubricant Development,” *Industrial and Engineering Chemistry*, Vol. 42 (1950).
- Zisman, W.A., “Historical Review of Lubricants and Lubrication,” in *Synthetic Lubricants*, R.C. Gunderson and A.W. Hart, eds. (Reinhold Publishing, 1962), Chapter 2.

⁷⁴ American Chemical Society, *Langmuir*, Vol. 3, No. 3 (1987).

⁷⁵ *Ibid.*

RADAR ABSORBING MATERIALS AND ANECHOIC CHAMBERS

ACHIEVEMENT

Since the end of World War II, NRL has pioneered the development and production capabilities for thin magnetic radar-absorbing materials (RAM), thicker nonmagnetic RAM, and designs for radar anechoic chambers. In 1945, the “NRL Arch” apparatus was constructed to provide a means for measuring angular-dependent performance of broadband RAM. The name “NRL Arch” is still used, and the apparatus is accepted worldwide by RAM manufacturers and stealth technology contractors. In 1953, NRL developed a broadband, nonmagnetic material called “DARKFLEX,”⁷⁶ the precursor to materials used in today’s radar anechoic chambers. NRL initiated a pilot production plant, then transferred large-scale production to Sponge Rubber Products Company. Also in 1953, NRL assembled the first effective radar anechoic chamber. The design and elements of it are contained in most chambers today.

The fundamental mechanisms of absorption by magnetic ferrites and alloys were extensively investigated at NRL by a group headed by G. Rado. The understanding of these fundamental mechanisms (magnetic moment rotation, domain wall displacement, and spin-waves) allowed the development of broad bandwidth frequency coverage, thin magnetic RAM. This led to the NRL project “NEWBOY,” initiated in 1976. Thin RAM materials from this project were extensively used by the Joint Cruise Missile Program Office and the other services as prototype stealth treatments for missile-like drones, aircraft, and ships.

IMPACT

After more than seven decades, NRL continues to be a resource for RAM innovation, prototype production, and measurement tools/facilities. In fact, NRL developed, produced, and in several instances installed materials on Navy/DoD platforms from the end of World War II through Operation Desert Storm. Much of NRL’s work preceded efforts on “stealth” technology and significantly impacted it in the areas of submarines, missiles, aircraft, ships, and land vehicles.

PRIMARY REFERENCE DOCUMENTS

- Wright, R.W., et al., “K-Band HARP,” NRL Report R- 3112, July 1947.
- Rado, G.T., Wright, R.W., and Emerson, W.H., “Ferromagnetism at Very High Frequencies III,” *Physical Review*, Vol. 80 (October 1950).
- Simmons, A.J. and Emerson, W.H. “An Anechoic Chamber Making Use of a New Broadband Material,” NRL Report 4193, July 1953.
- Emerson, W.H., et al., “Broadband Absorbing Materials,” *Tele-Tech and Electronics Industries Magazine*, Vol. 74, November 1955.
- Faraday, B.J. and Vittoria, C., eds. “Project NEWBOY - A Progress Report,” NRL Memorandum Report 4589, August 1981.

⁷⁶ Tanner, H.A., Sands, A.G., and McDowell, M.V., “DARKFLEX-A Fibrous Microwave Absorber,” NRL Report 4137, April 1953.

OVER-THE-HORIZON RADAR

ACHIEVEMENT

During the late 1940s, NRL foresaw the need for detecting moving targets, including aircraft and missiles, at distances and altitudes below the visual horizon. The coverage of microwave radar, as developed during World War II, is limited by the curvature of the Earth. In 1950, while using the pioneering propagation work it performed in 1926 (radio “skip distance” effect theory), NRL began to investigate the use of radar operating in the high-frequency (HF, or shortwave) portion of the radio spectrum to extend the range beyond the horizon. This is achieved by the refraction (bending) of radar waves when traveling through the ionosphere, which is located high above the Earth’s surface. Using the ionosphere to bend the radar energy back to the Earth’s surface can extend the range of a radar out to 2,000 nautical miles.

By 1955, NRL was operating a HF pulse doppler radar called MUSIC (Multiple Storage Integration Correlation). MUSIC was eventually able to detect missile launchings at ranges up to 600 nautical miles and atomic explosions up to 1,700 nautical miles. With the use of a bank of Reed filters, it could display multiple aircraft targets.⁷⁷

In 1961, based on the success with MUSIC, a high-power, large-antenna OTH radar known as MADRE (Magnetic Drum Radar Equipment) was installed at the NRL Chesapeake Bay field site. It was able to detect and track aircraft as they traveled across the Atlantic Ocean. With the NRL MADRE experimental radar, nearly all the fundamental capabilities of HF OTH radar were discovered and demonstrated: aircraft detection and tracking, ship detection, missile launch detection, nuclear test location, sea state determination, storm tracking, and vectoring intercepting aircraft.

IMPACT

NRL’s development of OTH radar solved a critical military requirement where the horizon limit of conventional radar was overcome, giving an order-of-magnitude-or-more increase in useful range. This technology provided the technology base that led to the Air Force’s AN/FPS-118 radar for continental air defense and the Navy’s AN/TPS-71 Relocatable Over-the-Horizon Radar. It also influenced HF radar development in other countries. HF OTH radar remains the most cost-effective wide-area sensor available and, as a result, is enjoying a renaissance enabled by signal processing advances.⁷⁸

PRIMARY REFERENCE DOCUMENTS

- Page, R.M. and George, S.F., “Magnetic Drum Storage Applied to Surveillance Radar,” NRL Report 4878, January 1957.
- Headrick, J.M., et al., “MADRE Detection of Aircraft and Missiles Using Narrow-Band Spectrum Analysis After Backscatter Rejection,” Proceedings of the ARPA Meeting of October 17, 1961,” Stanford Research Institute Contract SD-66, under ARPA Order 90, SRI-1-275, October 1961.

⁷⁷ Gebhard, L.A., *Evolution of Naval Radio-Electronics and Contributions of the Naval Research Laboratory*, NRL Report 8300, (1979), 216.

⁷⁸ Headrick, J.M., “Looking Over the Horizon,” *IEEE Spectrum*, July 1990.

HIGH-RESOLUTION RADAR

ACHIEVEMENT

High-resolution radar is important in many areas of radar. It allows the recognition of targets and the exclusion of unwanted clutter echoes so that small stationary or slowly moving targets can be detected in heavy clutter. The need for high range resolution to detect periscopes was recognized in the late 1940s.

NRL began to explore high-resolution radar for periscope detection and other applications in the mid-1950s. The first high-resolution pulse-compression radars were being developed at that time, thereby demonstrating that the energy of a long pulse could be obtained along with the resolution of a short pulse. Although not alone in this area, NRL was active in advancing the art of pulse compression. Other key contributions were made by MIT Lincoln Laboratory and Bell Labs.

In 1960, NRL embarked on a major effort to demonstrate X-band high-range-resolution radar technology for periscope detection and the detection of surface effects generated by a submerged submarine. This was called Project Cutwater. NRL successfully demonstrated both surface and airborne radar for the detection of submarines. In 1965, the Naval Air Systems Command (then the Bureau of Aeronautics) initiated procurement of an antisubmarine warfare (ASW) radar for new S-3 carrier-based aircraft that would employ the technology developed by NRL. Texas Instruments was awarded the contract for the radar that became the AN/APS-116.

IMPACT

NRL's work in high-resolution radar resulted in ASW radars for the U.S. Navy's S-3 and P-3 aircraft. These high-resolution radars were the only operational U.S. radars for submarine detection for more than 30 years and derivative systems remain in service to this day. By developing the means to detect enemy submarines, the Laboratory met a critical national security need.

PRIMARY REFERENCE DOCUMENTS

- Davis, N.L. "High-Resolution Radar-Periscope Detection in Sea Clutter," NRL Report 4924, May 9, 1957.
- Watterson, C.C., "Detection of a Periscope in Clutter with a 10 Milli-Microsecond Fast Scan Radar," University of New Mexico Symposium, May 1959.
- Ohman, G., "Getting High-Range Resolution with Pulse-Compression Radar," *Electronics*, October 7, 1960.
- Myers, G.F., "High Resolution Radar, Part III, Sea Clutter," NRL Report 4952, July 1967.
- Fuller, I.W. and Myers, G.F., "Nanosecond Radar Observations of Sea Clutter Cross Section vs Grazing Angle," NRL Report 6933, October 8, 1969.

VANGUARD PROGRAM — THE ROCKET

ACHIEVEMENT

Between 1955 and 1959, NRL conducted the first American satellite program, called Vanguard. The program was initiated to represent the U.S. in the International Geophysical Year (IGY), a cooperative international scientific effort to study the physical properties of the Earth. The nation's leaders chose to participate in the IGY by placing an artificial satellite into orbit, and a competition was held to determine which government agency would build and launch the satellite. NRL's plan was selected, due in part to its success with the Viking program. The Laboratory's pioneering task was to design, build, launch, place into Earth orbit, and track an artificial satellite carrying a scientific experiment. The contractor for the rocket project was the Glenn L. Martin Company.

The rocket successfully met the program's objective of putting a satellite into orbit during the IGY. The *Vanguard I* satellite was launched into Earth orbit on March 17, 1958, 5 months and 13 days after the Soviet Union launched *Sputnik I* and about 6 weeks after the launch of *Explorer I*, America's first orbiting satellite.

Successfully designing and developing a three-stage rocket, with three brand new and unproven stages, on such a timely schedule was unprecedented. Experience in the DoD at that time showed that in missile programs, it took more than 5 years from the start of a program to arrive at the date of the first successful launch; the Vanguard team achieved their objective in 2 years, 6 months, and 8 days.⁷⁹ Wernher von Braun, chief architect of the Redstone rocket that launched *Explorer I* into orbit, called it a miracle.⁸⁰ The Redstone rocket was America's first large ballistic missile and it had made its first successful flight in 1953, two years before NRL's Vanguard proposal was approved in 1955.

IMPACT

The Vanguard rocket successfully met the program's objective of launching a scientific satellite into orbit during the IGY, and the rocket technology pioneered by Vanguard was used by later programs. The use of a "strapped down" gyro platform, the rotatable exhaust jets of the first-stage turbopump, which ensured efficient roll control, and the C-band radar antenna beacon employed on the Thor-Able vehicle all originated with Vanguard. In fact, the Air Force used many design concepts from Vanguard's second and third stages in its Thor-Able booster. Finally, one of America's most versatile and reliable launchers, the Delta rocket, reflects much of Vanguard's design.⁸¹

PRIMARY REFERENCE DOCUMENTS

- "A Scientific Satellite Proposal," by the Rocket Development Branch of the Atmospheric & Astrophysics Division, NRL Memorandum Report 487, April 13, 1955.
- "Project Vanguard Report No. 1 Plans, Procedures, and Progress," NRL Report 4700, January 13, 1956.

⁷⁹ Hagen, J.P., "Vanguard—The Laboratory Ventures Into Space," *Report of NRL Progress*, NRL (1973), 31; "The Viking and the Vanguard," *Technology and Culture*, Vol. IV, no. 4 (Fall 1963), 435-451.

⁸⁰ Green, C.M. and Lomask, M., *Vanguard: A History*, NASA (Washington, DC, 1970), 254.

⁸¹ *Ibid.*, 255.

VANGUARD PROGRAM — MINITRACK AND SPACE SURVEILLANCE

ACHIEVEMENT

Since a suitable satellite tracking system did not exist at the time of the Vanguard program, NRL developed the world's first satellite-tracking system (called "Minitrack") in 1956. This tracking network was later transferred to the Goddard Space Flight Center and formed the basis for the satellite tracking networks used by NASA. Ironically, the Minitrack system first demonstrated its capabilities by tracking another nation's satellite. During October 5–26, 1957, NRL accurately predicted and tracked the orbits of the Soviet Union's *Sputnik I*. Three months later, NRL confirmed and tracked *Explorer I*, America's first orbiting satellite, launched into orbit by the U.S. Army on January 31, 1958. Weeks later, Minitrack tracked the orbit of *Vanguard I*, launched on March 17, 1958.

After the Soviet launch of *Sputnik I*, the detection and tracking of foreign satellites orbiting over the United States became a major national security issue. As a result, the Navy Space Surveillance System (NAVSPASUR) was developed by NRL on a "crash basis" for the Advanced Research Projects Agency from 1958 to 1964 in order to detect and track such satellites. NRL was selected to develop this system primarily because of Minitrack's success. But unlike Minitrack, NAVSPASUR was designed to track satellites that transmitted signals as well as those that were "quiet." NAVSPASUR consisted of nine bistatic radar sites stretching between southern California and Georgia and comprised a radar "fence" capable of detecting basketball-sized objects in orbit as high as 7,500 miles above the Earth.⁸² The information gathered was used to warn U.S. naval units of periods when they would be vulnerable to detection.

By 1983, NAVSPASUR was a critical element in the North American Air Defense Command's Space Detection and Tracking System and was tracking more than 4,966 objects every day. NAVSPASUR was later renamed the Navy Space Sensor System, and then became the Air Force Space Surveillance System (AFSSS). After 52 years of service, AFSSS was deactivated in October 2013.

IMPACT

As the world's first satellite tracking system, the impact of Minitrack was significant, not only to the primary task of tracking the orbit of the Vanguard satellites, but also in tracking the orbits of the Sputnik and Explorer satellites. Later, the concept was employed by NRL in the design and development of NAVSPASUR, the primary system for maintaining surveillance of space objects and for warning U.S. fleet units of periods of vulnerability to foreign surveillance satellites.

PRIMARY REFERENCE DOCUMENTS

- "A Scientific Satellite Proposal," by the Rocket Development Branch of the Atmospheric & Astrophysics Division, NRL Memorandum Report 487, April 13, 1955.
- Mengel, J.T., "Tracking the Earth Satellite, and Data Transmission, by Radio," *Proceedings of the IRE National Convention*, March 20, 1956.
- Easton, R.L. and Fleming, J.J., "The Navy Space Surveillance System," *Proceedings of the IRE National Convention*, April 1960.

⁸² Glaeser, F., "Space: A New Dimension in Naval Warfare," *U.S. Naval Institute Proceedings*, Vol. 113, 133 (May 1987).

VANGUARD PROGRAM — THE SATELLITES AND THE SCIENCE

ACHIEVEMENT

The *Vanguard I* satellite was successfully launched into Earth orbit on March 17, 1958. Although it was not the first U.S. satellite successfully launched, *Vanguard I* met the program's original objective of putting a satellite into orbit during the International Geophysical Year (IGY), a cooperative international scientific effort to study the physical properties of the Earth. *Vanguard I* achieved the highest altitude of any man-made vehicle to that time and established beyond doubt geologists' suspicions that the Earth is pear-shaped.⁸³

A significant innovation in *Vanguard I* was the use of miniaturized circuits. It carried two radios and a temperature sensor and was the first satellite ever to use solar cells as a power source.⁸⁴ The solar cells developed by the Signal Engineering Laboratories, placed by Vanguard engineers on the satellite shell so as not to interfere with the functioning of the internal instrumentation, set a new standard of efficiency and account for the long operating life of the satellite.⁸⁵ *Vanguard I* orbits the Earth today as the oldest man-made satellite and it will remain in orbit well into the 22nd century.

Vanguard II was placed into orbit on February 17, 1959, and was the first satellite designed to observe and record the cloud cover of the Earth. As such, *Vanguard II* was the forerunner of future meteorological satellites.⁸⁶

On July 29, 1958, president Dwight D. Eisenhower signed the National Aeronautics and Space Act, which created the National Aeronautics and Space Administration (NASA). Presidential order 10783 subsequently transferred many of NRL's Vanguard personnel into the newly created space agency on 1 October 1958, where they became a core of technical expertise at NASA's Goddard Space Flight Center.

IMPACT

The Vanguard program established landmark scientific achievements. According to a National Academy of Science panel in 1958, "The overall scientific program developed for use with the Vanguard launching system has made possible the total program of space vehicle instrumentation, observation, and data reduction carried out under IGY auspices. Additionally, it has provided the original basis of the present expanding program of scientific experiments for space research for the U.S."⁸⁷

PRIMARY REFERENCE DOCUMENTS

- "A Scientific Satellite Proposal," by the Rocket Development Branch of the Atmospheric & Astrophysics Division, NRL Memorandum Report 487, April 13, 1955.
- "Project Vanguard Report No. 1 Plans, Procedures, and Progress," NRL Report 4700, January 13, 1956.

⁸³ McDougall, W.A., *The Heavens and the Earth: A Political History of the Space Age* (Basic Books, Inc., New York, 1985), 168.

⁸⁴ Mitchell, P.A., "The Navy's Mission in Space," *Oceanus*, Vol. 20, No. 2, 23 (Summer 1985).

⁸⁵ Green, C.M. and Lomask, M., *Vanguard: A History* (NASA, Washington, DC, 1970), 254.

⁸⁶ Mitchell, "The Navy's Mission in Space," 23.

⁸⁷ Minutes of the 19th meeting, U.S. Technical Panel on the Earth Satellite Program, (26 July 1958), 5.

FIRST OPERATIONAL SATELLITE COMMUNICATION SYSTEM —

“COMMUNICATION MOON RELAY”

ACHIEVEMENT

While conducting its original high-frequency-propagation work in the 1920s, NRL was the first to determine the frequency above which radio waves would penetrate the Earth’s atmosphere and propagate through outer space, making radio communication in space possible. Years later, in 1951, NRL was the first to demonstrate that radio energy reflected from the Moon was much more coherent than predicted. As a consequence, a Moon circuit could be used to transmit data at a rate and a fidelity adequate for radio communication. NRL then developed the key transmitter and receiver technologies that allowed for effective communication through a passive Moon circuit.

In 1954, NRL was the first to transmit and return the human voice through outer space.⁸⁸ NRL first demonstrated transcontinental satellite communication, from Washington, DC to San Diego, California, in 1955.⁸⁹ The first official message to be transmitted via a satellite was sent over this circuit. The system was then designated “Communication Moon Relay,” or CMR. It should be noted that CMR was a spin-off of a classified NRL project, known as “Passive Moon Relay,” which used the Moon as a means to intercept reflecting Soviet radar signals.

In 1959, the world’s first operational satellite communication system, allowing communications from Washington, DC, to Oahu, Hawaii, was placed into operation. Public demonstration of this system took place on January 28, 1960, with the exchange of messages between the chief of naval operations and the commander in chief of the Pacific Fleet. The system proved reliable, its main limitation being position of the Moon. Operators manned the system for a period of four to eight hours daily, the time from moonrise in Hawaii to moonset in Washington. Also in 1960, NRL transmitted the first pictures (facsimile) over a satellite communications system, the CMR.

IMPACT

While the CMR never became a routine communications system, NRL ushered in the age of satellite communications by developing key technologies needed for viable artificial satellite communications. This was of critical value because the U.S. is a global maritime power with naval forces deployed worldwide. Communication with far-flung and constantly mobile forces is critical to American sea power. With the use of satellite communications, a task force commander can stay in contact without relying on vulnerable land lines, undersea cables, and radio relay stations, which are often on foreign soil.

PRIMARY REFERENCE DOCUMENTS

- Trotter, B.E. and Youmans, A.B., “Communications Moon Relay (CMR),” NRL Report 4907, June 1957.
- Trexler, J.H., “Lunar Radio Echoes,” *Institute of Radio Engineers* (January 1958).

⁸⁸ Trexler, J.H., “Lunar Radio Echoes,” *Institute of Radio Engineers*, 286-292 (January 1958); van Keuren, David, “Moon in Their Eyes: Moon Communication Relay at the Naval Research Laboratory, 1951-1962,” in Andrew J. Butrica, ed., *Beyond The Ionosphere* (Washington, D.C.: NASA, 1997), 9-18.

⁸⁹ Trotter, B.E. and Youmans, A.B., “Communications Moon Relay (CMR),” NRL Report 4907, June 1957.

X-RAY ASTRONOMY

ACHIEVEMENT

NRL's X-ray astronomy program, led by H. Friedman, dates back to the launch of an X-ray detector on a V-2 rocket on September 29, 1949. That launch was the first of a series of rocket and satellite-based experiments that determined that solar X-rays are the cause of ionization in the E-layer of the Earth's ionosphere. Following the initial report of significant cosmic X-ray emission in 1962 by American Science and Engineering, Inc.,⁹⁰ the NRL team expanded their attention to include detection of X-rays from nonsolar astronomical sources.

Over a period of three years, NRL conducted a series of sounding rocket experiments that demonstrated the discrete nature of the X-ray sources and their association with the Milky Way.⁹¹ They showed that the diffuse X-ray background was cosmic in origin.⁹² Subsequently, they detected the first extragalactic X-ray source.⁹³ In one of the most significant rocket experiments flown, NRL researchers observed the Crab Nebula during a lunar occultation of the object and demonstrated that the X-ray emission was emerging from the nebula.⁹⁴ This single experiment was the first positive identification of a source of cosmic X-rays with a known object and provided the first observational evidence for the X-ray production mechanism.

NRL produced a sky map of galactic and extragalactic emitters using observations made by an array of large-aperture X-ray detectors on NASA's High Energy Astronomical Observatory (HEAO-1). The resulting *HEAO A-1 X-Ray Source Catalog* included 842 discrete X-ray sources and became a standard reference source for galactic and extragalactic X-ray emitters.

IMPACT

The work by NRL researchers was critical to X-ray astronomy, contributing to the development of a new and important research specialty. X-ray research made important contributions to the advance of cosmology and astrophysics. *The HEAO A-1 X-Ray Source Catalog* became an important reference source in X-ray astronomy.

PRIMARY REFERENCE DOCUMENTS

- Bowyer, C.S., Byram, E.T., Chubb, T.A., and Friedman, H., "Lunar Occultation of X-ray Emission from the Crab Nebula," *Science*, Vol. 146, 912-917 (November 13, 1964).
- Bowyer, S., Byram, E.T., Chubb, T.A., and Friedman, H., "Cosmic X-ray Sources," *Science*, Vol. 147, 394-398 (January 22, 1965).
- Wood, K.S., *The HEAO A-1 X-Ray Source Catalog*, NRL R-1984-00109, 1984.

⁹⁰ Giacconi, R., Gursky, H., Paolini, F.R., and Rossi, B., "Evidence for X-Ray Sources Outside the Solar System," 1962, *Phys. Rev. Letters*, Vol.9, No. 11, 439-442.

⁹¹ Bowyer, S., Byram, E.T., Chubb, T.A., and Friedman, H., "Cosmic X-ray Sources," *Science*, Vol. 147, 394-398 (22 January 1965).

⁹² Hirsh, R., *Glimpsing an Invisible Universe: The Emergence of X-Ray Astronomy* (Cambridge University Press, Cambridge, 1983), 107ff.

⁹³ Charles, P.A. and Seward, F.D., *Exploring the X-Ray Universe*, (Cambridge University Press, 1995), 9.

⁹⁴ Bowyer, C.S., Byram, E.T., Chubb, T.A., and Friedman, H., "Lunar Occultation of X-ray Emission from the Crab Nebula," *Science*, Vol. 146, 912-917 (13 November 1964).

HIGH-FREQUENCY DIRECTION FINDING

ACHIEVEMENT

During the 1950s and 1960s, NRL demonstrated technology that permitted a radical improvement in the performance of high-frequency direction finding (HFDF) networks and oversaw the deployment of this technology in Project Boresight and Project Bulls Eye.

The first of three innovations that underlay NRL's work was *retrospective direction finding*. Previously, all stations in an HFDF network were required to measure characteristics of the same signal while transmission was still occurring. After-the-fact measurements were needed. Previous attempts were limited by storage bandwidth and recorder instabilities.⁹⁵ Recording significant fractions of the HF spectrum and using a digital method for overcoming recorder instabilities enabled retrospective DF.⁹⁶ This was the basis of Project Boresight in 1960, which deployed the AN/FLR-7 and AN/FRA-44 worldwide. Boresight was a classified program initiated when National Security Agency operators, who had been routinely intercepting daily HF signals from Soviet submarines, suddenly noticed no signals. The Soviets were compressing the signals and transmitting them in a fast burst too quick to be pinpointed.⁹⁷

The second innovation was the use of *circularly disposed wide-aperture direction finding arrays*,⁹⁸ which significantly increased HFDF location accuracy and signal-collection capabilities. In the 1950s, NRL had constructed a 400-ft-diameter electronically steerable array and perfected the underlying technology. During Project Bulls Eye, scaled-up versions of this prototype were deployed worldwide by the Navy as the AN/FRD-10. The third innovation was the use of computers for control of the HFDF network and for the prompt triangulation of target locations.⁹⁹

IMPACT

NRL developed the technology to intercept and locate submarine radio transmissions that the Soviets thought were undetectable. During the Cuban Missile Crisis in October 1962, Project Boresight gave America a significant advantage by providing the capability to track Soviet submarines *en route* to Cuba.¹⁰⁰ Boresight's crucial contribution to national defense was recognized by the awarding of the Distinguished Civilian Service Award to NRL's R.D. Misner and M.J. Sheets. The more ambitious Project Bulls Eye made HFDF a principal means of global ocean surveillance at the time.

PRIMARY REFERENCE DOCUMENTS

- Gleason, R.F. and Greene, R.M., "A Wide-Aperture HF Direction-Finder," NRL Memorandum Report 746, October 1957.
- Wald, B., "Utilization of a Multiprocessor in Command and Control," *Proceedings of the IEEE*, 1885-1888, December 1966.

⁹⁵ Misner, R.D. and Tool, A.Q., "D/F Bearing Recorder," NRL Memorandum Report 162, May 1953.

⁹⁶ Misner, R.D. and Wald, B., "Bearing Readout Systems for Goniometric Direction Finders," NRL Memorandum Report 830, August 1958.

⁹⁷ Ruzicka, D., *Historic American Buildings Survey*, U.S. Naval Base, Pearl Harbor, Naval Radio Station, AN/FRD-10 Circularly Disposed Antenna Array, (May 2007), 8.

⁹⁸ Trexler, J.H., "Circularly Disposed Antenna Arrays," NRL Report 3213, December 1947.

⁹⁹ Wald, B. and Googe, W.D., "HF-DF Fixing," NRL Report 5302, May 1959.

¹⁰⁰ Blanton, T., Burr, W., Savranskaya, S., eds., "The Underwater Cuban Missile Crisis: Soviet Submarines and the Risk of Nuclear War," National Security Archive Electronic Briefing Book No. 399, (24 October 2012); and Aid, M., *The Secret Sentry: the Untold History of the National Security Agency* (Bloomsbury Press, NY, 2009), 74-75.

SOLAR RADIATION (*SOLRAD*) I

ACHIEVEMENT

The SOLRAD (SOLar RADiation) program was conceived in the late 1950s as an improved means of studying the Sun's effects on the Earth, particularly during periods of heightened solar activity. Of prime interest were the effects of solar radiation on the ionosphere, which had critical importance to naval communications. It was one of the nation's longest continuing series of satellite projects dedicated to a specific research program. *SOLRAD I* was launched in June 1960, and ten more SOLRADs were fabricated by NRL and were flown through 1976.

SOLRAD I determined that radio fade-outs were caused by solar X-ray emissions, verifying a theory of NRL's H. Friedman. It was also one of the two satellites launched during the world's first multiple satellite launching and was the first satellite to be successfully commanded to shut off. On August 6, 1960, *SOLRAD I* recorded 6 of 18 minutes of the first solar flare recorded by an orbiting satellite and telemetered the information to a NASA tracking station. The data recorded throughout *SOLRAD I*'s active life shed new light on the relationships among sunspot activity, solar X-ray emission, and radio wave propagation.

Subsequent SOLRADs served as solar radiation monitors circling the Earth, on guard for any unusual solar disturbances that could have endangered astronauts on spaceflight missions. Special SOLRAD operations for the *Apollo 8* mission began at the request of NASA in 1968 when astronauts first circled the Moon. In 1969, solar flare forecasts derived from data furnished by *SOLRAD 9* were used to safeguard *Apollo 11* astronauts and their communications systems during the first lunar landing mission. NRL provided the data to the Space Disturbance Forecast Center of the Environmental Science Services Administration (now NOAA), which had responsibility for determining the status of radiation hazards to the astronauts. *SOLRADs 9, 10, 11A and 11B* provided these data throughout the Apollo and SKYLAB programs.¹⁰¹

IMPACT

The SOLRAD satellites monitored the Sun for more than 15 years, providing not just valuable real-time observation and warning, but also archiving for generations to come scientific information on many types of high-energy flares and the Sun's effects upon the Earth's atmosphere.¹⁰² The new knowledge gained by the program also yielded practical, and in some cases critical, benefits to naval communication and the U.S. manned space program.

PRIMARY REFERENCE DOCUMENTS

- Chubb, T.A., Friedman, H., Kreplin, R.W., Nichols, W.A., Unzicker, A.E., and Votaw, M.J., "Results from the NRL Solar Radiation Satellite," in *Space Research II*, Van de Hulst, H.C., et al., eds. (North Holland Publishing Company, Amsterdam, 1961).
- Horan, D.M., McClinton, A., and Kreplin, R.W., "Solar X-Ray Emission During the Flight of Apollo 8," NRL Report 6917, 13 June 1969.

¹⁰¹ Peterkin, E.W., "The Navy's Satellite Solar Activity Monitoring and Forecasting System," the Fourth Allerton House Conference on Radiolocation Research, University of Illinois, Monticello, Illinois (1971); "NASA To Launch SOLRAD Satellite," *Joint NASA/NRL Press Release*, 2 July 1971.

¹⁰² Vol. 1 NRL Space Science Division Achievements: 1960-1970, NRL Memorandum Report 7600—15-9637.

AMERICA'S FIRST OPERATIONAL INTELLIGENCE SATELLITE

ACHIEVEMENT

The now-unclassified *Galactic Radiation and Background I (GRAB I)* payload, an acknowledged co-flyer with the publicly recognized *Solar Radiation I (SOLRAD I)* scientific payload, was America's first operational intelligence satellite.¹⁰³ In June 1960, fifty-two days after a U-2 aircraft was lost on a reconnaissance mission over Soviet territory, the *GRAB I* satellite soared into orbit and began transponding space-intercepted electronic intelligence signals to Earth-bound signals intelligence stations.

GRAB I was the unique application of many emerging technologies. NRL's M.J. Votaw, previously with Project Vanguard, brought the technical experience and resources necessary to design, build, launch, and operate a satellite in space. R.D. Mayo supervised the design and development of the S-band antenna with crystal video receiver and ground receive equipment to collect signals from Soviet air defense radar. H.O. Lorenzen provided the overall technical direction, obtained intelligence community sponsorship, and led transfer of the technology into operational deployment.¹⁰⁴ The notion of operating the antenna/detector reconnaissance technology in an orbiting satellite and collecting its transponded signal on magnetic tape was a breakthrough answer to CNO Admiral Arleigh Burke's request for naval material bureaus and laboratories to consider how they could use space in their design ideas for the Navy.

With mission sponsorship by the Office of Naval Intelligence, NRL developed the satellite and its network of overseas ground collection sites. President Eisenhower approved the electronic intelligence (ELINT) program and its SOLRAD scientific experiment cover. The GRAB/SOLRAD payloads shared a ride into space with the Navy's third *Transit* navigation satellite as part of the world's first multiple-satellite launching. Field sites recorded *GRAB I* signals on magnetic tapes, which were couriered to NRL for evaluation and duplication. The National Security Agency (NSA) and the Strategic Air Command exploited the tapes for technical ELINT data and to support the Single Integrated Operations Plan.

IMPACT

The GRAB project provided proof of concept for satellite-collected ELINT. This was accomplished by demonstrating that a platform in outer space could collect as much as all other sea, air, and land-based reconnaissance platforms operating within the satellite's field of view, at a fraction of their cost, and at no risk to personnel. The output, initially overwhelming, stimulated invention by NRL and NSA of machine processing of digitized data using commercial computers. In searching the tapes for new and unusual signals, NSA found the Soviets were already operating a radar that supported a capability to destroy ballistic missiles. Such information could not be obtained by airborne reconnaissance, nor without enormous risk to human sources. The intelligence information gained from *GRAB I* had a profound impact on national security decision-making and on deterrence of nuclear war with the Soviet Union. A GRAB-I model is in the National Air and Space Museum (NASM).

PRIMARY REFERENCE DOCUMENTS

- Secretary of Defense McElroy letter to President Eisenhower, August 18, 1959.
- Technical Operations Group Report, October 13, 1960.

¹⁰³ Day, D., "Listening from Above: The First Signals Intelligence Satellite," *Spaceflight*, Vol. 41, no. 8 (1999), 339-346.

Van Keuren, D., "Cold War Science in Black and White," *Social Studies of Science*, Vol. 31, No.2 (April 2001), 207-229.

¹⁰⁴ The Department of the Navy honored H.O. Lorenzen for his contributions to electronic intelligence when the USNS *Howard O. Lorenzen* (T-AGM-25), a Missile Range Instrumentation Ship, went into service in 2012.

HIGH-POWER NEODYMIUM GLASS LASERS

ACHIEVEMENT

In the 1960s, prior work in France had created Nd:glass lasers with single-pulse energies of about 100 joules and a pulse duration of several nanoseconds. NRL subsequently addressed bridging the gap between hundreds of joules and the tens of kilojoules (kJ) or more needed for meaningful laser fusion experiments. Specifically, NRL recognized how output energy or power density of a disc laser scales with size, recognized the trade-off between laser gain (the amount of amplification), self-focusing, and spatial beam quality, developed a high-gain module and the pulsed power technology necessary to operate it safely, and developed, built, and demonstrated a laser system comprising these modules that produced a terawatt of peak power per beam. The success of this effort led to the adoption of this technology for the 10 kJ Shiva laser used by the laser fusion program at Lawrence Livermore National Laboratory (LLNL).

In the late 1970s, the issue became one of how to develop laser designs capable of scaling not to kilojoules per pulse, but to megajoules per pulse. One factor in scaling was the linear and nonlinear optical properties of the host laser glass. Another was the laser performance of the neodymium ion in the particular host glass matrix. A higher-gain laser could function with less glass end to end and hence could tolerate a higher intensity. NRL advocated for the use of phosphate laser glasses to address this issue. The Department of Energy (DoE) supported a test of this scaling concept, which culminated in the successful operation of NRL's Pharos II laser with phosphate laser glass in 1980 at over a kJ. Ultimately, LLNL and the DoE chose to reconfigure the large Nova laser using phosphate laser glasses based on NRL's success.

IMPACT

Between 1966 and 1982, NRL determined how to scale up high-peak-power glass lasers to conditions necessary to perform realistic experiments exploring the potential of inertial confinement fusion. This effort had a major impact on the U.S. laser fusion program. Specifically, it significantly influenced the design of DoE's 10 kJ Shiva laser, the reconfiguration of DoE's Nova laser, and the design of the National Ignition Facility.

PRIMARY REFERENCE DOCUMENTS

- McMahon, J.M., Emmett, J.L., Holzrichter, J.F., and Trenholme, J.B., "A Glass Disc-Laser Amplifier," *IEEE Journal of Quantum Electronics*, Vol. QE-9, No.10, 992 (1973).
- McMahon, J.M., "Optimization of Nd:Glass Lasers with Phosphate-Laser Glass," NRL Memorandum Report 3411, November 1976.
- McMahon, J.M., Burns, R.P., DeRieux, T.H., Hunzicker, R.A., and Lehmberg, R.H., "The Upgraded Pharos II Laser System," *IEEE Journal of Quantum Electronics*, Vol. QE-17, 1629 (1981).

IMPROVED AIRCRAFT CANOPY AND WINDOW MATERIALS

ACHIEVEMENT

NRL's interest in aircraft windows originated with the blowout failures of combat aircraft canopies. These failures resulted from the inability of the canopy material to halt the propagation of cracks caused by impacts of sharp objects or by missile penetration.¹⁰⁵ In 1953, J. Kies applied NRL's pioneering research in fracture mechanics for the first time to a practical problem — the failure of combat aircraft canopies.¹⁰⁶

Experiments by I. Wolock, then at the National Bureau of Standards and later with NRL, showed that craze cracking of acrylic could be eliminated by hot stretching, a result that led Kies to the idea that hot stretching could add to the toughness of aircraft windows. Kies worked with commercial manufacturers of acrylic material (e.g., Rohm and Haas) and used fracture mechanics to ascertain the toughness of the material. In the course of the work, NRL shattered hundreds of aircraft canopies by projectile impact, and then carefully reassembled them to allow crack paths to be traced.¹⁰⁷ Kies pointed out that the critical stress for a given crack size depended only on the product G_cE , which could be directly computed from the applied stress and crack size for the test.

The response of aircraft engineers concerned with testing stretch-toughened glazing materials was to express their fracture test results in values they termed K (K for Kies).¹⁰⁸ Kies's work is also incorporated in design criteria for aircraft plastic glazing materials issued jointly by the Departments of Commerce, the Navy, and the Air Force.

IMPACT

NRL worked cooperatively with the Air Force and with commercial manufacturers to introduce stretched acrylic plastic for military canopies with increased toughness, reduced weight, and prolonged service life. This material is now employed in military and civilian aircraft, thereby reducing a once-significant source of fatal accidents.

PRIMARY REFERENCE DOCUMENTS

- Kies, J.A., "Aircraft Glazing Materials, A Method for Evaluating the Shatter Resistance of Aircraft Canopy Materials," NRL Memorandum Report 237, November 1953.
- "Plastics for Aircraft: Transparent Glazing Materials," *ANC-17 Bulletin*, Part II, issued by the Department of Commerce, Department of Navy, and Department of Air Force, 1957.
- "Plastics for Flight Vehicles," *Military Handbook* No. 17, Part II, DoD, 1961.

¹⁰⁵ Kies, J.A. and Smith, H.L., "Aircraft Glazing Materials," NRL Memorandum Report 372, October 1954, 1.

¹⁰⁶ Rossmannith, H.P., "George Rankin Irwin - The Father of Fracture Mechanics," presented at the George R. Irwin Symposium on Cleavage Fracture, *The Minerals, Metals & Materials Society*, 1997, 17.

¹⁰⁷ Krafft, J.M., "The Metallurgy and Mechanics Divisions, Post-1950 History," in *Materials Science and Technology Division History*, NRL/PU-6300-93-240 (May 1993), 103.

¹⁰⁸ Irwin, G.R., "Fracture Mechanics," *Report of NRL Progress*, July 1973, 36; and Rossmannith, H.P., "George Rankin Irwin - The Father of Fracture Mechanics," 17.

PURPLE-K-POWDER

ACHIEVEMENT

Prior to the development of potassium bicarbonate dry chemical extinguishing agent, or “Purple-K-Powder” (PKP), hydrocarbon fires were extinguished using either sodium bicarbonate dry chemical powder or protein foam. The dry chemical was effective on three-dimensional and “hidden” fires (e.g., debris from an aircraft crash), but provided no protection against reflash. Protein foams were used to extinguish fuel spill or in-depth liquid pool fires. The thick foam blanket provided reflash protection by excluding oxygen from the fuel surface, but foams were ineffective on 3D and hidden fires. The agents could not be used in combination because the foam bubbles were chemically attacked and destroyed by commercially available dry chemicals. The first step in developing an optimal approach was to develop a superior, foam-compatible dry chemical.

In 1959, a series of investigations by NRL in the area of chemical flame extinction gave birth to Purple-K-Powder. Powdered bicarbonate of soda as a flame-halting agent had been employed for many years, but its action had never been satisfactorily explained. Working with other investigators, NRL conducted fire tests with many powdered substances, which helped to clarify the chemical actions involved. This work came to the conclusion that the substitution of the potassium ion for sodium extended the flame-quenching efficiencies of the chemical powders by a factor of two.¹⁰⁹ This meant PKP extinguished a fuel fire in half the time or extinguished twice as much fire as before. Ensuing industry efforts resulted in production of surface coatings that allowed PKP to be compatible with foams.

IMPACT

The development of Purple-K-Powder represented a major advancement in the state of the art for flammable liquid fire protection. PKP became used throughout the Navy and in U.S. municipal and industrial fire protection operations, and thereafter throughout the world.

PRIMARY REFERENCE DOCUMENTS

- Jablonski, E.J. and Moran, H.E., Jr., “Tests of Mobile Dry Powder Crash Fire Extinguishing Units at Wright-Patterson Air Force Base, NRL Observers’ Report of,” NRL letter report 3250-125/49, September 21, 1949.
- Peterson, H.B., Tuve, R.L., Neill, R.R., Burnett, J.C., and Jablonski, E.J., “The Development of New Foam-Compatible Dry Chemical Fire Extinguishing Powders,” NRL Report 4986, September 5, 1957.
- Jablonski, E. J. and Gipe, R.L., “A New Method for Determining the Degree of Compatibility of Dry Chemical Powders with Mechanical Foams,” NRL Report 5329, June 23, 1959.
- Military Specification MIL-F 22287 (Wep) December 15, 1959, “Fire Extinguishing Agent, Potassium Dry Chemical,” in present form a Federal Specification O-D-1407A.

¹⁰⁹ Tuve, R.L., “Recent Navy Research on Dry Chemicals,” *NFPA Quarterly*, Vol. 54, 162 (1960).

POLYTETRAFLUOROETHYLENE FOR THE NAVY

ACHIEVEMENT

In 1938, while researching Freon compounds as refrigerants, DuPont researchers discovered that an inert white solid had formed in one of their gas cylinders that they later trademarked as Teflon. This material — polytetrafluoroethylene (PTFE) — was inert and nonmelting, making it hard to manipulate, but it found early use in the Manhattan Project, as it was able to withstand highly corrosive environments.

NRL's W.A. Zisman and V.G. FitzSimmons helped DuPont utilize Teflon as a lubricant and a coating. Teflon's very low coefficient of dry friction was first recognized during cooperative wartime research with Du Pont in 1943.¹¹⁰ Zisman noted the very low coefficient of friction of thin sheets of Teflon and indicated to W.S. Calcott, director of DuPont's organic chemistry laboratory, that Teflon had the properties of a practical solid lubricant. NRL collaborated with DuPont on early sintering experiments that combined Teflon with metal powders and substrates. Through his professional networks in industry, Zisman learned of this novel material, uncovered some of its useful properties, shared these with industry and academe, and developed applications for the new material to exploit its properties for the U.S. Navy's benefit.

IMPACT

NRL worked with the Bureau of Ordnance, the Marine Corps, the Bureau of Ships and others to investigate the application of Teflon to naval systems and equipment. By 1959, Zisman and FitzSimmons had successfully applied Teflon as dry lubricants and preservatives of steel and brass cartridge cases, with applications to more than 200 different mechanisms on submarines and torpedoes. Zisman noted a wide range of its use by 1968 as a lubricant "in space vehicles, rockets, inaccessible portions of submarines, and in food processing, packaging, and textile machinery."¹¹¹ Zisman and FitzSimmons successfully patented PTFE-coating methods for the cartridge casings used in large-caliber (.50 and above) fully automatic rapid-fire guns,¹¹² as well as PTFE coatings and rings for hard and soft bullets designed to increase barrel life.¹¹³

PRIMARY REFERENCE DOCUMENTS

- FitzSimmons, V.G. and Zisman, W.A., "Thin Films of Polytetrafluoroethylene Resin as Lubricants and Preservative Coatings for Metals," *Industrial and Engineering Chemistry*, 1958.
- Zisman, W.A., *Proc. Summer Conference on Mechanical Wear, Mass. Inst. of Technology*, June 1948, p. 102, Am. Soc. Metals, 1950.
- FitzSimmons, V.G. and Zisman, W.A., "Thin Films of Polytetrafluoroethylene Resin (Teflon) as Lubricants and Preservative Coatings for Metals," NRL Report 4753, June 15, 1956.
- FitzSimmons, V.G. and Zisman, W.A., "Microfiber Reinforcement of Polytetrafluoroethylene (Teflon)," NRL Report 5724, January 9, 1962.
- Nash, H.C. and Kohn, E.J., "Studies on Reducing the Surface Friction of Elastomers," NRL Report 5911, May 1, 1963.
- Bowers, R.C., Clinton, W.C., and Zisman, W.A., "Frictional Properties of Plastics," *Modern Plastics*, 31, no. 6, 131+, 1954.

¹¹⁰ FitzSimmons, V.G., and Zisman, W.A., "Thin Films of Polytetrafluoroethylene Resin as Lubricants and Preservative Coatings for Metals," *Industrial and Engineering Chemistry*, 781-784, 50, 1958.

¹¹¹ Bowers, R.C. and Zisman, W.A., "Pressure Effects on the Friction Coefficient of Thin-film Solid Lubricants," *Journal of Applied Physics*, 39, 5385-5395, (1968), 5385.

¹¹² FitzSimmons, V.G. and Zisman, W.A., "Ammunition Cartridge Cases," US Pat. No. 2972947, 28 February 1961.

¹¹³ Zisman, W.A. and FitzSimmons, V.G., "Projectile Rotating Band," US Pat. No. 2928348, 15 March 1960; and Zisman, W.A. and FitzSimmons, V.G., "Bullets," US Pat. No. 3040662, 26 June 1962.

QUANTITATIVE X-RAY FLUORESCENCE ANALYSIS

ACHIEVEMENT

NRL introduced many of the developments which have made X-ray fluorescence analysis (XRF) the quantitative method that it is today. In 1948, H. Friedman and L.S. Birks first outfitted an XRF spectrometer with a Geiger counter, ushering in the era of electronic detection for XRF.

Under the leadership of Birks, NRL brought XRF to maturity by pioneering the use of new instruments such as the electron microprobe,¹¹⁴ curved crystal spectrographs, and multichannel energy analyzers, and by devising novel analytical methods and computer codes that implement them. Beginning with a calculation of X-ray production in the microprobe, where microscopic standards could not be realized, the codes evolved into a comprehensive software package for quantitative chemical analysis using XRF, incorporating both fundamental parameters and empirical coefficients into a single flexible program. It has been estimated that by the 1990s, more than 1,000 laboratories worldwide had used the NRL software (NRLXRF), or similar programs employing the fundamental parameter approach developed at NRL.¹¹⁵

IMPACT

Virtually every X-ray chemical analysis system produced today incorporates one or more of NRL's seminal advances in instrumentation and analysis. NRL's research in XRF resulted in industrial applications in mining, manufacturing, and metals recycling. This legacy continued with the development of technologies for environmental cleanup and for wear monitoring of high value machinery.¹¹⁶ L.S. Birks has been honored with a recurring award established in his name by the Microbeam Analysis Society. In addition, the biennial Birks Award in X-Ray Spectrometry is given by the Denver X-Ray Conference.

PRIMARY REFERENCE DOCUMENTS

- Friedman, H. and Birks, L.S., "A Geiger Counter Spectrometer for X-Ray Fluorescence Analysis," *Review of Scientific Instruments*, Vol. 19, 323 (1948).
- Gilfrich, J.V. and Birks, L.S., "Spectral Distribution of X-Ray Tubes for Quantitative X-Ray Fluorescence Analysis," *Analytical Chemistry*, Vol. 40, 1077 (1968).
- Criss, J.W., Birks, L.S., and Gilfrich, J.V., "Versatile X-Ray Analysis Program Combining Fundamental Parameters and Empirical Coefficients," *Analytical Chemistry*, Vol. 50, 33 (1978).
- U.S. Patent No. 2,835,820 to Birks, L.S., "Curved Crystal Fluorescent X-Ray Spectrograph," May 20, 1958; U.S. Patent No. 2,842,670 to Birks, L.S., "Flat Crystal Fluorescent X-Ray Spectrograph," July 8, 1958; and U.S. Patent No. 2,449,066 to Friedman, H., "Analysis by Fluorescent X-Ray Excitation," September 14, 1948.

¹¹⁴ The NRL microprobe is held by the Navy Museum.

¹¹⁵ NRLXRF was made available to the public through COSMIC, an agency of the NASA/DOD Technology Transfer Network. The COSMIC version of the program was designed for mainframe computers, and from 1977 to 1990, two hundred copies were distributed. Personal computers widened the distribution of this software.

¹¹⁶ Gilfrich, J.V., "X-Ray Fluorescence Analysis at the Naval Research Laboratory: 1948-1997," NRL Memorandum Report 6685-98-8120, 19 March 1998.

IMPROVED BOILER WATER TREATMENT

ACHIEVEMENT

Naval 1200 psig steam propulsion boilers are subject to the damaging effects of corrosion and scale formation on the watersides if a proper boiler water treatment is not applied. Tube failures due to acid corrosion and scale formation are two major concerns that in the past were satisfactorily controlled by a low phosphate/free caustic treatment. However, accumulations of suspended solids required mechanical and chemical cleaning. Both types of cleaning require ships' boilers to be out of service and increase the crew's workload.

NRL and the Naval Ship System Engineering Station (NAVSSSES) started investigations into new water treatments to clean, *in situ*, naval high-pressure boilers in the late 1960s. NRL investigated the thermal stability chemistry of ethylenediaminetetraacetate (EDTA) salts as possible active components of a boiler water treatment for high-pressure boilers. Nuclear magnetic resonance was used to study the chemistry of EDTA salts and free acid under various thermal conditions. The reported kinetics of the chemical reactions indicated the amount of EDTA to add to the boiler on a continuous basis. This research was the guide that R.L. Dausuel, Jr., NAVSSSES, used to introduce EDTA into operating U.S. Navy boilers.¹¹⁷

This group effort led to a final treatment that included the addition of hydrazine to stabilize the EDTA solutions upon their addition to the boilers. After excellent results from four trial ships, the chief engineer of the Naval Sea Systems Command directed the implementation of a boiler water treatment based on an Na₄EDTA-and-hydrazine process. Results of shipboard testing demonstrated that use of the Na₄EDTA to clean, *in situ*, high-pressure steam boilers could extend the normal 1,800 hours of operation between cleanings to 15,000 to 20,000 hours. In addition, the passivated surfaces within the steam systems treated with Na₄EDTA would be beneficial when boilers were shut down for long periods of time.

IMPACT

NRL's basic research was instrumental to keeping U.S. Navy ship boilers in service for much longer periods and in reducing the costs associated with frequent cleanings.

PRIMARY REFERENCE DOCUMENTS

- Venezky, D.L. and Moniz, W.B., "Nuclear Magnetic Resonance Study of the Thermal Decomposition of Ethylenedinitrilotetraacetic Acid and Its Salts in Aqueous Solutions," *Analytical Chemistry*, Vol. 41 (January 1969).
- "EDTA for Continuous Treatment of Boilers," Fourth Inter-Naval Conference on Marine Corrosion, NRL, October 12, 1972. Part I — Venezky, D.L., "Rate and Mechanism of EDTA Decomposition in Aqueous Solutions at High Temperatures." Part II — Kelly, B.E. and Dausuel, Jr., R.L., "Shipboard Trial of Chelate Feedwater Treatment, 1200 PSIG Boiler."

¹¹⁷ "Boiler Water/Feedwater Test and Treatment," *Naval Ship's Technical Manual*, S9086-GX-STM-020, Chap. 220, Vol. 2, 15 December 1995 (Seventh Revision).

FRACTURE TEST TECHNOLOGY

ACHIEVEMENT

While NRL's G.R. Irwin was concerned primarily with the basic science of fracture, his colleague W.S. Pellini established methods for prevention of fracture based on experimental methods. Pellini developed engineering approaches for design and material selection in structures based on metallurgical principles. His work solved the mystery of brittle fractures of World War II *Liberty* ships, in which entire ships sometimes fractured in calm water at dockside, and is still relevant in the age of high-performance ships, aircraft, and missiles.

The test methods developed by NRL are the dynamic tear test, the drop-weight nil-ductility transition temperature test (DWT-NDT, standardized by the ASTM in 1963 and used along with the fracture analysis diagram for design of steel structures worldwide), the explosion bulge test, and the explosion tear test. Such tests were incorporated into materials procurement and fabrication specifications for construction of critical submarine and surface ship components.¹¹⁸ A prominent example is the selection of materials for submarine pressure hulls that had to withstand local deformations from explosive attack without crack extension. NRL worked with the Navy's ship and submarine materials and design codes to develop methods for evaluating materials, weldments, and welding processes. These methods, based on modeling, established the requirements for qualifying welds, welders, and new companies for the construction of submarine pressure hull structures.

The DWT-NDT proved the fracture resistance of HY-80 steel was superior to conventional steels, and the fully plastic performance of welded HY-80 plates in the explosion bulge test convinced the Navy that HY-80 should be used for submarine hulls and for any other critical application.¹¹⁹ In addition, two deep-submergence rescue vehicles that were built with pressure hull material certified to be reliable as measured by fracture mechanics methods were put into the fleet.

IMPACT

For more than 20 years, NRL was recognized as the leading international center for the development of structural integrity technology. During this time, the Navy relied upon NRL's expertise to ensure the structural integrity of aircraft, ships, and submarines, and in doing so, to safeguard their crew members. These techniques also increased the performance of naval vehicles, providing such payoffs as reliable deployment of deeper-running submarines.

PRIMARY REFERENCE DOCUMENTS

- Pellini, W.S., "Use and Interpretation of the NRL Explosion Bulge Test," NRL Report 4034, September 4, 1952.
- Pellini, W.S., Puzak, P.P., and Eschbacher, E., "Procedures for NRL Drop Weight Test," NRL Memorandum Report 316, June 1954.
- Pellini, W.S. and Puzak, P.P., "Fracture Analysis Diagram Procedures for the Fracture-Safe Engineering Design of Steel Structures," NRL Report 5920, March 15, 1963.

¹¹⁸ Lange, E.A., "Personal Account of Research Conducted Between 1950 and 1980 in the Metal Processing and the Strength of Metals Branches," in *Materials Science and Technology Division History*, (May 1993), 123.

¹¹⁹ Pellini, W.S. "Principles of Structural Integrity Technology," Office of Naval Research (1976), 227.

DEEP-OCEAN SEARCH

ACHIEVEMENT

On April 10, 1963, the nuclear submarine USS *Thresher* (SSN 593) was lost in deep water 260 miles east of Boston, Massachusetts, with 112 crew and 17 civilian technicians. The loss of the submarine and its personnel was a deep shock to the Navy and to the country.

In an effort to determine the reasons for the loss, NRL applied deep-towing technology, developed years earlier for underwater acoustic research, to the deep-seafloor search for the *Thresher*. However, the search was terminated in September 1963 with the onset of bad weather.¹²⁰ On May 18, 1964, the task group began new search operations. To augment its search capability, NRL had acquired the USNS *Mizar*, a retired cargo ship suited for launching and towing the deep-towed instrument vehicle, or “fish,” as it was called. NRL’s “fish” included a set of three cameras to photograph the wreckage, a side-scanning sonar to probe beyond camera range, two strobe lights, a magnetometer to locate the *Thresher* pressure hull, a transponder, a sonar pinger to measure the “fish’s” altitude, and a telemetry system. This unmanned vehicle, towed by *Mizar*, detected the *Thresher* hull after only eight hours of bottom operations. NRL’s photographs were later assembled into a photomosaic of most of the major parts of the sunken submarine.¹²¹

After NRL’s success in the *Thresher* search, the Laboratory was called upon to locate and recover a lost H-bomb off the coast of Spain in 1966, to locate and photograph the lost submarine USS *Scorpion* (SSN 589) in 1968, to assist in the recovery of the deep submersible *Alvin* in 1969, and to locate and photograph the lost French submarine *Eurydice* in 1970. NRL’s emergency search mission was transferred to other Navy organizations in 1980.

IMPACT

NRL-developed ocean search technology now resides in other government and private organizations. According to a 1966 commendation from the Marine Technology Society, NRL was responsible for “pioneering new techniques” and had “established a methodology for future ocean engineering.” Years later, after the *Titanic* was located by Dr. Ballard’s team, a former Navy supervisor of salvage stated before Congress that “the superb work of the scientific teams from NRL ... led the way for the [*Titanic*] search operation in the North Atlantic.”¹²²

PRIMARY REFERENCE DOCUMENTS

- Spies, F.N. and Maxwell, A.E., “Search for the *Thresher*,” *Science*, Vol. 145, No. 3630 (July 24, 1964).
- Andrews, F.A., “Search Operations in the Thresher Area—1964,” Section 1, *Naval Engineers Journal*, 549-561 (August 1965).
- Buchanan, C.L., “Search for the *Scorpion*: Organization and Ship Facilities,” *Proceedings of the 6th U.S. Navy Symposium on Military Oceanography*, Vol. 1, 58-63 (1969).

¹²⁰ Initial discovery of the bulk of the USS *Thresher* remains was made by the Navy’s deep submersible *Trieste* in September 1963.

¹²¹ Brundage, W., “NRL’s Deep Sea Floor Search Era - A Brief History of the NRL/MIZAR Search System and Its Major Achievements,” NRL Memorandum Report 6208, 29 November 1988.

¹²² Searle, W.F., Hearings on H.R. 3272, *The Titanic Maritime Memorial Act*, 29 October 1985.

TIMATION AND NAVSTAR GPS

ACHIEVEMENT

The NAVSTAR Global Positioning System (GPS) is designed to provide precise navigation data to military and civilian users by means of a constellation of 24 satellites. NAVSTAR is based on NRL's TIMATION (TIME/navigATION) research program, begun in 1964. R. Easton is recognized for conceiving the idea of the time-based navigational system, which eventually led to the GPS. NRL tested TIMATION concepts by developing and launching two small experimental satellites, *TIMATION I* and *TIMATION II*.

NRL launched *TIMATION I* on May 31, 1967, and *TIMATION II* on August 30, 1969. *TIMATION I* demonstrated that a surface vessel could be positioned to within 2/10 of a nautical mile and an aircraft to within 3/10 of a nautical mile using range measurements from a time-synchronized satellite. The TIMATION program proved that a system using a passive ranging technique, combined with highly accurate clocks, could provide the basis for a revolutionary navigation system with three-dimensional coverage (longitude, latitude, and altitude) throughout the world.

In 1973, NRL's program was merged with an Air Force program that was investigating similar techniques to form the NAVSTAR GPS program. *TIMATION III* was redesignated *Navigation Technology Satellite One (NTS-1)* and was launched in 1974 in connection with the new NAVSTAR effort. *NTS-1* carried the first atomic clocks into orbit. *NTS-2* was launched in 1977 as the first NAVSTAR satellite.¹²³

IMPACT

NAVSTAR's military and commercial applications are revolutionary and too numerous to enumerate here. In 1993, the National Aeronautic Association selected the GPS Team comprising NRL, the U.S. Air Force, Aerospace Corp., Rockwell International, and IBM Federal Systems Co. as winners of the 1992 Robert J. Collier Trophy, the most prestigious of all aviation awards in the U.S. The citation accompanying the trophy honors the GPS Team "for the most significant development for safe and efficient navigation and surveillance of air and spacecraft since the introduction of radio navigation 50 years ago." In 2005, R.L. Easton received the 2004 National Medal of Technology and Innovation from President George W. Bush for "his extensive pioneering achievements in spacecraft tracking, navigation and timing technology that led to the development of the NAVSTAR Global Positioning System."

PRIMARY REFERENCE DOCUMENTS

- U.S. Patent No. 3,789,409 to Easton, R.L., "Navigation System Using Satellites and Passive Ranging Techniques," January 29, 1974.
- Easton, R.L., "Optimum Altitudes for Passive Ranging Satellite Navigation Systems," *Naval Research Reviews*, August 1970.
- Easton, R.L., "The Role Of Time/Frequency in Navy Navigation Satellites," *Proceedings of the IEEE*, Vol. 60, No. 5, 557-563 (1972).
- Easton, R.L., et al., "The Contribution of Navigation Technology Satellites to the Global Positioning System," NRL Report 8360, December 28, 1979.

¹²³ Mitchell, P., "Navy's Mission in Space," *Oceanus*, Vol. 20, No. 2, 24 (1985); Glaeser, F., "Space: New Dimension in Naval Warfare," *U.S. Naval Institute Proceedings*, Vol. 113, 134 (May 1987); Easton, R.L., "The Navigation Technology Program," *Navigation, Journal of The Institute of Navigation*, Vol. 25, No. 2 (1978), 107-112.

RADIATION DETECTION

ACHIEVEMENT

The need for accurate and convenient dosimetry was recognized soon after the discovery of ionizing radiation. NRL's J.H. Schulman developed a radiophotoluminescent glass dosimeter in 1951. This dosimeter, the DT-60/PD, was accepted as a standard radiation monitor in the 1950s. Later, in the 1960s, Schulman and his colleagues developed a successful thermoluminescent dosimeter. Until NRL's thermoluminescent dosimeter, no such device had been considered a suitable replacement for the photographic film badge for health physics monitoring. Although the film badge was capable in accurately detecting a lower level of radiation, it was an uneconomical and inconvenient method that prevented rapid estimations of dose. NRL's dosimeter satisfied the detection range necessary without the disadvantages of the film badge.¹²⁴

Following the September 11, 2001, terror attacks, NRL developed the Mobile Imaging and Spectroscopic Threat Identification (MISTI) system, a sensitive mobile gamma-ray spectroscopy system constructed and sent to Lawrence Berkeley National Laboratory for use in detailed background gamma-ray surveys. MISTI's success led to the development of a second-generation system at NRL known as SuperMISTI, funded by the Office of Naval Research (ONR) and constructed in 2009. In 2012, SuperMISTI was one of eight instruments fielded on a barge in an ONR-sponsored test. SuperMISTI detected and identified sources in all scenarios. Because of its sensitivity and mobility, SuperMISTI was later employed by the DoD and the wider government community in research programs with applicability in terrestrial and maritime domains.

IMPACT

During the 1950s, the Navy and U.S. Air Force purchased several million of the NRL-originated dosimeters for personnel monitoring in case of nuclear attack. NRL's radiation dosimeters were used to provide the military with an effective, convenient, and economical diagnostic tool for radiation exposure. They also served medical uses in areas such as clinical radiology and cancer treatment.¹²⁵

The SuperMISTI system is a deployable asset of the Navy/DoD that has probed the limits of the possible with respect to standoff radiation detection, imaging, and localization. Passive detection and imaging of radioactive sources have been demonstrated on water at standoff distances of 300 feet.

PRIMARY REFERENCE DOCUMENTS

- U.S. Patent No. 2,524,839 to Schulman, J.H., Ginther, R.J., and Evans, L.W. (1950).
- Schulman, J.H., "Glass Dosimeters," NRL Memorandum Report 266 (1954).
- Schulman, J.H., Attix, F.H., West, E.J., and Ginther, R.J., "New Thermoluminescent Dosimeter," *Review of Scientific Instruments*, Vol. 31, 1263 (1960).
- Naval Surface Warfare Center Carderock Division (2013). *Results of the Office of Naval Research Sponsored Maritime WMD Detection Nuclear Threat Assessment (MANTA) Test Campaign* (Report No. NSWCCD-63-TR-2013/55).
- Hutcheson, A. L., et al., (2014). Maritime Detection of Radiological/Nuclear Threats with Hybrid Imaging System. *Homeland Security Affairs*.

¹²⁴ Schulman, J.H., et al., "Thermoluminescent Dosimeter," NRL Report 5326, 1 June 1959.

¹²⁵ Attix, F.H., Letter to H.J. Gimpel, 11 December 1972, NRL History Office; Spurny, Z., "Thermoluminescent Dosimetry," Institute of Nuclear Research, Czechoslovak Academy of Sciences, in *Atomic Energy Review*, Vol. 3, No. 2 (International Atomic Energy Agency, Vienna, 1965).

NUCLEAR REACTOR SAFETY

ACHIEVEMENT

A major application of NRL's fracture-test technology was the Laboratory's participation in the Heavy-Section Steel Technology Program conducted by the Nuclear Regulatory Commission. The technical issue was to determine the safety of nuclear reactor pressure vessels fabricated from 12-inch-thick steel as a function of the thickness and temperatures. NRL's W.S. Pellini and F.J. Loss built the apparatus and conducted experiments on full-thickness specimens to demonstrate the safety of the vessels. The program lasted several years and attracted international attention. The ASME Code rules for the operation of nuclear pressure vessels are based on the results of that program.¹²⁶

In the early 1960s, NRL demonstrated the potentially severe embrittlement of nuclear reactor steels to be a function of neutron exposure and irradiation (service) temperatures. While emphasizing light-water reactor pressure containment steels and their modes of failure after neutron exposure, the properties of other reactor component alloys were studied as well. Broad interest in NRL's work led to support by the Atomic Energy Commission and the Army.

This work is believed by most nuclear safety authorities to be a primary basis for assurance against catastrophic failure of radiation containment. In 1975, a definitive book by NRL's L.E. Steele, *Neutron Irradiation Embrittlement of Reactor Pressure Vessel Steels*, was published and became a landmark guide for specialists worldwide.¹²⁷

IMPACT

All military and civilian power reactors that feature a steel pressure shell are designed or operated, or both, on the fracture principles developed by NRL.¹²⁸ In addition, the Laboratory's work in radiation embrittlement in reactor pressure vessel steels led to the production of radiation-resistant steels, which are applied in new reactors throughout the world, and in the assurance of reactor containment safety in older reactors.

PRIMARY REFERENCE DOCUMENTS

- Pellini, W.S. and Puzak, P.P., "Practical Considerations in Applying Laboratory Fracture Test Criteria to Fracture-Safe Design of Pressure Vessels," *Journal of Engineering for Power*, October 1964.
- Hawthorne, J.R., Steele, L.E., and Pellini, W.S., "Effects of Nuclear Radiation on the Properties of Reactor Structural Materials," ASME 61-WA-332, No. 28, 1961.
- Steele, L.E., *Neutron Irradiation Embrittlement of Reactor Pressure Vessel Steels*, Technical Report 163 (International Atomic Energy Agency, Vienna, 1975).

¹²⁶ Lange, E.A., "Personal Account of Research Conducted Between 1950 and 1980 in the Metal Processing and the Strength of Metals Branches," in *Materials Science and Technology Division History*, NRL/PU-6300-93-240 (May 1993), 127.

¹²⁷ Steele, L.E., International Atomic Energy Agency Technical Report 163; quoted in *Materials Science and Technology Division History*, 131.

¹²⁸ Whitman, G.D., Robinson, G.C., and Sanolainen, A.W., "Technology of Steel Pressure Vessels for Water-Cooled Nuclear Reactors," ORNL-NSIC-21, December 1967, Chapter 7 uses NRL Report 6598, November 1967; cited by Irwin in *Materials Science and Technology Division History*, 101.

REMOTE SENSING OF THE UPPER ATMOSPHERE

ACHIEVEMENT

The concept of ultraviolet (UV) remote sensing and the Special Sensor Ultraviolet Limb Imager (SSULI) operational sensors are examples of Navy research culminating in the transition of technology. The observation of spectral lines in the altitude range from about 120 to several hundred kilometers with instruments developed by NRL's P. Mange during the 1960s and flown on NASA's Orbiting Geophysical Observatories enabled NASA and NRL to recognize the correspondence between UV emission lines from oxygen and local electron density in the ionosphere.¹²⁹

UV images of the Earth taken from the surface of the Moon with the Far UV Electrographic Camera, built by NRL's G. Carruthers for the *Apollo 16* lunar mission, revealed details about arcs of charged particles stretching around the globe — phenomena under study today as the interplay between Earth and space weather. Research by NRL's R.R. Meier¹³⁰ in the 1970s provided firm theoretical basis for this correspondence. The UV camera remains on the Moon and a backup is on display at the National Air and Space Museum. A version of this instrument was deployed on Skylab in 1974 to observe and study comets.¹³¹

Beginning in the 1980s, NRL's work led to new insights and to the design of space instruments for recording atmospheric data and converting them into parameters of interest to the DoD.¹³² In 1985, NRL initiated the Atmospheric and Ionospheric Remote Sensing Program, which developed the UV remote sensing concept. During the 1980s, the DoD Space Forecast Center and the Defense Meteorological Satellite Program recognized that requirements for global atmospheric space weather data were not being met. NRL's SSULI sensors were developed to meet those operational requirements.

Success of these early programs led to further instrument design and spaceflight missions that included UV sensors, as well as near-UV/visible sensors, and GPS radio occultation sensors. The continued investment of remote sensing spaceflight sensor technology, coupled with the advent of small satellites, has led to an evolution of atmospheric sensing, reducing the size, weight, and power of the instrumentation.

IMPACT

Global remote sensing of the upper atmosphere now produces global maps of electron density, neutral density, temperatures and winds. This capability provides the basis for a new kind of forecasting of upper atmospheric and "space weather" characteristics, much as global measurements of cloud cover led to greatly improved tropospheric weather forecasting. For his invention of the Far UV Electrographic Camera, G. Carruthers received the 2011 National Medal of Technology and Innovation from President Barack Obama.

PRIMARY REFERENCE DOCUMENTS

- Carruthers, G. and Page, T., "Apollo 16 Far UV Images of the Polar Auroras, Tropical Airglow Belts and General Airglow," *Journal of Geophysical Research*, Vol. 81, 483-496, (1976).
- Meier, R.R., "Overview of Ultraviolet Remote Sensing of the Ionosphere," NRL MR 5292, 1984.

¹²⁹ Chandra, S., *et al.*, "Remote Sensing of the Ionospheric F Layer by Use of O I 6300-Å and O I 1356- Å Observations," *Journal of Geophysical Research*, Vol. 80, 2327-2332 (1975).

¹³⁰ Meier, R.R. and Opal, C.B., "Tropical UV Arcs," *Journal of Geophysical Research*, Vol. 78, 3189-3193 (1973).

¹³¹ Meier, R.R. and Opal, C.B., Keller, H.U., Page, L., and Carruthers, G.R., "Hydrogen Production Rates from Lyman- α Images of Comet Kohoutek (1973XII)," *Astronomy and Astrophysics*, 52, 283-290 (1976).

¹³² McCoy, *et al.*, "Special Sensor Ultraviolet Limb Imager: An Ionospheric and Neutral Density Profiler for the Defense Meteorological Satellite Program Satellites," *Optical Engineering*, Vol. 33, 423-429 (1994).

SECURE VOICE COMMUNICATION

ACHIEVEMENT

The linear predictive coder (LPC) is a means to represent the speech spectrum efficiently. In the LPC representation of speech, the speech spectral envelope is represented by an all-pole spectrum. In 1973, NRL's G.S. Kang developed the world's first LPC prototype capable of operating in real time to encode speech at low data rates. NRL's efforts generated an impetus to modernize DoD tactical secure voice communication equipment. Subsequently, NRL incorporated the LPC concept into the DoD Advanced Narrowband Digital Voice Terminal (ANDVT) that was under development at the time. Later, Kang incorporated the ANDVT voice encoding algorithm in Federal Standard 1015.

The computational steps required to execute LPC processing were enormous. In fact, it was doubted that LPC could be implemented as a voice communication device. But, in 1973, NRL was successful in implementing a real-time LPC telephone operating at 2,400, 3,600, and 4,800 bits per second because the Laboratory had developed a computationally efficient iterative solution to the LPC analysis.

In the 1990s, the DoD introduced a new narrowband voice-processing algorithm called the Mixed-Excitation Linear Predictor for supporting tactical communications. Due to its earlier research in secure voice processing and successful development of the LPC, NRL was asked to find a way to translate the old and new voice data so that old and new tactical phones could interoperate directly. Building on its early work, NRL's speech-encoding experts took only six weeks to invent a voice communication processing system that provided the needed interoperability, and thus saved the DoD millions of dollars in replacement and transition costs. The resulting algorithm also improved speech intelligibility and was widely disseminated across DoD and NATO for tactical communications.

IMPACT

NRL's development in 1973 of the world's first LPC prototype capable of operating in real time to encode speech at low data rates brought a complete upgrading of military tactical secure voice communication equipment in the 1970s. The LPC-based ANDVT replaced the old channel vocoders. By 2005, 40,000 ANDVTs had been deployed by the Navy, the Air Force, the Army, allied forces, and other government agencies to support tactical secure voice communications. In addition, much of this research into computationally efficient LPC analysis was widely adopted into the cellphone industry and is still utilized today.

In the 1990s, NRL's narrowband voice translation system provided direct interoperability between old and new speech parameters, allowing new and legacy ANDVT phones to work together. The result was that 40,000 legacy phones were not retired prematurely and there was no long transition period between new and old systems. Continued use of the legacy units yielded a one-time cost savings of nearly \$460 million.

PRIMARY REFERENCE DOCUMENTS

- Kang, G.S., "Application of Linear Prediction Encoding to a Narrowband Voice Digitizer," NRL Report 7774, 1974.
- Kang, G.S. and Heide, D.A., "Transcoding Between Two DoD Narrowband Voice Encoding Algorithms (LPC-10 and MELP)," NRL Formal Report 9921 (1999).
- Office of Naval Research, 2001 Vice Admiral Harold G. Bowen Award to NRL's G.S. Kang and L.J. Fransen.
- "Naval Advanced Secure Voice Architecture," SPAWAR Systems Center, (Version 0.1), February 26, 2004, AV-68

SUBMARINE HABITABILITY

ACHIEVEMENT

In the 1950s, as the age of the nuclear submarine emerged, the requirement grew for extending the capabilities of closed-cycle atmospheres for periods up to 90 days. The need for new atmosphere habitability capabilities was evident when NRL participated in a scientific cruise of the first nuclear submarine, USS *Nautilus*, in 1956. Its atmosphere was found to be “loaded” with pollutants, such as carbon dioxide, carbon monoxide, hydrogen, and hydrocarbons. NRL formed a team to solve the problem. In the 1950s and 1960s, this effort led to the CO/H₂ Hopcalite burner, the monoethanol amine CO₂ scrubber, and the adsorbent carbon bed. The major source of the hydrocarbons was paint thinners. As a result, painting was prohibited immediately prior to submergence and during deployment.

It was also apparent that an analytical instrument was needed to monitor contaminants.¹³³ In the 1970s, NRL and its private-sector partners convinced the Navy that mass spectrometry was the technique of choice for atmosphere analysis onboard nuclear submarines. NRL evaluated prototype systems that became the basis of the Central Atmosphere Monitoring System Mark-I (CAMS-I). These systems were installed aboard all nuclear submarines, replacing previous, poorly performing analyzers. Later, NRL’s research capabilities in mass spectrometry were used to formulate the design of the next-generation analyzer, the CAMS-II. NRL directed the development, laboratory testing, and at-sea trials of the prototype. The CAMS-II is installed in Trident- and Seawolf-class submarines. NRL was also successful in transferring this technology to industry and in convincing the British Navy to use the CAMS-II aboard Royal Navy submarines.

IMPACT

Several NRL technologies led to the purification of submarine atmospheres. CAMS replaced atmosphere analyzers that were always on the “top ten” problem list of submarines. Combined, these technologies enable the Navy to operate its submarine fleet on extended deployments and at the same time be assured as to the safety of their atmospheres. The commercial version of CAMS, developed by Perkin Elmer for IBM,¹³⁴ has been used in semiconductor processing facilities to provide continuous monitoring of a variety of hazardous materials. The advantages of CAMS are its ability to measure many different atmosphere constituents, from parts-per-billion to 100% levels, and its reliability.

Following the transition of CAMS to industry and the fleet, NRL has continued to address submarine habitability issues by evaluating portable chemical detection devices for use on submarines and verifying the efficacy of the materials control program put into place for the construction of Virginia-class submarines.

PRIMARY REFERENCE DOCUMENTS

- Carhart, H.W. and Piatt, V.R., “Present Status of Chemical Research in Atmosphere Purification and Control on Nuclear Powered Submarines,” NRL Report 6053, December 31, 1963.
- Saalfeld, F.E. and Wyatt, J.R., “NRL’s Central Atmosphere Monitor Program,” NRL Report 3432, December 1976.
- Wyatt, J.R., “Recent Developments in Atmosphere Monitoring On Board Nuclear Submarines,” JANNAF Safety and Environmental Protection Subcommittee, CPIA 436 (1985).
- Johnson, K.J., Rose-Pehrsson, S.L., DiGiulio, C., and Burnside, D., “USS *Virginia* Atmospheric Sea Trials: Analytical Results,” NRL Memo Report, NRL/MR/6180--06-8940, March 6, 2006.

¹³³ DeCorpo, J.J., Wyatt, J.R., Saalfeld, F.E., “Atmospheric Monitoring in Submersibles,” *ASME 80-ENAS-31* (1981).

¹³⁴ Krieger, J.H., “System Continuously Monitors Air Quality in Industrial Process Sites,” *C&EN*, 12 August 1985.

FLUX-CORRECTED TRANSPORT

ACHIEVEMENT

In the late 1960s, NRL conducted theoretical and computational investigations of high-altitude nuclear effects (HANE) for the Defense Nuclear Agency. During 1970 and 1971, to perform this work, NRL had to develop an entirely new technique to solve the fundamental conservation equations describing fluid dynamics computationally. The technique, now called flux-corrected transport (FCT), enabled accurate calculations of strong shocks, high-resolution turbulence, and other steep-gradient phenomena by eliminating the numerical oscillations, ripples, and excess diffusion that had plagued all previous techniques for decades.

In addition to the HANE research, FCT has been employed in missile silo design, nuclear and conventional weapons design, naval oceanography, non-acoustic antisubmarine warfare, and atmospheric communications research. Other uses include research in civil hydrodynamics and water resources, mine safety, atmospheric pollution transport, supernova explosions, solar weather prediction, laser and ion-beam fusion, aerodynamics, and base and force protection against weapons of mass destruction.

IMPACT

With over 1,000 citations, the original paper on FCT was NRL's most cited publication between 1973 and 1988. Over 500 computational laboratories, universities, and companies dealing with fluid flow problems that impact military operations, civil projects, and public health and safety have adopted this technique. More recently, FCT is being used for 3D urban airflow computations that serve as the high-accuracy basis of CT-Analyst®, a faster-than-real-time tool for urban defense against weapons of mass destruction. In fact, this tool was developed at NRL using FCT.

A conference entitled "High-Resolution Schemes for Convection Dominated Flows: 30 Years of FCT" was held in Dortmund, Germany in 2003. Ten years later, in 2013, the journal *Computers and Fluids* solicited an invited review article on FCT by NRL's J. Boris entitled "Flux-Corrected Transport Looks at Forty" to commemorate this development.

PRIMARY REFERENCE DOCUMENTS

- Boris, J.P., "A Fluid Transport Algorithm That Works," Computing as a Language of Physics, 171-189, (IAEA-SMR-9/18, International Centre for Theoretical Physics, 1971).
- Boris, J.P. and Book, D.L., "Flux-Corrected Transport. I. SHASTA, A Fluid Transport Algorithm That Works," *Journal of Computational Physics*, Vol. 11, 38 (1973).
- Book, D.L., Boris, J.P., and Hain, K.H., "Flux-Corrected Transport II: Generalization of the Method," *Journal of Computational Physics*, Vol. 18, 248 (1975).
- Boris, J.P. and Book, D.L., "Flux-Corrected Transport III: Minimal Error FCT Algorithms," *Journal of Computational Physics*, Vol. 20, 397 (1976)
- J.P. Boris, J.P., Landsberg, A.M., E.S. Oran, E.S. and Gardner, J.H., "LCPFCT – A Flux-Corrected Transport Algorithm for Solving Generalized Continuity Equations," NRL Memorandum Report 6410-93-7192, December 1992.

HIGH-POWER, HIGH-CURRENT PULSED-POWER GENERATORS

ACHIEVEMENT

In the 1960s, high-power, pulsed-power research was driven by the need to produce intense sources of radiation in the laboratory to simulate the effects of nuclear weapons on commercial and military systems. The U.K. and the U.S. were exploring ways to generate 1 MA at 1 MV for 50 ns (5×10^{-8} s). NRL had pioneered the use of water as a dielectric in a lower-power, low-voltage water capacitor used to drive an exploding wire, then, ten years later, in 1968, NRL designed and built the Gamble I pulsed-power generator (750 kV, 500 kA, 50 ns). This was the first high-power, low-impedance facility to use demineralized water as a dielectric-energy-storage medium at high voltage. The advantages of water as a capacitive-energy-storage medium are that it has a high dielectric constant, is self-healing to electrical breakdowns, and acts as a good insulator for high-voltage pulses of 10^{-5} s duration or less. J. Martin and I. Smith in England performed water breakdown measurements in 1965 that provided the critical design data for Gamble I.

The success of Gamble I led NRL to build the Gamble II generator that was, when completed in 1970, the largest pulsed-power generator of its kind in the world, capable of delivering 1 MV across a 1-ohm load for 50 ns. The 1 TW output power was more than the entire electrical power capacity of the U.S. At that time, the primary purpose for this capability was to provide an intense radiation source for simulating nuclear-weapon effects in the laboratory to supplement the U.S. underground simulation effects testing program. Military electronics were exposed to this radiation to assess their survivability in a real nuclear environment. Gamble III is being constructed now, with initial operations planned in 2026.

IMPACT

Gamble I and II were the prototypes for all modern high-power, low-impedance generators now in use in industrial laboratories, universities, DoD and DoE laboratories, and foreign laboratories. In addition to being critical for important weapon-effects simulations, pulsed-power technology based on water-dielectric capacitive energy storage has also generated other areas of research on high-power electron and ion beams and soft X-rays from z-pinch plasmas for inertial confinement fusion, matter at high-energy densities, directed-energy weapons, high-power microwaves, flash X-ray radiography, pumping gas lasers, and X-ray laser technology.¹³⁵

PRIMARY REFERENCE DOCUMENTS

- Scherrer, V.E., "The NRL-AFSWP Exploded Wire Research Program," in *Exploding Wires*, W.G. Chace and H.K. Moore, eds. (Plenum Press, Inc., New York, 1959).
- Martin, J.C. and Smith, I.D., "Dielectric Strength Notes," AWRE (England), November 1965.
- Lupton, W.H., Frame, J.F., and Vitkovitsky, I.M., "Gamble I Current Generator," DASIAC Report 80, Sept. 1968.
- Shipman, J.D., Jr., "The Electrical Design of the NRL Gamble II Pulse Generator," *IEEE Transactions on Nuclear Science*, Vol. NS-18, 255 (1971).

¹³⁵ Cooperstein, G., "New Horizons in Pulsed-Power Research," 1988 *NRL Review*, NRL Publication 148-4770 (July 1989), 47; and Cooperstein, G., Condon, J.J., and Boller, J.R., "The Gamble I Pulsed Electron Beam Generator," *Journal of Vacuum Science Technology*, Vol. 10, 961 (1973).

MARINE SURFACE MONOLAYERS

ACHIEVEMENT

Beginning in the early 1960s, NRL performed research on the nature and effects of surface-active substances at critical interfaces in the marine environment. Much of this early basic research was guided by W. Zisman. This research led to three applications:

Oil Spill Control — NRL discovered that certain invisibly thin surface films applied around oil spilled on water could compress the oil into a much smaller area and maintain the oil in a thick layer, thereby enhancing the efficiency of oil-recovery operations. While developing the technique, NRL worked with JBF Scientific Corp., a manufacturer of oil recovery vessels. Following EPA approval, the method was incorporated into Navy pollution control programs for harbors and bays. It has also been used in commercial training for oil spill control.¹³⁶

Seamarker — Used in combination with the standard green dye, NRL's surface-active compound spontaneously spreads rapidly over the sea surface and makes a much larger mark than the dye alone. Because of the damping effect of the compound on small capillary waves on the sea surface, the one-molecule-thick films are readily detectable both visually and by radar, with radar providing nighttime and poor-weather detectability.

Mosquito Control — NRL developed a thin surface film that prevents mosquitos in the pupal and larval stages from attaching to the water's surface, where they breathe and feed. This causes them to drown, thus killing by physical, not toxic, means. No pesticide is required nor is a petroleum-based solvent needed to deliver the compound. The method has proven effective against mosquito genera, which are carriers of tropical diseases, including malaria. The commercially manufactured, nontoxic compound has been licensed for application [NRL-LIC-96-016] and has been used in mosquito control districts across the U.S.

IMPACT

The mosquito control technique has reduced public health hazards by controlling mosquitos using a more environmentally safe method in place of toxins. The oil-spill control technique has reduced damage to property, the fishing industry, and the environment. The sea marker benefits the military in air-sea rescue operations.

PRIMARY REFERENCE DOCUMENTS

- Pomerantz, P., Clinton, W.C., and Zisman, W.A., "Spreading Pressure, Interfacial Tension, and Adhesion Energy of the Lower Alkanes, Alkenes, and Alkyl Benzenes on Water," NRL Report 6495, January 19, 1967.
- U.S. Patent No. 3,676,359 to Garrett, W.D. and Barger, W.R., "Chemical Sea Surface Marker," July 11, 1972.
- U.S. Patent No. 4,160,033 to Garrett, W.D. and Barger, W.R., "Method for the Control of Mosquitos by the Use of Film-Forming Materials," July 3, 1979.

¹³⁶ Barger, W.R., Garrett, W.D., et al., "Instruction Manual: U.S. Navy Oil Spill Containment and Cleanup Kit," NAVSHIPS 0994-013, Naval Materiel Command (1973); "Oil and Hazardous Material Control Training Division," Texas A&M University System, sponsored by the American Petroleum Institute.

WIND SPEED MEASUREMENT USING MICROWAVE IMAGING

ACHIEVEMENT

NRL pioneered the use of passive microwave sensing to measure ocean surface roughness and then to use those measurements to derive the surface wind speed. Surface waves, called capillary waves, are excited by the wind. The mechanism is that the wind must have zero speed at the surface so the drag force exerted by the wind is dissipated in these small waves. The interactions between the wind and the capillary waves result in distinct increases in the thermal microwave emission from the ocean. This increase can be measured with a microwave radiometer and the increased emission can then be used to derive ocean wind speed.

In aircraft and tower experiments from 1966 to 1977, NRL's J.P. Hollinger recognized that this phenomenon could be used to fill the Navy's need to measure ocean winds. He promoted the inclusion of the Special Sensor Microwave Imager (SSM/I) on the Defense Meteorological Satellite Program (DMSP) and set its specification by chairing the DoD specification panel in 1978. The first SSM/I was launched on DMSP F8 in 1987. Hollinger led the calibration validation effort that brought the SSM/I into operational use in 1988.

Following the successful SSM/I series of sensors, an improved version, SSM/IS or imaging sounder, entered service on DMSP F16 in 2003. NRL's WindSat satellite radiometer built on the success of SSM/I and SSM/IS by adding polarimetry to also sense wind direction. The Weather System Follow-on, DoD's next-generation weather satellite system, is currently in development and includes a polarimetric microwave radiometer capable of measuring wind speed and direction.

IMPACT

The Navy requires ocean wind measurements to provide the U.S. fleet with the most accurate meteorological forecasts possible. Due in large measure to NRL's efforts, satellite passive microwave sensing is the primary operational source of ocean surface wind speed used by both civilian and military forecasters. It also provides data as input to numerical weather prediction models of the Fleet Numerical Meteorological and Oceanographic Center, the National Oceanic and Atmospheric Administration, and the European Center for Medium-range Weather Forecasting.

PRIMARY REFERENCE DOCUMENTS

- Hollinger, J.P., "Passive Microwave Measurements of Sea Surface Roughness," *Journal of Geophysical Research*, Vol. 75, 5209 (1970).
- Hollinger, J.P., "Introduction to Special Issue on the Defense Meteorological Satellite Program: Calibration and Validation of the Special Sensor Microwave Imager," *IEEE Transactions on Geoscience and Remote Sensing*, Vol. 28, 779 (1980).
- Hollinger, J.P. 1989: *DMSP Special Sensor Microwave/Imager Calibration/Validation*. Final Report, Vol. I., Space Sensing Branch, Naval Research Laboratory, Washington D.C.

SPACEBORNE SOLAR CORONAGRAPHS

ACHIEVEMENT

The study of the Sun's corona, its outermost atmosphere, is a fundamental aspect of solar science. At first, the corona could only be seen during the brief interval of a full solar eclipse. Ground-based telescopes allowed regular observations of the corona, but close to the Sun's surface. With the advent of space-based instrumentation, routine observations out to large distances from the Sun became possible. The first coronagraph for this purpose was developed and launched on a sounding rocket by NRL in 1963. Its success gave birth to a new understanding of the solar atmosphere.

Then on December 14, 1971, the orbiting NRL coronagraph on NASA's OSO-7 satellite captured images of an immense explosion of solar material moving through the instrument's field of view. This was a major discovery. A new phenomenon, called the coronal mass ejection (CME), was born. The measured speed of the outburst was about 600 miles/s and its estimated size was many times the size of the Earth.¹³⁷ The frequency and the space weather impact of such events was established by NRL's SOLWIND coronagraph, which launched in 1979. SOLWIND led to the Large Angle and Spectroscopic Coronagraph (LASCO), which was jointly developed for the ESA-NASA Solar and Heliospheric Observatory (SOHO) mission by NRL and labs in Europe. Launched in 1995, SOHO verified that CMEs produce geomagnetic storms at Earth, explained the relationship between flares and CMEs, and established the magnetic flux rope as the probable configuration. LASCO still operates today and helps to predict CME arrival times at Earth.

IMPACT

Spaceborne solar coronagraphs are essential to space weather models of CMEs. NRL was first to demonstrate the existence of CMEs and their role in major geomagnetic storms, which are disruptive of communications, power, and military detection systems. If these storms are severe, astronauts and equipment in space can be at risk. NRL's scientific discovery led to operational space weather. In 2018, the secretary of the Navy directed that "DON organizations shall promote investment in associated technologies that ...manage, reduce, or mitigate impacts from ... space weather events, including CMEs."¹³⁸

PRIMARY REFERENCE DOCUMENTS

- Tousey, R. 1973, *Space Research XIII*, Vol. 2, 713
- Koomen, M.J., et al., "White Light Coronagraph in OSO-7," *Applied Optics*, Vol. 14, 753 (1975).
- Brueckner, G.E., et al., "The Large Angle Spectrometric Coronagraph (LASCO)," *Solar Physics*, Vol. 162, 357-402 (1995).
- Howard, R. A., Michels, D. J., Sheeley, N. R., Jr., Koomen, M. J., "The observation of a coronal transient directed at Earth", *Astrophysical Journal*, Vol. 263, L101-L104 (1982)
- Sheeley, N. R. et al., "Coronal mass ejections and interplanetary shocks", *Journal of Geophysical Research*, Vol. 90, 163-176 (1985)
- Chen, J., et al., "Evidence of an Erupting Magnetic Flux Rope: LASCO Coronal Mass Ejection of 1997 April 13", *The Astrophysical Journal*, Vol. 490, L191 (1997)
- Thernisien, A.F., and Howard, R.A., "Modeling of Flux Rope Coronal Mass Ejections". *Astrophysical Journal*, Vol. 652, 763-773, (2006).

¹³⁷ Dahlburg, J., et al., *NRL Space Science Division Research Achievements* (MR/7600-15-9637), October 2015, 13.

¹³⁸ SECNAVINST 2400.2A, "Electromagnetic Environmental Effects and Space Weather Event Preparedness Policy and Management," (2 February 2018).

FIBER-OPTIC INTERFEROMETRIC ACOUSTIC SENSORS

ACHIEVEMENT

In 1977, NRL demonstrated the world's first fiber-optic interferometric acoustic sensor.¹³⁹ Based on this work, NRL received the first U.S. patent awarded for an optical interferometric sensor to measure external fields. This device focused on acoustic fields. From the beginning, it was viewed as a generic device in that it would be capable of responding to other external perturbations — electric field, magnetic field, temperature, etc. — depending on the design of the fiber coating or the mounting structure.

NRL's work launched Navy, DoD, and national interest in fiber-optic acoustic sensors in particular, and fiber-optic nonacoustic sensors in general. In 1978, based on the fiber acoustic sensor results, NRL conducted the first Navy/DoD program in fiber-optic sensor systems (FOSS) — the vanguard of a rapidly growing interest in fiber interferometric sensors. NRL was the leader in this technology in the late 1970s to early 1980s. Other organizations, such as the Naval Underwater Warfare Center, the Naval Surface Warfare Center, and Litton, joined NRL in developing systems based on these sensors.

A number of sensor system technologies based on interferometric fiber acoustic sensors were successfully demonstrated. One such system was an all-optical towed array (AOTA) with a full complement of fiber-optic acoustic sensors. In 1983, fiber-optic acoustic sensors were first tested at sea. Based on the results, an AOTA Advanced Technology Demonstration was initiated. Successfully completed in 1990, it met all performance goals and showed that the concept was a cost-effective alternative to piezoceramic technology.

IMPACT

NRL's original invention, and the subsequent FOSS program, led to the now-ubiquitous presence of fiber-optic sensor devices. These devices resulting from NRL's pioneering work have been exploited in numerous sensor-related areas, including acoustic, magnetic, electric, thermal, vibration, and flow applications. Commercial versions of these sensors have been applied to traffic control, medical care, construction safety, and seismology. Military applications are also numerous. For example, the Lightweight Wide Aperture Array, a large-channel-count fiber-optic, acoustic array, is deployed on the Navy's Virginia-class nuclear submarines.

PRIMARY REFERENCE DOCUMENTS

- Bucaro, J.A., Dardy, H.D., and Carome, E.F., "Fiber Optic Hydrophone," *Journal of the Acoustical Society of America*, Vol. 62, 1302-1304 (1977).
- Bucaro, J.A., Dardy, H.D., and Carome, E.F., "Optical Fiber Acoustic Sensor," *Applied Optics*, Vol. 16, 1761-1762 (July 1977).
- U.S. Patent No. 4,162,397 to Bucaro, J.A., Dardy, H.D., and Carome, E.F., "Fiber Optic Acoustic Sensor," July 1979.
- Giallorenzi, T.G., Bucaro, J., Dandridge, A., Sigel, Jr., G.H., Cole, J., Rashleigh, S., and Priest, R., "Optical Fiber Sensor Technology," *IEEE Journal of Quantum Electronics*, 626 (1982).
- U.S. Patent No. 4,648,083 to Giallorenzi, T.G., "All-Optical Towed and Conformal Arrays," March 3, 1987.
- U.S. Patent No. 5,394,378 to Dandridge, A et al., "Hydrophone transduction mechanism," 1993
- Dandridge A, *et al*, "Development of the Fiber Optic Wide Aperture Array: From Initial Development to Production". NRL Review, (NRL/PU/3430-04-471), 177-179, 2004.

¹³⁹ The possibility of incorporating optical fibers into bulk interferometers to detect weak acoustic signals was also demonstrated independently by Cole et al. in November 1977 (Cole, J.H., Johnson, R.L., and Bhuta, P.G., *Journal of the Acoustical Society of America*, Vol. 62, 1136 (1977)). (NRL published its paper in July 1977.)

SEMI-INSULATING GALLIUM ARSENIDE CRYSTALS

ACHIEVEMENT

In the 1970s, NRL invented and developed a liquid-encapsulated Czochralski (LEC) method of compounding and growing high-purity single crystals of gallium arsenide (GaAs) that were semi-insulating in nature without the need for doping. Because of their high-purity-semiconductor and semi-insulating properties, wafers made from these crystals could be used simultaneously as a dielectric and ion-implanted active semiconductor layer material to produce high-performance microwave and millimeter-wave devices and integrated circuits. This development was important because transistors and microcircuits made of silicon, the most common semiconductor material used at the time, operated poorly at microwave frequencies. NRL performed the basic process development, demonstrated the principles for achieving the high-purity semi-insulating GaAs substrate, and was instrumental in transferring the technology to industry for commercialization.

This cost-effective method of GaAs wafer production was important because it led to the early adoption of high-performance GaAs devices and monolithic microwave integrated circuits (MMICs) in military microwave and millimeter-wave systems.

Cost reduction is also critical to the competitiveness of U.S. companies. NRL's technology was adopted by major U.S. industrial firms, such as Rockwell International, Westinghouse, Texas Instruments, and Hughes Research.¹⁴⁰ In commending NRL's achievement, one U.S. company claimed that in 1980, approximately 100% of the GaAs device industry was in Japan, but that in 1997, the GaAs integrated circuit industry would realize sales of \$447 M, with American companies representing 65% of that total.¹⁴¹

IMPACT

NRL's achievement yielded a key enabling technology for GaAs monolithic microwave integrated circuits. Military systems using these technologies are in all forms of military radar systems, electronic warfare systems, communications systems, satellite systems, and many weapons systems such as HARM, Phoenix missile, AIM-9L, and AMRAAM. Commercial uses are ubiquitous and include weather and navigation radar, communications systems including cellular and satellite systems, and wireless LANs. The technology demonstrated audited savings to the military for the 10-year period from 1979 to 1989 of over \$560 million (in 1986 dollars).¹⁴² This is all the more impressive given that the original investment in NRL's research was \$528,000.¹⁴³

PRIMARY REFERENCE DOCUMENTS

- Swiggard, E.M., et al., "GaAs Synthesized in Pyrolytic Boron Nitride," *Gallium Arsenide and Related Compounds 1976* (Institute of Physics Conference Series 33b), 23.
- Henry, R.L. and Swiggard, E.M., "LEC Growth of InP and GaAs Using PBN Crucibles," *Gallium Arsenide and Related Compounds 1976* (Institute of Physics Conference Series), 28.
- Lessoff, H., "Non-Uniform Etching of Single Crystal GaAs," *Material Letters*, Vol. 3, 251 (1985).

¹⁴⁰ Presidential Letter of Commendation to H. Lessoff, nomination of 1985, awarded by President Reagan in 1988.

¹⁴¹ Letter to H. Lessoff from J. Vaughan (Vice President, Business Development), M/A-COM, 21 September 1997.

¹⁴² Commander, NAVAIRSYSCOM.

¹⁴³ Commander, NAVAIRSYSCOM, Letter of Commendation to H. Lessoff and E. Swiggard (3 March 1986).

SUPER-RAPID-BLOOMING OFFBOARD CHAFF

ACHIEVEMENT

NRL developed the first widespread decoy system applied to all major Navy surface combatants. The MK-36 and the MK-182 cartridge were successfully operationally evaluated in 1977. Because of the operational success of this system, a follow-on international program was established to provide the continual product improvements that result from ongoing innovation. This international program led to the successful development of the MK-214 and MK-216 cartridges, which entered the fleet in 1987 and 1988, respectively, and which are in current use. The super-rapid-blooming offboard chaff (Super RBOC) system and its family of decoys has been used by the U.S. Navy and its allies for many years.

IMPACT

Super RBOC and its family of decoys significantly improved the Navy's capability to conduct electronic warfare from its surface combatants. It was a major advancement in the state of the art in its ability to rapidly produce an alternate target for the protection of ships against anti-shipping cruise missiles. With the extensive proliferation of the cruise missile threat throughout the world, this solution was especially timely and critical to the survivability of the fleet. It was subsequently replaced by the active decoy Nulka, jointly developed by the U.S. and Australia, which is on virtually all capital ships within the U.S. and Australian navies. Other allied navies still deploy the Super RBOC system.

PRIMARY REFERENCE DOCUMENTS

- COMTHIRDFLT TACMEMO 221-3-74, "Use of Chaff in Anti-Ship Missile Defense," May 29, 1975.
- Report on the CNO Project 114-DT-III, "Technical Evaluation (TECHEVAL) of the Super RBOC System," April 11, 1977.
- OPTEVFOR Report on CNO Project 114-OT-III, "Operational Evaluation of Super RBOC," January 20, 1977.
- OPTEVFOR, "Follow-On Operational Evaluation of Super RBOC," Report 3960-12 (114-OT-IV), June 14, 1977.
- "The Electronic Warfare Suite for the USS *NEW JERSEY*," NRL Memorandum Report 4841, July 1982.
- "NATO SEA GNAT Radio Frequency (RF) Seduction Cartridge," Commander Operational Test and Evaluation Force Report 3960 (621-1-OT-II), October 3, 1984.

ION-IMPLANTATION METALLURGY

ACHIEVEMENT

In the late 1970s, NRL researchers devised a surface modification technique to develop new metal alloys with enhanced properties and operating lifetimes by accelerating ions (electrified atoms) and implanting them into the surface of ordinary materials. This process, known as ion-implantation metallurgy, has found great application in improving the performance, increasing the corrosion resistance, and reducing friction and wear of critical components such as ball bearings.

The alloy ASA M50 and M50 NIL are the primary bearing steels used by the Navy in its turboshaft engines. Since the Navy operates over salt water, the environment is very corrosive compared to that experienced by Air Force and commercial aircraft. Refurbishment and replacement of bearings, which, in the 1980s, cost up to \$3,000 each, was a significant maintenance expense. Turboshaft bearings must maintain high rolling contact fatigue resistance at relatively high operating temperatures; therefore, stainless steel cannot be used. Protection of the bearings with an anticorrosion coating had been unsuccessful due to delamination of the coatings. NRL's research in ion implantation offered an answer to this problem.

Bearings were ion implanted with Cr ions that produced a 75-nm-thick stainless steel layer on the low-alloy bearing steels ASA M50 and 52100. This improved by a factor of 2 to 10 the service life and shelf life of the expensive bearings and other components for which the downtime required for replacement is high. This research stimulated a Manufacturing Technology Program for ion implantation of bearings with Cr or Cr+P ions. Results showed that the bearings could be implanted for between \$70 and \$170 per bearing, and that this cost was more than paid for by the average increase in the bearing service life of 2.5 times. The Navy program demonstrated to three commercial companies in the U.S. and Europe that implantation of rolling element bearings could be part of their ion-implantation business operations. A primary commercial interest in the process was for instrument bearings. Motivated by the Navy program, the U.S. Army undertook a study of ion implantation of tool steels for helicopter rework. The study was successful, and as a result, the Army purchased an ion-implantation facility for installation at a Corpus Christi Army helicopter rework facility.

IMPACT

The early NRL work established the state of the art for ion-implantation metallurgy. In one application, NRL's technology led to advances in corrosion protection of ball bearings on naval aircraft, thus providing a solution to an important Navy problem. It also benefitted the U.S. Army and found application in commercial processes.

PRIMARY REFERENCE DOCUMENTS

- Hubler, G.K., Valori, R., and Popgoshev, D., "Ion Implantation of Bearing Surfaces for Corrosion Resistance," *Journal of Lubrication Technology*, Vol. 105, 53A (1983).
- Yang, Y.F., *et al.*, "Application of Ion Implantation for the Improvement of Localized Corrosion Resistance of M50 Bearing Steel," *Thin Film Solids*, Vol. 63, 11-18 (1979).
- Smidt, F.A., Sartwell, B.D., and Bunker, S.N., "U.S. Navy Manufacturing Technology Program on Ion Implantation," *Materials Science and Engineering*, Vol. 90, 385 (1987).
- Picraux, S.T., "Ion Implantation Metallurgy," *Physics Today*, Vol. 37, No. 11, 38 (1984).

FLUORINATED NETWORK POLYMERS

ACHIEVEMENT

Polyurethane coatings were introduced in the 1960s as a material to line fuel tanks used for long-term storage of aviation, marine, and vehicle fuels. This was done as a means of achieving longer lifetimes for the fuel tanks, cleaner fuels for aircraft and ships, and the elimination of fuel leakage through the porous welds of these large, underground, steel tanks. Each tank holds up to 300,000 barrels of aviation fuel, with the largest being 100 ft in diameter by 250 ft high. To give a better indication of the size of these fuel storage tanks, a 300,000-barrel tank holds enough gasoline to give a 12-gallon fill-up to 1,050,000 automobiles.

To improve the polyurethane coatings, NRL developed tank linings consisting of a fluorinated polyurethane filled with Teflon powder. The material is both hydrophobic and oleophobic and impermeable to water, gases, hydrocarbons (fuels), and other corrosive agents. Use of the lining began in 1983; by early 1986, the lining had been installed in tanks at Naval Air Station Pensacola, Florida (four tanks), Corpus Christi, Texas (two tanks), Norfolk, Virginia, and Patuxent River, Maryland, and at Naval Support Facilities at Yokosuka, Japan, Craney Island, Virginia (two tanks), Diego Garcia (two tanks), and Pearl City, Hawaii (five tanks).

In estimating the financial savings of the fluoropolyurethane topcoat, the Naval Facilities Engineering Command performed a life cycle cost analysis for a 60-year life for the tanks at Craney Island, Virginia. The command included costs for coating installation and necessary replacement, plus periodic cleaning of the tanks. In 1993 dollars, the epoxy coating cost \$60,863 per year, a conventional urethane coating cost \$40,698 per year, and the fluorinated urethane coating cost \$30,144 per year.¹⁴⁴ Based on 18 fuel tanks coated by 1998, the total life-cycle savings for using fluorinated urethane coatings in place of conventional urethane coatings were \$11.4 M, and more than \$33 M by replacing epoxy coatings.

IMPACT

NRL's fluorinated polymer coating is an effective lining for the fuel tanks at naval air stations and naval support facilities. It also saves a significant amount of money over the life of the tanks. The U.S. Army mandates this lining for the same purpose,¹⁴⁵ and the Defense Fuel Supply Center also specifies this coating in all new tanks. Finally, a clear coating of this polyurethane was adopted in 1987 as the standard coating for BRA-22 radomes on all Los Angeles-class submarines because the water shedding characteristics of the coating provide more rapid access to stable radar when broaching the sea surface.

PRIMARY REFERENCE DOCUMENTS

- U.S. Patent No. 4,157,358 to Griffith, J.R., "Fluorinated Network Polymers," June 5, 1979.
- Griffith, J.R. and Brady, Jr., R.F., "Ready for the Market: An Intriguing Class of Coatings," *Chemical Technology*, Vol. 19, 370 (1989).

¹⁴⁴ Naval Facilities Engineering Command Memorandum, ser OOCE/93-242, from J.J. Cecilio (Chief Engineer), 24 November 1993.

¹⁴⁵ U.S. Army Corps of Engineers Guide Specification, CEES-09873.

EXCIMER LASER TECHNOLOGY

ACHIEVEMENT

NRL researchers S. Searles and G. Hart discovered the first excimer laser in 1975. Excimer lasers operate in the ultraviolet (UV) and have short-duration pulses that allow the study of fast processes. UV lasers can be more tightly focused relative to lasers with longer wavelengths in the visible range of the spectrum, and excimer lasers are more efficient than other UV lasers.

The demonstration at NRL that an electrical discharge could be used to make an excimer laser with order-of-magnitude lower voltages led to commercial development. Once the commercial sector began development of the technology, excimer lasers became research tools for fundamental studies that increased rapidly in all fields, especially in biology and medicine. By 1998, over 10,000 articles had been published with “excimer laser” as a keyword. In the commercial sector, the technology was developed for photolithography in the semiconductor industry and for medical applications. Searles, Hart, and four others were presented the 1992 Rank Prize for Optoelectronics “for their discoveries leading to the development of the rare gas halide excimer lasers.” The award read:

“Today’s high power ultraviolet gas lasers find applications in science, industry, and medicine ranging from the production of integrated circuit chips by photolithographic techniques to a surgical procedure in which the cornea of the eye can be reshaped so as to correct for defects in vision.”

Follow-on research at NRL led to the development of krypton-fluoride (KrF) excimer-laser technology for inertial confinement fusion (ICF) applications. The Laboratory’s laser fusion program is the world leader in high-energy excimer-laser technology. Recently, NRL converted its Electra krypton-fluoride (KrF) laser system to argon-fluoride (ArF) operation, which has the potential to be a superior laser driver for ICF and inertial fusion energy due to its short wavelength, broad bandwidth, and high efficiency.

IMPACT

NRL’s discovery of the excimer laser provided the research community with a new tool, especially for fundamental studies in biology and medicine. In the commercial sector, the laser found applications in the production of integrated circuit chips and in corneal sculpting for vision correction. In the latter application alone, the market was estimated to be over a billion dollars by the late 1990s.

As for NRL’s laser fusion program, the Electra ArF laser recently set a new energy record of 200 J. ArF laser light provides a larger ablation pressure for imploding a laser fusion target than any other laser technology.¹⁴⁶

PRIMARY REFERENCE DOCUMENTS

- U.S. Patent No. 4,143,336 to Searles, S. and Hart, G., “Xenon Bromide (XeBr) Excimer Laser,” March 6, 1979.
- Searles, S.K. and Hart, G.A., “Stimulated Emission at 281.2 nm from XeBr,” *Applied Physics Letters*, Vol. 27, 243 (1975).
- Myers, M.C. *et al.*, “Development of an Electron-Beam Pumped, Argon Fluoride Laser for Inertial Confinement Fusion,” *2019 IEEE Pulsed Power & Plasma Science (PPPS)*, 2019, 1-4.

¹⁴⁶ Navy News Release, “NRL-Built Argon Fluoride Laser Marks Breakthrough, Sets New Energy Record” (22 September 2020).

SPECIFIC EMITTER IDENTIFICATION

ACHIEVEMENT

Specific Emitter Identification (SEI) provides electronics intelligence (ELINT) signal collection platforms with the capability to uniquely identify a radar transmitter with such accuracy as to make it possible to assign a “fingerprint” to that particular signal. In using SEI techniques, systems with a radar transmitter can be cataloged and tracked, and the data interchangeability between SEI systems allows a signal to be collected by one system and then “handed off” to another system for tracking. For example, SEI can be used to covertly track a contraband transport whose signal of interest can be collected by an aircraft and then transmitted electronically to a ship for subsequent tracking.

On April 14, 1982, NRL’s R. Goodwin was the recipient of the Navy Superior Civilian Service Award. He was cited for “performing and directing the research and development efforts that led to the achievement of an important, new Navy capability in real-time pulsed-emitter characterization.”

In June 1993, the National Security Agency (NSA) recognized the superior capability of NRL’s SEI concept and equipment after a competition among numerous participants from industry and other service laboratories.¹⁴⁷ The NSA test served as an impartial means for selecting an SEI methodology for use as a national standard. As a result of the test, NSA issued a message (DTG 011440Z, June 1995) that stated in part, “Accordingly, NSA has selected the Naval Research Laboratory processor (L-MISPE) to be the standard for conducting SEI/UMOP collection operations ...”

Since that decision, SEI platforms have been very successful at cataloging and tracking platforms of interest. In one application, a library of over 300,000 specific radar signals was compiled. This library was shared among sites to aid in performing tactical intelligence and surveillance tasks. The platforms for making SEI observations have since proliferated.

IMPACT

SEI identifies radars by their unique characteristics with such accuracy as to “fingerprint” it. In fact, it can distinguish between identical models produced off the same assembly line. With SEI systems deployed on ships, aircraft, submarines, and ground sites, NRL’s technology has had significant warfighting impact. It saw combat action in Kosovo and in Operation Iraqi Freedom. Furthermore, Coast Guard vessels, Navy warships, and aircraft have used it to support drug interdiction, to enforce treaties, and to monitor the movement of materials used in weapons of mass destruction.

PRIMARY REFERENCE DOCUMENTS

- Goodwin, R.L., “System for Classifying Pulsed Radio-Frequency Modulation,” NRL Classified Patent Disclosure No. 772,602, February 10, 1977.¹⁴⁸
- Goodwin, R.L., “Electronic Warfare Unintentional-Modulation Processors: System Definition Considerations,” NRL Report 9040, June 1988.

¹⁴⁷ Christiansen, R.M., et al., “Assessment of L-MISPE Performance in Musketeer Dixie II,” NRL Memorandum Report 7404-93, 14 February 1994.

¹⁴⁸ This is Goodwin’s original patent disclosure for emitter feature extraction and use for SEI. Since the abstract was classified, no patent was pursued.

INVERSE SYNTHETIC APERTURE RADAR

ACHIEVEMENT

Inverse synthetic aperture radar (ISAR) is a coherent imaging technique for classifying ships at sea. NRL's D.W. Kerr originated the concept for using the ship's irregular motions to provide the angle-aspect change necessary for imaging.

ISAR processes the radar echoes in fine range-resolution cells, resolving the incremental Doppler frequency shift between scatterers caused by the ship's motion (roll, pitch, and yaw) during an observation interval. The Navy uses this as a mode with a scanning surveillance radar. In the scanning mode, the radar produces a plan-position indicator (PPI) map of the ocean in which detected ships appear as bright "blips." When a radar operator designates a "blip" with a cursor, the radar antenna spotlights the ship position, and a continuous sequence of ISAR ship images appear on the screen.

The AN/APS-116 radar, which was based on earlier NRL developments, was replaced by the AN/APS-137, which has the added capability of performing recognition of ships based on NRL's ISAR technique. The APS-137 was installed in P-3 as well as the S-3 aircraft before the S-3 Viking was retired from Navy service in 2016.

As an ocean surveillance tool, the Navy uses ISAR for providing ship classification and the targeting for long-standoff-range missiles. The APS-147, which also incorporates ISAR in its operations, is now installed in the SH-60R (LAMPS) helicopters.

IMPACT

ISAR provides the Navy with the important capability to identify targets at considerable ranges. It is included in major operational systems on the Navy's P-8 aircraft, the Navy's MH-60R helicopter, the Coast Guard's C-130 aircraft, and on the Navy's Triton long-duration UAV.

PRIMARY REFERENCE DOCUMENTS

- Hermann, G., Kerr, D., and Tamny, M., "Interactive SAR Interpretation Facility," *IEEE Transactions on Aerospace and Electronic Systems* 11 (3) 427- 427 (1975).
- Musman, S., Kerr, D.W., and Bachmann, C., "Automatic Recognition of ISAR Ship Images," *IEEE Transactions on Aerospace and Electronic Systems*, Vol. 321, No. 4, 1392-1403 (1996).
- Lipps, R., NRL, Washington, DC, Snider, G.A., Surveillance and Avionics Technology Office, Naval Air Systems Command, Patuxent River, MD, (U), The Past, Present, and Future of the AN/APS-137. 8-9 December, 1998.

KEY DISTRIBUTION AND MANAGEMENT FOR CRYPTOGRAPHIC EQUIPMENT

ACHIEVEMENT

NRL's Navy Key Distribution System (NKDS) substantially improved the security of cryptographic key material distributed throughout the Navy to communications security (COMSEC) accounts. Traditionally, key material was generated and distributed as unencrypted text on paper tape. This left the key vulnerable to compromise and made rapid key distribution impossible.

NRL initiated development of NKDS in response to the Walker espionage ring, whose theft of Navy cryptographic material led to the compromise of many encrypted naval messages between 1967 and 1985. The concept, architecture, and requirements developed by NRL for NKDS changed the paradigm of key material generation, distribution, and management. The NRL requirements called for the replacement of the unencrypted paper key scheme by an electronic system in which keys are encrypted from generation until employment so that their confidentiality and integrity are ensured. NKDS afforded electronic exchange of key material, thereby facilitating rapid execution of battlegroup communication plans, improved operational flexibility, and interoperability with civilian agencies, embassies, and allied coalition nations. This approach further provided the security needed to protect key material from compromise, and thus protect lives and the mission of the fleet.

IMPACT

The NRL-developed architecture and requirements became the cornerstone of DoD key material generation, distribution, and management systems at the time. NKDS became operational in 1994 under the Common Tier 1 program established by the assistant secretary of defense for C3I. The ideas and concepts of NKDS later became part of the Electronic Key Management System (EKMS) program, providing the basis for a secure, efficient, and responsive COMSEC Material Control System.

Under EKMS, each military service operated its own key management system using common software, based on NKDS, which supported physical and electronic key distribution, traditional electronic key generation, management of material distribution, ordering, and other related accounting and central office functions. EKMS continued to serve as the DoD COMSEC Material Control System until 2013, when it was replaced by the Key Management Infrastructure program.

PRIMARY REFERENCE DOCUMENTS

- McChesney, T. and Ehrenwald, A., "Navy Key Distribution System: Operational Concept," NRL Report 5691, December 1985.
- Chincheck, S., "System Specification for the Navy Key Distribution System (NKDS)," Type-A System Specification, November 1988.
- Chincheck, S., "Computer Security Analysis of the Navy Key Distribution System," NRL Report 9297, April 1991.
- Chincheck, S., "Detailed Operational Concept for the Navy Key Distribution System," NRL Report 9803, July 1991.

INFRARED THREAT WARNING

ACHIEVEMENT

A passive anti-aircraft missile warning system based on detection of the infrared (IR) radiation from missile plumes was demonstrated by NRL in the 1990s. This device detected heat-seeking missiles fired at aircraft at greater ranges and with lower false alarm rates than earlier systems based on the ultraviolet signature of the missile launch. The longer-range detection provides earlier warning and hence more time for more effective deployment of countermeasures. Development evolved from initial concept analyses and proceeded through sensor development, measurements to verify the concept, and multiple live-fire demonstrations to reach a system suitable for engineering development. OPNAV approved engineering development of the system for initial evaluation on the F/A-18E/F. The Army adopted the NRL missile warning approach as the preplanned product improvement for their Common Missile Warning System. The Director for Electronic Warfare, OSD, identified NRL's demonstrated approach as the eventual tri-service missile warning system.

More recently, in response to a joint urgent operational need, NRL developed, assembled, and demonstrated a highly effective and lightweight infrared countermeasure system that has the capability to protect allied aircraft against infrared guided missiles. Previous systems were too large, heavy, expensive, and ultimately unreliable for many airborne platforms. NRL's Distributed Aperture Infrared Countermeasures (DAIRCM) system delivers a high-performance missile warning and laser-jamming capability within those constraints to protect aircraft against current and future threats. Equally important, the system is very affordable, costing half of other existing IR countermeasures systems. The House Armed Services Committee has reported that "Navy, Marine Corps, and Air Force all view DAIRCM as part of their long-term strategy for sustainable, cyber-secure aviation survivability against future battlefield threats."¹⁴⁹

IMPACT

Historically, the biggest threat to military aviation has been "heat-seeking" missiles, and the biggest challenge for airborne countermeasure systems has been achieving adequate performance within the size, weight, power, and cost constraints of an airborne platform. DAIRCM was chosen as a solution to support a Joint Urgent Operational Need (JUON) SO-0010 signed by OSD in 2016. The system is now fielded on five different type model series helicopters for the Navy, the USMC, the Army and the Air Force.

PRIMARY REFERENCE DOCUMENTS

- "Helicopter Infrared Self-Protection Study," submitted on 21 August 1981, Takken, E.H., and Schnitzler, A., — Memo 65-147:TGG:mm in response to Memos 1001-342:AB:ncs dtd July 24, 1981 and 1001-326:AB:ncs dtd July 10, 1981.
- Katz, G., Pauli, M., Sarkady, K.A., Kruer, M.R., Havlicek, J., Michaels, W.P., York, R.A., and Wilder, E., "Recent Measurements and Processed Imagery from a Dual-Band 128 x 128 Mid-Wave Infrared Staring Data Measurement Sensor (Fly's Eye)," *Passive Sensors IRIS*, March 1989.
- Sarkady, K.A., Lynn, J.G., Romero, H.A., Mabe, R., Bistransin, M., Strothers, K.A., Nichols, B., Sagusti, R. "Distributed Aperture IRCM (DAIRCM)", *MSS Specialty Group on Infrared Countermeasures*, April 2009
- JUON/UON # SO-0010, signed by OSD in 2016.

¹⁴⁹ House Armed Services Committee, *NDAA for Fiscal Year 2023: Draft Report on H.R. 7900*, July 2022.

OPTICAL FIBER GYROSCOPE

ACHIEVEMENT

NRL was the first to demonstrate long-term inertial-quality performance in a fiber-optic gyroscope. This achievement was a pivotal milestone in the device's development into a practical, precision, inertial-quality navigation instrument that stimulated intense industrial development of the device.

The fiber-optic gyroscope provides rotation sensing for inertial navigation and other positioning and directional applications, such as attitude, heading, and reference in airplanes. The device is used for air and sea navigation and satellite attitude control. Since it provides longer lifetime rotation sensors, it also leads to lower operational cost.

Before 1983, the fiber-optic gyroscope was essentially a laboratory curiosity, with little industrial activity due to limited sensitivity and large bias drifts. The sensitivity problem was solved in Germany by R. Ulrich with the introduction of the broadband source. The bias drift problem was solved at NRL by W.K. Burns and his colleagues, who built one of the first fused-fiber couplers with polarization-maintaining fiber, and used this coupler to build a fiber gyroscope with polarization-maintaining fiber. This fiber and coupler greatly reduced the polarization noise that was responsible for long-term bias drift, and performance of 0.035 deg/hr over 24 hours was demonstrated. This result led to the initiation of widespread industrial interest and development efforts, as it demonstrated that the fiber-optic gyroscope was capable of practical inertial navigation. Numerous companies market fiber gyroscopes today that directly incorporate NRL's work.

In 1995, the Institute of Navigation awarded NRL's W. K. Burns the prestigious Thurlow Award for his contributions to the development of the fiber-optic gyroscope.

IMPACT

NRL was the first to demonstrate long-term inertial-quality performance in a fiber-optic gyroscope. The technology replaced spinning-mass gyroscopes with fiber-optical devices that had no moving parts. This was a revolution in rotation-sensing technology and will have a permanent impact due to higher reliability and longer lifetime, as well as weight, size, and cost reduction. The fiber gyroscope has had significant impact on both military and civilian applications ranging from use on U.S. military platforms to automobiles. The optical-fiber gyroscope is in production in the U.S. as well as in Europe and Japan.

PRIMARY REFERENCE DOCUMENTS

- Villarruel, C.A., Abebe, M., and Burns, W.K., "Polarization Preserving Single Mode Fiber Coupler," *Electronic Letters*, Vol. 19, 17 (1983).
- Burns, W.K., Moeller, R.P., Villarruel, C.A., and Abebe, M., "Fiber Optic Gyroscope with Polarization Holding Fiber," *Optics Letters*, Vol. 8, 540 (1983).
- U.S. Patent No. 4,612,028 to Abebe, M., Burns, W.K., and Villarruel, C.A., "Polarization Preserving Single Mode Fiber Coupler," 1986.
- Burns, W.K., "Polarization Control with PM Fiber," Chapter 6 in *Optical Fiber Rotation Sensing*, Burns, W.K., ed. (Academic Press, 1994).

PERMANENT MAGNET MATERIALS

ACHIEVEMENT

Rare earth-iron-boride magnets have had a tremendous impact in the concept and design of devices that use a magnetic field to generate power and to produce motion. Their function as permanent magnets, those that are able to maintain their magnetic orientation at high fields, allows the compact and efficient operation of motors at both small and large scales. Their discovery and use have had the biggest impact in the development of motor technology and the electrification of transportation that directly addresses problems of global climate change and takes advantage of the intrinsic efficiencies of electromotive propulsion over fuel-powered engines.

In 1980, NRL's N.C. Koon and B.N. Das were the first to fabricate and examine the magnetic properties of rare earth-iron-boron ($R_2\text{-Fe}_{14}\text{B}$) alloys and demonstrated their promise for permanent magnet use. This groundbreaking work resulted in fundamental patents that were licensed to several firms and delivered in commercial products now used in electromotive technology worldwide.

In 1986, N.C. Koon and his colleagues were awarded the American Physical Society's International Prize for New Materials for "*pioneering research on the preparation and characterization of rare earth-iron-boron materials which led to the discovery of a new class of permanent magnets of unusual scientific interest and technological promise.*"

IMPACT

Rare earth-iron-boride magnets are ubiquitous today in electromotive technology. Since 1983, commercial alloys based on R-Fe-B have been in production at industrial scale, and by 1985, these materials provided almost twice the magnetic energy density of the best materials previously available. It is this property, along with mechanical strength, that has allowed realization of electric motors that compete economically with gas- and diesel-powered engines in performance and with the added benefit of reduced carbon emission — a goal with global impact to fend off global warming.

PRIMARY REFERENCE DOCUMENTS

- Koon, N.C. and Das, B.N., "Magnetic Properties of Amorphous and Crystallized ($\text{Fe}_{0.82}\text{B}_{0.18}$) $_{0.9}\text{Tb}_{0.05}\text{La}_{0.05}$," *Applied Physics Letters*, Vol. 39, No. 10 (1981).
- Koon, N.C. and Das, B.N., "Crystallization of FeB Alloys with Rare Earths to Produce Hard Magnetic Materials," *Journal of Applied Physics*, Vol. 55, 2063 (1984).
- Williams, C.M., Koon, N.C., and Das, B.N., in *High Performance Permanent Magnet Materials*, Materials Research Society Symposium Proceedings, Vol. 96, 111 (1987).
- U. S. Patent No. 4,402,770 to Koon, N.C., "Hard Magnetic Alloys of a Transition Metal and Lanthanide," September 6, 1983.
- U. S. Patent No. 4,533,408 to Koon, N.C., "Preparation of Hard Magnetic Alloys of a Transition Metal and Lanthanide," August 6, 1985.

NOGAPS/NAVGEN GLOBAL WEATHER PREDICTION

ACHIEVEMENT

The Navy Operational Global Atmospheric Prediction System (NOGAPS) and its replacement, the Navy Global Environmental Model (NAVGEN), represent more than 40 years of R&D by NRL. Work on the first of several NOGAPS generations began in 1976. NOGAPS went operational in 1982, and an improved model went operational in 1988. NOGAPS became the DoD's unified global weather analysis/forecast system, used for operational weather prediction around the world. Much of the atmospheric and oceanographic support for military operations had its roots in NOGAPS, whether it was the prediction of cloud cover over the strike target, estimation of environmental effects on weapons systems, the prediction of tropical cyclone formation and movement, or high-seas warnings.

In the early 2000s, NOGAPS transitioned from purpose-built supercomputers to high-performance systems assembled with commodity components. In 2013, NAVGEN went operational, replacing its predecessor. In 2020, NAVGEN transitioned a new, scalable architecture to operations that enabled benefits in terms of price and performance that translated into improved forecasts for the DoD.

NAVGEN provides the world's first prototype of a global numerical weather prediction system extending from the ground to the edge of space. NAVGEN has become the central engine of the Navy's operational weather-prediction system. It feeds data into oceanographic systems such as polar ice forecasts, ocean spectral wave models, the thermodynamic ocean-prediction system, and the prediction of ocean currents. Wind, temperature, and moisture forecasts provide lateral boundary conditions for regional prediction models and tropical cyclone predictions.

IMPACT

NAVGEN supports a wide variety of fleet operations. For example, weather forecasts aid ship and aircraft routing, dust and fog visibility forecasts ensure safety, and predictions of ocean temperature and salinity optimize the efficacy of weapons and sensing platforms. NAVGEN's predictions of the "near space" (~10–100 km) environment support emerging Navy assets such as high-altitude, long-endurance airframes, boost-phase missile defense technologies, airborne laser weapon systems, high-altitude injection, and prediction models concerning transport of chemical, biological, nuclear, and radiological material.

In 2012, NRL scientists were recognized with the Department of the Navy's Acquisition Excellence Award in Technology Transition. NAVGEN products are used by all branches of the U.S. armed services, the National Oceanic and Atmospheric Administration, and the Department of Energy.

PRIMARY REFERENCE DOCUMENTS

- Hogan, T. F. and Rosmond, T.E., "Description of the Navy Operational Global Atmospheric Prediction System's Spectral Forecast Model," *Monthly Weather Review*, 119(8), 1991.
- Rosmond, T.E. and Xu, L., "Development of NAVDAS-AR: Non-linear formulation and Outer Loop Tests," *Tellus, Series A: Dynamic Meteorology and Oceanography*, 58 (1) 45-58 (2006).
- Kuhl, D. D., Rosmond, T. E., Bishop, C. H., McLay, J., & Baker, N. L. (2013). Comparison of Hybrid Ensemble/4DVar and 4DVar within the NAVDAS-AR Data Assimilation Framework, *Monthly Weather Review*, 141(8), 2740-2758
- Hogan, T.F., M. Liu, J.A. Ridout, M.S. Peng, T.R. Whitcomb, B.C. Ruston, C.A. Reynolds, S.D. Eckermann, J.R. Moskaitis, N.L. Baker, J.P. McCormack, K.C. Viner, J.G. McLay, M.K. Flatau, L. Xu, C. Chen, and S.W. Chang. 2014. The Navy Global Environmental Model. *Oceanography* 27(3):116–125

GENERALIZED NEAR-FIELD ACOUSTICAL HOLOGRAPHY

ACHIEVEMENT

NRL developed and implemented a new measurement technique called generalized near-field acoustical holography (GENAH). In 1982, NRL's E.G. Williams began the pioneering work that revolutionized the field of experimental acoustics in noise characterization and control throughout the world. He has since received the Per Bruel Gold Medal for Noise Control and Acoustics (2009) and the American Acoustical Society's Trent-Crede Medal "for development and application of near-field acoustical holography" (2016).

GENAH is the only experimental technique that, from a single array measurement, can provide a complete global analysis of the vibration, radiation, and scattering of structures in air and under water. This provided the Navy with a powerful tool to understand the radiation and scattering of sound from submarines. The understanding of fluid-structure interaction and wave propagation gained through GENAH has been a cornerstone in the Navy's effort to study and remedy acoustic vulnerabilities in the U.S. submarine fleet. This work changed the way the Navy viewed the vibration, radiation, and scattering from submarines and has been a major force in changing the thinking of Navy and non-Navy researchers in their endeavors to quiet the U.S. submarine fleet.

Because of the remarkable scientific and engineering impact of this research, NRL has inspired nearfield acoustic holography efforts throughout the world. In underwater acoustics, the French, Italian, and Japanese navies applied GENAH to study the vibration and radiation of submarines. In architectural acoustics, the measurement technology for studying the transmission of sound through building structures has been revolutionized using GENAH principles in France, while in Japan, new techniques for the measurement of reflection coefficients have been developed. Other transitions of NRL's work have concentrated on noise control in the automotive and aerospace industries, including studies in tire noise and interior cabin noise at laboratories in the U.S., Korea, and Japan. It has also been used to deal with moving noise sources such as cars and trains in France, Korea, and Japan.¹⁵⁰

IMPACT

NRL's development of GENAH revolutionized the field of acoustic noise characterization and control throughout the world. The U.S. Navy is using NRL's work to reduce acoustic vulnerabilities in the submarine fleet and is applying it to surface ship acoustics. In industry, major acoustical measurement companies have marketed systems based on GENAH for use in a broad range of applications, including noise control in the automotive and aerospace industries. NASA is using GENAH to develop powerful handheld microphone arrays for real-time interior aircraft noise characterization. Research papers citing NRL's work have appeared in almost every major scientific country in the world.

PRIMARY REFERENCE DOCUMENTS

- U.S. Patent No. 4,415,996 to Maynard, J.D. and Williams, E.G., "Nonwavelength-limited Holographic Sound Field Reconstruction," November 15, 1983.
- Williams, E.G., "Method of Measuring Structural Intensity in Vibrating Plate Radiators," U.S. Statutory Invention Registration H1330, July 5, 1994.

¹⁵⁰ Bruel and Kjaer, "Vehicle Noise Investigation Using Spatial Transformation of Sound Fields," *Sound and Vibration*, April 1989.

FIXED-WING AIRBORNE GRAVIMETRY

ACHIEVEMENT

Measurement and analysis of the spatial variations in the gravity field of the Earth are useful from both geologic/geophysical and geodetic perspectives. Gravity data serve in the first case as a remote sensing probe of shallow and deep mass distributions beneath the surface of the ocean or the land, an important tool for economic geology and basic geophysical research. In the second area, geodesy/gravity data are used to establish the shape and figure of the Earth. Geodetic quantities are of critical operational importance to the Navy, primarily as corrections to high-accuracy inertial navigation systems in submarines and ballistic missiles. Over the years, enormous efforts and expenditures have been devoted to shipboard and terrestrial gravity surveys to meet Navy requirements.

Airborne gravimetry had long been a desirable goal because of the lower costs, rapid collection, and access to logistically difficult areas made possible by airborne surveying techniques. However, the extremely poor signal-to-noise characteristics of airborne gravity measurements defeated numerous attempts since the 1950s by government, academic, and industry researchers to provide airborne data of useful accuracy and resolution. It was found possible to acquire data at low speeds in helicopters; however, their range was too limited and their costs too high to make them preferable to traditional ship and land survey methods.

In 1979, NRL began a program in airborne gravimetry from long-range, fixed-wing aircraft capable of meeting Navy requirements. The program required development of extremely accurate three-dimensional aircraft positioning, specialized aircraft operational techniques, and improvements to gravimeter technology. This resulted in the world's first successful demonstration of accurate fixed-wing-based airborne gravity measurements. A field test of the prototype system in 1981 achieved accuracies of 2 to 3 parts per million on several profiles over an Atlantic gravity test range at aircraft speeds of 250 knots.

IMPACT

NRL's long-range airborne gravity measurement system has provided vital data for Navy and other DoD tactical and strategic systems that cannot be acquired in any other way.¹⁵¹ Airborne gravity data are collected worldwide to support operational requirements for submarines, ballistic missiles, and aircraft. In other uses, fixed-wing airborne gravimetry was deployed in Afghanistan for a successful airborne remote sensing and mapping project conducted by NRL and the U.S. Geological Survey called Rampant Lion. Building on that success, both agencies completed Rampant Lion II in 2008. Rampant Lion I focused on collecting data that might aid in economic development. Rampant Lion II had an additional goal to support the warfighter. This marked the first deployment of NRL scientists into a combat theater since World War II. The project's impact was significant. According to one U.S. Army officer, "Without the (Rampant Lion Mission) imagery, our missions would not have been successful ... on at least 5 occasions, the imagery was critical to getting us out of tight spots that could have been disastrous."

PRIMARY REFERENCE DOCUMENTS

- Brozena, J.M., "A Preliminary Analysis of the NRL Airborne Gravimetry System," *Geophysics*, Vol. 49, 1060-1079 (1984).
- Brozena, J.M., "Airborne Gravimetry," *CRC Handbook of Geophysical Exploration at Sea* (CRC Press, Boca Raton, 1992), Chapter 4.

¹⁵¹ Salman, R.D. (Geoscience Program Manager, NIMA) letter to H. Eppert (Superintendent, Marine Geosciences Division, NRL), Subj. "DoD Utility of Fixed Wing Airborne Gravimetry," 27 March 1998; and Forsberg, R. (President, International Association of Geodesy) letter to Brozena, J. (NRL), 30 March 1998.

ACOUSTIC MATCHED-FIELD PROCESSING

ACHIEVEMENT

Matched-field processing (MFP) is a beamforming technique used to localize acoustic sources in a waveguide or to infer waveguide parameters. The conceptual foundation of MFP appeared in a 1961 paper by A. Parvulescu of Hudson Laboratories. The MFP concept was first discussed in an analytic format in 1976 by H. Bucker of the Naval Undersea Center. NRL subsequently began a program to demonstrate MFP's practical viability. In 1981, NRL began research on the MFP concept in the shallow-water propagation environment. In 1983, NRL presented simulations of the MFP concept, now known as the conventional, or Bartlett, processor. This processor has become the baseline and most widely used matched-field processor. A pioneering experimental demonstration of MFP was reported by NRL in 1985. This work produced the widely used adaptive, or high-resolution, MFP processor. The conventional and adaptive MFP processors were used as the theoretical basis for MFP shallow-water research programs conducted at the SACLANT ASW Research Centre, Italy, and at the Naval Oceanographic R&D Activity (now a NRL division) located at the Stennis Space Center, Mississippi. The NRL shallow-water work was expanded to the deep-water environment with the initiation of the Office of Naval Technology's High Gain Initiative (HGI). NRL provided much of the theoretical basis and numerical simulation for the research conducted by the HGI from 1988 to 1993. The HGI results suggest that large volumetric acoustic array systems, which use MFP concepts, may be useful for long-range surveillance purposes in deep-water environments.

In a related area, the use of MFP to invert for antisubmarine warfare (ASW)-related environmental parameters received significant attention by the naval research community. These MFP inversion methods were pioneered at NRL and were incorporated into programs directed toward rapid extraction of environmental parameters needed to estimate ASW sonar performance. NRL research included the development of algorithms and the early experimental demonstrations of MFP inversions of ice and bottom properties. One of the first such inversions was for sea ice parameters in the Arctic. The use of global optimization techniques to invert for geoacoustic parameters (a common approach now) was pioneered at NRL.

IMPACT

NRL's early work in MFP provided much of the theoretical and experimental basis for the Navy's HGI and served as the basis for the design and performance evaluation of large-volumetric-arrays concepts. MFP techniques also led to applications for multiline towed arrays. In addition, MFP techniques pioneered at NRL for determining geoacoustic parameters in ocean sediments were introduced into the Navy's Oceanic and Atmospheric Master Library. Research into time-reversal techniques and focused acoustic fields had its roots in the early MFP work.

PRIMARY REFERENCE DOCUMENTS

- Parvulescu, A., "Signal Detection in a Multipath Medium by M.E.S.S. Processing," *Journal of the Acoustical Society of America*, Vol. 33, 1674 (1961).
- Bucker, H.P., "Use of Calculated Sound Fields and Matched-Field Detection to Locate Sound Sources in Shallow Water," *Journal of the Acoustical Society of America*, Vol. 59, 368-373 (1976).
- Baggeroer, A.B., Kuperman, W.A., and Mikhalevsky, P.N., "An Overview of Matched-Field Methods in Ocean Acoustics," *IEEE Journal of Oceanic Engineering*, Vol. 18, 4 (1993).
- Tolstoy, A., *Matched Field Processing for Underwater Acoustics* (World Scientific, 1993).

MAGNETIC MATERIALS AND SEMICONDUCTOR TECHNOLOGY

ACHIEVEMENT

NRL's G.A. Prinz recognized that the developments in semiconductor materials technology in the 1970s, which permitted atomic control of crystal film growth in ultrahigh vacuum, could be exploited to fabricate new magnetic materials in thin-film form. Furthermore, he saw that the close lattice match between compound semiconductors and the body-centered cubic (bcc) phases of iron (Fe), cobalt (Co), and nickel (Ni) would open the door to integrating these two fields of materials into common monolithic structures. He initiated molecular beam epitaxial (MBE) growth of magnetic materials on semiconductors in 1979 and demonstrated the first MBE epitaxial growth of iron on gallium arsenide in 1981.

NRL's J.J. Krebs carried out the characterization of these new materials. Using the powerful techniques of angularly dependent ferromagnetic resonance, along with magnetic susceptibility and X-ray fluorescence, he generated a detailed description of these new materials, including the interface and surface properties that dominated their behavior. Further work in this field confirmed the general properties of epitaxial ferromagnetic metal films established by the Laboratory's work.

NRL's work was a key technology development that enabled the demonstration of the giant magnetoresistance (GMR) effect by laboratories in France and Germany using Fe/Cr multilayers epitaxially grown on GaAs. The 2007 Nobel Prize in Physics was awarded to Albert Fert and Peter Grünberg for the discovery of GMR.

The use of magnetic metal films on semiconductors for sensors is now widespread. The largest use is in read heads for computer hard disks. They are under development for mechanical motion sensors by the automotive and machine tool industry, as well as by the military for fuses and perimeter defense. The largest impact will probably be for nonvolatile magnetic memory in computers, which is under development at several corporations within the U.S. as well as abroad in Japan, Germany, France, and the Netherlands.

IMPACT

NRL's pioneering work was a key technology development that enabled the demonstration by researchers located in France and Germany of the giant magnetoresistance effect using Fe/Cr multilayers epitaxially grown on GaAs. The work of those researchers earned them the 2007 Nobel Prize in Physics.

In the commercial arena, magnetic metal films on semiconductors, exploited for the giant magnetoresistance effect, by 1998 was generating \$10 billion in sales for sensors in read heads, and the introduction of magnetic computer memory was projected to impact a market measured at \$100 billion annually. For military applications, this technology promised far better performance of satellites, missile guidance, and aircraft navigation.

PRIMARY REFERENCE DOCUMENTS

- Prinz, G.A. and Krebs, J.J., "Molecular Beam Epitaxial Growth of Single-Crystal Fe Films on GaAs," *Applied Physics Letters*, Vol. 39, No. 5, 397-399 (1981).
- Prinz, G.A., Rado, G.T., and Krebs, J.J., "Magnetic Properties of Single-Crystal (110) Fe Films Grown on GaAs by Molecular Beam Epitaxy," *Journal of Applied Physics*, Vol. 53, 2087 (1982).

MARITIME DOMAIN AWARENESS

ACHIEVEMENT

NRL developed a spaceborne computer in the 1990s that, at the time, was 100 times more capable than anything else flying. By doing so, the On-Board Processor (OBP) program achieved an unparalleled advancement in engineering in support of military operations for multiservice and multinational tactical and strategic users. NRL's program included total concept development, system engineering, hardware development, algorithm development, fabrication, test, and deployment. From 1996 through 2002, it was the largest supplier of tactical data to the military.

NRL's subsequent efforts in the area of multi-intelligence data automated ship tracking has revolutionized the way the intelligence community (IC) and the Department of Defense (DoD) monitor maritime vessels throughout the world. This web-based enterprise effort began in 2004 as a proof-of-concept activity called the Vessel Tracking Program. It demonstrated that automated ship tracking was feasible and led to a demonstration program that advanced the capability of global maritime domain awareness (MDA).

NRL's later development of web-based Sea-Link Advanced Analysis (S2A) advanced MDA from tracking hundreds of objects daily using humans in loop to correlate data over time into tracks to automatically producing hundreds of thousands of tracks daily, allowing users in the Navy, the DoD, and the IC to spend more time assessing vessel intent and threat. The history of tracks produced by S2A provided the ability to determine patterns of life and prediction tools for vessels. S2A is a force multiplier for MDA within U.S. and coalition partner operations.

A related effort was the development of Pirate Attack Risk Surface (PARS), a guidance tool created due to an increase in pirate activity within the Somali Basin Region and the Gulf of Aden that threatened maritime security and stability in these regions. PARS integrates environmental conditions, pirate concept of operations, commercial shipping information, and all relevant piracy intelligence to produce a probability forecast of shipping vulnerability to pirate attack as a function of latitude, longitude, and time. The tool enabled operators to focus on regions where their efforts were likely to be the most productive.

IMPACT

In the 1990s, the OBP made a two-orders-of-magnitude improvement in low-power, high-performance, fully programmable spaceborne computing. From 1996 through 2002, it was the largest supplier of tactical data to the military. The OBP provided, for the first time, real-time situational awareness information not available with either organic assets or other systems to military units located throughout the world.

NRL's subsequent efforts revolutionized the way maritime vessels are monitored throughout the world. MDA advanced from tracking hundreds of objects daily using humans in loop, to automatically producing hundreds of thousands of tracks daily allowing users in the Navy, the DoD, and the IC to spend more time assessing vessel intent and threat.

PRIMARY REFERENCE DOCUMENTS

- *Users Guide for TRAP & TADIXS-B Broadcasts*, NRO Operational Support Office, June 1997.
- Hansen, J.A., Hodyss, D., Bishop, C.H., and Campbell, W., (2014). "Method for Predicting Pirate Attack Risk in a Geographical Area Based on INTEL Regarding Pirates and Pirate Behavior Coupled with METOC Conditions", US Patent 8,838,515 B2.

DEEP SPACE PROGRAM SCIENCE EXPERIMENT (*CLEMENTINE*)

ACHIEVEMENT

The Deep Space Program Science Experiment (*Clementine*) was a highly successful lunar mapping mission. During the 1980s, the Ballistic Missile Defense Organization developed advanced sensor and component technologies for missile defense systems. In 1991, a joint NASA/DoD study concluded that a collaborative deep-space mission could test these developments and provide a significant science return. The DoD's goals were to test lightweight miniature sensors and components by exposing them to a long-duration space environment while obtaining imagery of the Moon and the near-Earth asteroid Geographos. NRL was tasked with responsibility for mission design, spacecraft engineering, spacecraft manufacturing and testing, launch vehicle integration, terrestrial support, and flight operations.

In 1994, NRL put a satellite equipped with a sensor payload into orbit around the Moon. The spacecraft successfully used much newly developed hardware, including imaging sensors provided by Lawrence Livermore National Laboratory. A high-quality mapping mission of the lunar surface was completed with outstanding success — a complete imaging of the lunar surface (1.8 million images) in 11 discrete wavebands with coarse altimetry over most of the surface. After completing the lunar mission, *Clementine* suffered an onboard malfunction that prevented it from performing the flyby of Geographos.

This imaging of the Moon's surface was a great success in its scientific returns: relative positions of widely separated lunar features could be accurately determined for the first time, including those on the Moon's far side, some regions in the lunar south pole were imaged with good resolution for the first time, with some data indicating the presence of ice, and complete multispectral imaging provided information on local mineral composition over the entire lunar surface. Finally, these images helped resolve issues such as the character and evolution of the primitive lunar crust, the thermal evolution of the Moon and lunar volcanism, and the impact record and redistribution of crustal and mantle materials. *Clementine's* images were made available for students everywhere to explore in a 3D interactive environment on the Internet.¹⁵²

IMPACT

With *Clementine's* success, the U.S. returned to the Moon for the first time since the end of the Apollo lunar missions. NRL's satellite demonstrated that the goal of "faster, better, cheaper" was attainable: it was built in only 22 months (less than half the usual time) for 1/5 the usual cost for similar space probes.¹⁵³ The probe was so simple to operate that its mission control center comprised eight engineers working in a warehouse in Alexandria, Virginia.¹⁵⁴ As for the presence of ice on the Moon, NASA's Lunar Prospector mission in 1998 found evidence of ice at both lunar poles.¹⁵⁵

PRIMARY REFERENCE DOCUMENTS

- Nozette, S., Rustan, P., Plesance, L.P., Horan, D.M., Regeon, P., et al., "The *Clementine* Mission to the Moon: Scientific Overview," *Science*, Vol. 266, 1835-1839 (1994).
- "*Clementine* Mines Its First Nuggets on the Moon," *Science*, Vol. 264, June 17, 1994.

¹⁵² NASA News Release 05.56AR, 26 October 2005.

¹⁵³ Excerpt from certificate accompanying the 1995 Stellar Award to the *Clementine* Development Team.

¹⁵⁴ Excerpt from the *Discover* Magazine Award for Technological Innovation (1995).

¹⁵⁵ NASA Press Release, "Lunar Prospector Finds Evidence of Ice at Moon's Poles," (# 98-38), 5 March 1998.

DECADAL IMPACT OF EL NIÑO

ACHIEVEMENT

El Niño events in the Pacific Ocean can have significant local effects lasting up to two years. For example, the 1982–1983 El Niño caused increases in the sea-surface height and temperature off the coasts of Ecuador and Peru, with important consequences for fish populations and local rainfall. But until NRL’s work in this area, the scientific community believed that the long-range effects of El Niño events were restricted to changes transmitted through the atmosphere, for example, causing precipitation anomalies over the Sahel.

Under the leadership of G. Jacobs, NRL provided evidence from modeling and observations that planetary-scale oceanic waves, generated by reflection of equatorial shallow-water waves from the American coasts during the 1982–1983 El Niño, crossed the North Pacific and a decade later caused a northward rerouting of the Kuroshio Extension (a strong current that normally advects large amounts of heat from the southern coast of Japan eastward into the midlatitude Pacific). This led to significant increases in sea-surface temperature at high latitudes in the northwestern Pacific of the same amplitude and with the same spatial extent as those seen in the tropics during important El Niño events.

These changes may have influenced weather patterns over the North American continent during the decade following the 1982–1983 El Niño, which may demonstrate that the oceanic effects of El Niño events can be extremely long-lived. It is interesting to note that the most dramatic meteorological event over North America during 1993 was the record-breaking summer rainfall and flooding of the Mississippi river basin. Was this flooding, the worst of the century in the central United States, a delayed effect of the strongest El Niño of the century?¹⁵⁶

IMPACT

NRL’s research showed for the first time that the oceanic effects of El Niño events can be extremely long-lived. The scientific importance of this discovery was noted in an opinion piece by M.J. McPhaden in the same issue of *Nature* as the original Jacobs et al. (1994) article.¹⁵⁷ It was similarly recognized by *Discover* magazine as one of the top 75 science stories in 1994.¹⁵⁸

PRIMARY REFERENCE DOCUMENTS

- Jacobs, G.A., Hurlburt, H.E., Kindle, J.C., Metzger, E.J., Mitchell, J.L., Teague, W.J., and Wallcraft, A.J., “Decade-Scale Trans-Pacific Propagation and Warming Effects of an El Niño Anomaly,” *Nature*, Vol. 370, 360-363 (1994).

¹⁵⁶ McPhaden, M.J., “The Eleven-Year El Niño?,” *Nature*, Vol. 370, 326-327 (1994).

¹⁵⁷ *Ibid.*

¹⁵⁸ Zimmer, C., “El Grande,” *Discover*, Vol. 16, 68 (1995).

OPTICAL IMMUNOASSAYS AND SENSORS

ACHIEVEMENT

Beginning in the 1990s, NRL worked to develop portable biosensors intended to be easy to use and requiring only that the sample be a relatively nonviscous liquid. Ideally, these biosensors would be sensitive and simple to use and would require minimal sample processing. The biosensors developed by NRL enabled applications from environmental monitoring of contaminants to food safety and clinical detection approaches. The developed systems used antibodies and other biomolecules to recognize biological threat agents and environmental hazards/contaminants rapidly and at extremely low concentrations.

NRL's Fiber Optic Biosensor (FOB) and the similar Continuous Flow Sensor were used for monitoring of explosives in groundwater and soil. The FOB and the Array-Based Biosensor were used to measure biological toxins in river water and clinical samples (blood, serum, plasma) and harmless bacteria released in field exercises and collected from the air. The Continuous Flow Sensor was utilized in the detection of drugs of abuse in urine and saliva. The Array-Based Biosensor was applied extensively to evaluation of contaminants in food and food-related products as well as the detection of biothreat agents.

The Continuous Flow Sensor informed manufacture of the Research International (RI) FAST 2000, applied by the Environmental Protection Agency in monitoring Superfund cleanup sites, and the Lifepoint, Inc. IMPACT Test System, applied to on-site lab-quality drug and alcohol testing. The RI Analyte 2000 provided capabilities for detection of both explosives-related contamination and biothreat agents. RI also developed and marketed the RAPTOR fiber-optic biosensor based on NRL's technology, a device that was embedded with the U.S. Marine Corps. The Array-Based Biosensor informed development of a system by Hanson Technologies for food safety, by Constellation Technology Corp. for biothreat detection in post offices, and by Precision Photonics for a clinical application. These systems have been tested extensively in field trials and demonstrated results that were comparable to sophisticated laboratory analytical techniques.

IMPACT

NRL's portable biosensors provide automated, sensitive detection of biological threats, drugs, and explosives in scenarios that include clinical applications, environmental monitoring, and food safety.

PRIMARY REFERENCE DOCUMENTS

- U.S. Patent No. 5,061,857 to Thompson, R. and Villarruel, C., "Waveguide-Binding Sensor for Use with Assays," October 19, 1991.
- U.S. Patent No. 5,077,210 to Ligler, F.S., *et al.*, "Immobilization of Active Agents on Substrates with a Silane and Heterobifunctional Crosslinker," December 31, 1991.
- U.S. Patent No. 5,183,740 to Ligler, F.S., *et al.* Gaber, B.P., Kusterbeck, A.W., and Wemhoff, G.A., "Flow Immunosensor Method and Apparatus," February 2, 1993.
- U.S. Patent No. 5,430,813 to Anderson, G.P. and Golden, J.P., "Mode-Matched Combination Taper Fiber-Optic Probe," July 4, 1995.
- U.S. Patent No. 6,192,168 to Feldstein, M.J., Golden, J.P., Ligler, F.S., Rowe, C.A., "Reflectively coated optical waveguide and fluidics cell integration" February 20, 2001.
- U.S. Patent No. 6,245,296 to Ligler, F.S., Gaber, B.P., Kusterbeck, A.W., Wemhoff, G.A., "Flow Immunosensor Apparatus" June 12, 2001.

INTERFEROMETRY AT OPTICAL WAVELENGTHS

ACHIEVEMENT

NRL developed techniques to coherently combine light detected simultaneously over a broad bandpass with several independent telescopes. This overcomes the limitations imposed by atmospheric turbulence and physics on the angular resolution achieved with a single telescope or aperture. Turbulence in the Earth's atmosphere had limited the resolution of imaging systems to that achieved by an aperture 4 inches in diameter, or a spatial resolution of 1 arc second (10^{-5} radians). To achieve higher resolution, a larger number of spatial frequencies must be coherently sampled before temporal effects cause a change in the image. This was accomplished by using low-noise photodetectors, laser metrology, precision delay lines, and high-speed computing to detect and compensate for wavefront distortions caused by the atmosphere on timescales of a millisecond.

The development of these techniques started with a two-element interferometer at Mount Wilson (1984–1990) and was then expanded into the Navy Precision Optical Interferometer (NPOI). Construction of the NPOI happened from 1989 to 1998, resulting in a system capable of combining light from up to six telescopes separated by up to 435 m, allowing for the development of wide-bandwidth synthesis at optical wavelengths. The NPOI is capable of imaging at spatial resolutions as high as 10^{-9} radians and has achieved images at 10^{-8} radians resolution, easily exceeding that obtained with a single aperture. This work revolutionized the field of optical interferometry, demonstrating several observational and postprocessing techniques that became standard in the field and allow for routine high-angular-resolution imaging of targets.

IMPACT

NRL's development of wide-bandwidth imaging at optical wavelengths is equivalent to the invention of the telescope, with techniques that will be employed in future astronomical and remote sensing systems. Based on these techniques, the NPOI has been able to fulfill the Navy's positioning, navigation and timing needs and determine high-precision fundamental stellar parameters, such as mass, luminosity, and age, which are essential for refining stellar atmosphere and evolution models and for determining properties of planets around other stars.

The NPOI has also played a key role on space surveillance and intelligence-gathering systems with the first detection of optical interferometric fringes from a glinting geostationary communications satellite during a favorable Earth-satellite-Sun alignment. The results from this effort guided the development of the Amon Hen project, a hypertelescope that will be capable of obtaining direct images of geostationary satellites on a routine basis. The capabilities developed in this program will allow military systems to see farther with higher definition, allowing larger standoff distances from targets and objects of interest.

PRIMARY REFERENCE DOCUMENTS

- Armstrong, J.T., *et al.*, "The Navy Prototype Optical Interferometer," *Astrophysical Journal*, Vol. 496, 550 (1998).
- Hindsley, R.B., *et al.*, "Navy Prototype Optical Interferometer observations of geosynchronous satellites," *Applied Optics*, Vol. 50, 2692 (2011).
- Hutter, D. J., *et al.*, "Surveying the Bright Stars by Optical Interferometry. I. A Search for Multiplicity among Stars of Spectral Types F-K," *Astrophysical Journal S.S.*, Vol. 227, 4 (2016).
- Baines, E. K., *et al.*, "Fundamental Parameters of 87 Stars from the Navy Precision Optical Interferometer," *Astronomical Journal*, Vol. 155, 30 (2018).

MESOSCALE PREDICTION SYSTEMS

ACHIEVEMENT

The Coupled Ocean/Atmosphere Mesoscale Prediction System (COAMPS®) is the Navy's operational mesoscale (high-resolution) coupled prediction capability. The system is the culmination of several decades of collaborative development by the NRL Marine Meteorology and Oceanography Divisions. COAMPS provides state-of-the-art high-resolution numerical analysis and short-term (0- to 5-day) predictions of the atmosphere, ocean, and wave conditions for regional domains worldwide. COAMPS development began in 1988 became the Navy's operational mesoscale atmosphere model in 1998. By 2006, the Navy Coastal Ocean Model (NCOM), the Navy Coupled Ocean Data Assimilation (NCODA), and two-way ocean-atmosphere coupling were integrated into COAMPS. By 2010, the COAMPS coupling layer was extended to include coupling with ocean waves and the Wavewatch III and Simulating Waves Nearshore (SWAN) wave models.

As a result of this multidecade effort, the Navy has a world-class and exclusive capability to conduct new and extensive research on a number of phenomena in which air/sea/wave interactions are an important component of the physical processes, such as with tropical cyclones, explosive cyclogenesis, and electromagnetic and acoustic propagation. The atmospheric component of COAMPS allows for more accurate forecasts over areas that exhibit steep topographic features and strong convection. It predicts tropical cyclone track and structure (COAMPS-TC®), the distribution of aerosols, and explicitly predicts water and ice clouds as well as rain and snow.

IMPACT

COAMPS has supported Navy and DoD operations worldwide over the last 25 years by providing high-resolution predictions of the environment and it is used to drive many tactical applications. Environmental prediction products from COAMPS are distributed to DoD commands around the world to support mission planning, ship and aircraft operations, and hazardous weather avoidance. Its data are also used by academic institutions and government organizations (including NOAA/National Hurricane Center, NOAA/Central Pacific Hurricane Center, NOAA Central and Northern California Ocean Observing System).

PRIMARY REFERENCE DOCUMENTS

- Allard, R., *et al.*, "The US Navy coupled ocean-wave prediction system," *Oceanography*, 27(3), (2014) 92-103.
- Chen, S., *et al.*, "COAMPS version 3 model description," NRL/PU/7500-04-448, (2003) 143.
- Chen, S., *et al.*, Coupled Ocean Atmosphere Mesoscale Predicting System (COAMPS) full system version 2021 validation test report, NRL memorandum IR-7533-21-41U (2021).
- Doyle, J.D., Y. Jin, R. Hodur, S. Chen. Y. Jin. J. Moskaitis, S. Wang, E.A. Hendricks, H. Jin, T.A. Smith, 2014: Tropical cyclone prediction using COAMPS-TC. *Oceanography*, 27, 92-103.
- Doyle, J.D., *et al.*, "Real time tropical cyclone prediction using COAMPS-TC." *Advances in Geosciences*, 28, Eds. Chun-Chieh Wu and Jianping Gan, Singapore, 15-28.
- Hodur, R. M., 1997: The Naval Research Laboratory's Coupled Ocean/Atmosphere Mesoscale Prediction System (COAMPS). *Mon. Wea. Rev.*, 125, 1414–1430.
- Hodur, R. M., and J. D. Doyle, 1999: The coupled ocean/atmosphere mesoscale model prediction system (COAMPS). *Coastal Ocean Prediction, Coastal and Estuarine Studies* 56, 125-155.
- Jensen, T.G., T. Shinoda, S. Chen, M. Flatau, 2015: Ocean response to CINDY/DYNAMO MJOs in air-sea coupled COAMPS, *J. Meteorol. Soc. Jpn*, v93A, 157-178.

SURFACE ACOUSTIC WAVE CHEMICAL SENSORS

ACHIEVEMENT

NRL pioneered the use of surface acoustic wave (SAW) technology to detect chemical vapors including chemical warfare agents (CWA). The Laboratory's efforts, dating back to 1981, were supported in the developmental stages by the U.S. Army and the U.S. Air Force, and became a fielded technology when the DoD's Joint Chemical Agent Detector (JCAD) entered into low-rate production in 2007. Ultimately, the JCAD system based on SAW sensor devices was superseded by a handheld ion mobility spectrometry (IMS) technology. In a joint project, NRL partnered with the Army Edgewood Chemical Biological Center to develop a combined SAW-and-IMS chemical detector as a payload for an unmanned aerial vehicle.

Much of NRL's SAW R&D focused on developing chemically selective sorbent coatings for an array of devices to provide chemical selectivity, to amplify the signal response to hazardous chemistries, and to provide patterned signal responses to allow pattern recognition algorithm methods for CWA identification. In the early 1990s, NRL developed the first portable instrument to include a 4-SAW sensor array for patterned responses and a preconcentrator to provide increased sensitivity and analyte separations for improved system selectivity. From 1993 to 1995, an NRL-developed SAW sensor system was field tested. In the late 1990s, and early 2000s, an NRL-developed SAW sensor system was integrated into a miniature UAV for airborne applications.

IMPACT

SAW chemical sensors, like those implemented in JCAD, were a significant capability for military and homeland defense detection of chemical warfare agents. Advanced prototype units of JCAD were deployed in Operation Iraqi Freedom, and commercial models of JCAD subsequently became available. The handheld device sounded an alarm if nerve agents such as sarin or blister agents such as mustard gas were present. An earlier NRL SAW sensor system was developed for and employed by the U.S. Marine Corps Chemical and Biological Incident Response Force at the 1996 Olympics.

PRIMARY REFERENCE DOCUMENTS

- U.S. Patent No. 4,312,228 to Wohltjen, H., "Methods of Detection with Surface Acoustic Wave Apparati," January 26, 1982.
- U.S. Patent No. 5,756,631 to Grate, J.W., "Siloxanes with Strong Hydrogen Bond Donating Functionalities," May 26, 1988.
- U.S. Patent No. 5,469,369 to Rose-Pehrson, S.L., Dilella, D., Grate, J.W., "Smart Sensor System and Method Using a Surface Acoustic Wave Vapor Sensor Array and Pattern Recognition for Selective Trace Organic Vapor Detection," November 21, 1995.
- McGill, R. A., *et al.*, Sensors and Actuators B: Chemical, Vol 65, Issues 1–3, June 30, 2000, (10-13), "The 'NRL-SAWRHINO': a nose for toxic gases" DOI10.1016/S0925-4005(99)00352-4.
- Houser, E. J., *et al.*, "Recent Developments in Sorbent Coatings and Chemical Detectors at the Naval Research Laboratory for Explosives and Chemical Agents", Proc. SPIE 4038, Detection and Remediation Technologies for Mines and Mine-like Targets V, (August 22, 2000).
- U.S. Patent No. 6,289,328 to Schaffer, R.E., "Chemical Sensor Pattern Recognition System and Method Using a Self-Training *Neural Network* Classifier with Automated Outlier Detection," September 11, 2001.
- U.S. Patent No. 7,939,337 to McGill, R.A., Houser, E.J., "Carbosilane Polymers and Methods for Use in Analytical and Purification Applications," May 10, 2011.

AN/ALE-50 TOWED COUNTERMEASURES

ACHIEVEMENT

NRL's earlier development of monopulse radar provided a tenfold improvement in angular accuracy for long-range tracking by fire and missile-control radars.¹⁵⁹ By the 1970s, however, adversaries had applied monopulse capabilities to their surface-to-air missiles. This created a distinct threat to American aircraft. NRL responded to this threat by development of the Airborne Active Expendable Decoy (AAED), which was an electronic device designed to counter modern radar-guided anti-aircraft threats. Laboratory researchers initially explored the development of both towed countermeasures and decoys attached to aircraft launched missiles for threat deflection. Eventually, towed concepts proved more practicable, and the towed version of the AAED, the AN/ALE-50, was the first towed decoy to be used as an in-flight countermeasure.

The towed decoy concept differs from the traditional goals of electronic warfare, in which anti-aircraft missiles are denied the information needed to launch and intercept. Advances in monopulse radars and processing have made this an increasingly hard task. Instead, the towed decoy's effectiveness lies in looking more like an aircraft than the aircraft itself, pulling the threat to itself instead of pushing it away, as in the case for onboard systems.

During the joint Navy/Air Force Multi-Service Decoy Program, flightworthy devices were tested and proved to be extremely effective. Over the years, the AN/ALE-50 surpassed expectations at every stage of its development. More than 25,000 decoys have been delivered for use on F-16, F/A-18E/F, and B-1B aircraft.

IMPACT

At a relatively modest cost of \$22,000 per decoy,¹⁶⁰ NRL's AN/ALE-50 made billions of dollars' worth of advanced anti-aircraft threats in the hands of the U.S.'s opponents less effective. It has had a dramatic impact on the way U.S. aircraft fly and fight. Before the AN/ALE-50, aircrews were forced to fly low-altitude, "nap-of-the-earth" flight paths to avoid the radar-guided threat, which, in turn, forced them into the envelope of shoulder-fired missiles and anti-aircraft artillery. In fact, this decoy protects combat aircraft so well that it earned the nickname "Little Buddy" from our pilots.¹⁶¹ In the Kosovo campaign alone, 1,479 were used and the system was credited with saving several aircraft.¹⁶²

PRIMARY REFERENCE DOCUMENTS

- DD1498, "Airborne Active Expendable Decoy," WU#57-1284-0, dated May 12, 1980.
- ASN (RD&A) memorandum to Program Executive Officer for Tactical Aircraft Programs, subj. "AN/ALE-50 (V) Countermeasures Decoy Dispensing Set Milestone III Approval," Dec. 9, 1996.

¹⁵⁹ Gebhard, L.A., *Evolution of Naval Radio-Electronics and Contributions of the Naval Research Laboratory*, NRL Report 8300, 1979, 200.

¹⁶⁰ Association of Old Crows Press Release, "Electronic Weapons: Little Buddy Goes Stealthy", 2 July 2020.

¹⁶¹ "Order for ALE-50 Doubles After Success in Kosovo," *Aviation Week & Space Technology*, 15 November 1999.

¹⁶² Lambeth, B., *Aerospace Power Journal*, Summer 2002, 21.

ANTI-SHIP MISSILE DEFENSE RADAR

ACHIEVEMENT

In response to the USS *Stark* incident in 1987, and to the increased deployment of U.S. forces in dangerous littoral and other heavy-clutter environments, NRL developed and tested shipboard radars that can detect and track low-radar-cross-section air and surface targets in challenging clutter environments that pose potential threats to naval assets.

Low-Observable Detection and Tracking — Beginning in the 1980s, NRL developed the technology necessary for reliable detection of small targets in clutter and demonstrated them using the NRL-developed, high-power SENRAD surveillance radar testbed. The techniques operate the radar at full sensitivity, enabling detection and tracking of small targets at very long ranges. Laboratory researchers designed the transmitted waveform and innovative, new processing techniques enabling the radar to reject echoes from stationary clutter and slow-moving nuisance targets. The radar was then able to concentrate on the small, high-speed targets of interest, with a low false tracking rate. The technology was transitioned to an upgrade of the AN/SPS-49 radar.

Sea Skimmer Detection Radar — Beginning in 1990, the Laboratory developed the concept for what became the new AN/SPQ-9B Anti-Ship Missile Defense Radar (ASMD). The concept incorporated a new air mode that provides low RCS sea-skimmer detection capability and a surface mode with improved performance over the AN/SPQ-9A. An Advanced Development Model was constructed and successfully demonstrated in land-based tests and at sea aboard the USS *Decatur*. This model was able to detect and track sea-skimming missiles near the horizon in difficult littoral environments, with extremely low false alarm rates. The radar operates simultaneously in both surface and air modes, with the air mode providing an unprecedented clutter-rejection level that was orders of magnitude better than previous technology. The surface mode was able to track small boats and helicopters in heavy sea clutter. The concept was rapidly developed, demonstrated, and transitioned to production at an affordable cost. The production contract for what became the AN/SPQ-9B radar was awarded in 1994.

IMPACT

The AN/SPQ-9B radar scans out to the horizon and performs simultaneous and automatic air and surface target detection and tracking of low flying anti-ship cruise missiles, surface threats, and low/slow-flying aircraft, UAVs and helicopters. It is an important addition to naval sensors in challenging environments such as the Red Sea and the Persian Gulf. The radar is installed on the CVN-68, LPD-17, DDG-51, CG-47, WMSL-750, LHD-1, and LHA-6 ship classes. NRL's low-observable detection technology has been able to provide the AN/SPS-49 radar the ability to detect and track very small high-speed targets through heavy land, sea, rain and ducted clutter, as well as when large numbers of nuisance objects, such as birds, are present. It provides the Navy the capability to detect and defend itself from attacks from small, high-speed vessels in the littoral environment.

PRIMARY REFERENCE DOCUMENTS

- Trunk, G.V., Gordon, W.B., Cantrell, B.H., "False alarm control using ambiguous velocity" Proceedings of the IEEE National Radar Conference, (1989), 73.
- Trunk G.V., Gordon, W.B., and Cantrell, B.H., "False Alarm Control Using Velocity Estimation," National Radar Symposium, Dallas Texas, March 29-30, (1989), 73-75.

CT-ANALYST

ACHIEVEMENT

NRL's CT-Analyst® system (Contaminant Transport Analyst system) is the first operational instantaneous emergency assessment system for airborne contaminants and weapons of mass destruction (WMD) threats in cities. It is a product application that was made possible by many years of NRL's related work in basic fluid dynamics and atmospheric research.

CT-Analyst takes full account of the effect of buildings on the airflow and is faster and more accurate than other existing systems. It can run on a PC and automatically combines data from sensors and verbal reports to plot optimal evacuation routes through use of a new fluid-dynamics solution methodology called dispersion nomographs. This new approach uses detailed 3D, high-resolution fluid simulations to generate a complete database for the wind flow over a city, with all buildings and trees included. The database is compressed into 18 tables, or dispersion nomographs, one for each of 18 wind directions over the city.

IMPACT

CT-Analyst was deployed as the nation's crisis-management model and was used at the HazMat Reachback Center (HRC), hosted by NRL during the 2009 presidential inauguration under the auspices of the Secret Service and the National Medical Response Team. The HRC was designated to provide crisis and consequence assessment for the Washington, D.C., area in the event of an airborne contaminant release. Participants included the Federal Bureau of Investigation, D.C fire and police personnel, Army and Marine chemical incident support teams, the Department of Homeland Security, and the Defense Threat Reduction Agency. CT-Analyst has also been deployed in Los Angeles for the DHS Golden Phoenix exercise.

At the 2013 inauguration, CT-Analyst provided the capability for initial assessment of possible airborne contaminant threat to the NRL team working in the Scientific Reachback Center (SRC) at the FBI's All Hazards Center, the coordinating center for emergency responses. CT-Analyst was used specifically because of its speed and accuracy in modeling plumes in complex urban geometries and assessing any potential threat. The assessments provided by CT-Analyst were available for review within a minute or two. CT-Analyst also supported the 2017 and 2021 inaugurations.

CT-Analyst has supported security for several Super Bowls, the Academy Awards, and State of the Union events. It is deployed with federal emergency managers, police, and fire officials in Washington, D.C., Los Angeles, Boston, Chicago, Hamburg, Germany, and Oslo, Norway.

PRIMARY REFERENCE DOCUMENTS

- Boris, J.P., Obenschain, K., Patnaik, G., and Young, Jr., T., "CT-Analyst: Fast *and* Accurate CBR Emergency Assessment," Proceedings of the First Joint Conference on Battle Management for Nuclear, Chemical, Biological, and Radiological Defense, November 4-8, 2002.
- Boris, J.P., "The Threat of Chemical and Biological Terrorism: Preparing a Response," *Computing in Science and Engineering* 4 (2), March/April 2002, 22-32.
- Boris, J.P., "Dust in the Wind: Challenges for Urban Aerodynamics," AIAA 2005 Fluid Dynamics Prize Address, 17th AIAA Fluid Dynamics Meeting, Toronto Canada, June 4-8, 2005, AIAA Paper 2005-5393, American Institute for Aeronautics and Astronautics, Reston VA.
- Patnaik, G., Boris, J., Grinstein, F., Iselin, J., and Hertwig, D., "Large Scale Urban Simulations with FCT," in *Flux-Corrected Transport – Principles Algorithms, and Applications*, 2nd Edition, Kuzmin, D., Löhner, R. and Turek, S. Eds., Springer 2012.

MOUNTAIN WAVE FORECAST

ACHIEVEMENT

Mountain waves are among the most hazardous conditions that aircraft encounter. They are the result of air rising up the windward side of a mountain and then, under certain atmospheric conditions, descending on the leeward side. This results in the formation of a series of standing waves downwind from the mountain that may extend over considerable areas and form a potential flight hazard.¹⁶³

Mountain wave turbulence is the major global source of severe turbulence for high-altitude, long-endurance Department of Defense aircraft such as the U-2s and Global Hawk unmanned aerial vehicles (UAVs). To reach their 60,000- to 70,000-foot cruise altitudes, such aircraft must eliminate weight and maximize lift, sacrificing some of the heavy structural rigidity of conventional aircraft. This makes them vulnerable to any severe turbulence they may encounter at altitude. These aircraft also have enormous geographical range, and thus require global forecasts of atmospheric conditions for safe flight planning.

In response to these challenges, NRL developed the Mountain Wave Forecast Model (MWFM), which is the only meteorological model capable of globally forecasting mountain wave activity and wave-induced turbulence in the Earth's atmosphere from near the surface to beyond 100,000 feet. MWFM is also a valuable tool for fundamental atmospheric research. It has been used to direct flights with NASA/European Union aircraft and balloons for studying the physics of polar stratospheric clouds. MWFM provides hemispheric hindcasts of mountain wave effects for global chemical transport models related to the study of the seasonal impact of polar stratospheric clouds on winter ozone loss in the Arctic, and it has provided modeling support for the first observations of mountain waves from satellite platforms.

IMPACT

The MWFM, adopted for operational use by the U.S. Air Force, is a significant tool in identifying and forecasting middle and upper atmosphere turbulence and reducing risks to in-flight military and civilian aircraft and occupants.¹⁶⁴ It was used to predict flight conditions for allied aircraft during operations Southern Watch, Enduring Freedom, and Iraqi Freedom. It was also adapted to run hindcasts of stratospheric mountain wave turbulence over Afghanistan from 1994 to 2001. This was done in order to generate a multiyear climatology of anticipated turbulence levels and geographical distributions in response to requests from the Air Force Combat Climatology Center. In addition, NASA has requested MWFM turbulence forecasts for flight planning during airborne science campaigns with their instrumented DC-8 and high-altitude ER-2 research aircraft.

PRIMARY REFERENCE DOCUMENTS

- Bacmeister, J.T., Newman, P.A., Gary, B.L., and Chan, K.R., "An Algorithm for Forecasting Mountain Wave Related Turbulence in the Stratosphere," *Weather Forecasting*, Vol. 9, 241-253 (1994).
- Eckermann, S.D., "Climatology of Mountain Wave-Induced Turbulence in the Stratosphere over Central Asia: October-December 1994-2001," NRL Technical Memorandum, (NRL/MR/7640-02-8594), May 24, 2002.

¹⁶³ Australian Transport Safety Bureau, Public Education Factsheets, "Mountain Wave Turbulence."

¹⁶⁴ NRL Press Release, "Dr. Stephen Eckermann Receives NRL Sigma Xi Award for Applied Science," 11 October 2013.

LOW-SOLAR-ABSORBANCE SHIP PAINT

ACHIEVEMENT

NRL developed low-solar-absorbance (LSA) paint in order to reduce solar heating on Navy ships. The paint was tested in 1995, when it was applied to the USS *Dextrous* (MCM 13), and it produced a significant reduction in surface temperatures during summertime operations in the Gulf of Mexico. Testing demonstrated that LSA not only reduced ship surface temperatures and the load on air conditioning systems, but it also decreased the ship's infrared signature.

The USS *Dextrous* was relocated to the Persian Gulf, where the paint's solar-reflective properties reduce heat buildup, increase crew comfort, and decrease the ship's infrared (IR) ship signature. LCA paint has been transitioned into the fleet, and now all Navy ships are painted with the NRL-designed paint.

IMPACT

LSA paint has reduced solar heating on Navy ships, leading to lower air conditioning and maintenance costs and greater crew comfort. The paint has reduced the susceptibility of all coated Navy ships to hostile IR sensors and to IR-guided munitions. The per-gallon cost of the LSA paint is virtually identical to the Standard Haze Gray paint it replaced, resulting in a cost-effective infrared stealth technology for the Navy. For many years, it was the standard Navy paint system, and the concepts of pigmenting paints for LSA properties are still in use today in new generations of paint systems.

PRIMARY REFERENCE DOCUMENTS

- Brady, R.F. and Wake, L.W., "Principles and Formulations for Coatings with Tailored Infrared Properties," *Progress in Organic Coatings*, Vol. 20, no. 1, pp. 1-25 (1992).
- Dries, J., D. Fraedrich and Surko, S., "Infrared Ship Signature Reductions Using Low-Solar Absorbance paint," *Proceedings of the 41st Annual Joint Electronic Warfare Conference*, San Francisco, 1996.
- Surko, S. and Fraedrich, D., "Haze Gray and ... Sunk?," *U.S. Naval Institute Proceedings*, Vol. 123, no. 11 (November 1997), 67-69.

TACTICAL COMMUNICATIONS

ACHIEVEMENT

In the 1990s, NRL developed three major items of tactical receive equipment: the Multi-Mission Advanced Tactical Terminal (MATT), the Improved Data Modem (IDM), and the Joint Combat Information Terminal (JCIT). MATT filled a need for a miniaturized multifunction radio and processor that provided near-real-time national intelligence data to field commanders or tactical fighters. The U.S. Special Operations Command selected NRL to develop MATT. The IDM established the first digital data link capability between fighter aircraft and between fighter aircraft and ground units. IDM gave pilots the ability to do in seconds (or less) what used to take several minutes by voice radio, thus minimizing exposure to enemy jamming and/or transmission interception. In 1994, the U.S. Army contracted NRL to develop an airborne tactical operations center (TOC) that was to be housed in a UH-60 Black Hawk helicopter. The TOC would need to support 37 heritage radios, an impossible housing and power demand for a helicopter. To meet the Army's needs, NRL developed JCIT. Through the mediation of software, JCIT took the place of the 37 heritage radios, demanding as a consequence only a fraction of the latter's size, power, and weight.

Using knowledge gained through the MATT, IDM, and JCIT programs, NRL designed an interoperable communication infrastructure called InfraLynx to provide assured communications to military commanders. Three days after the September 11, 2001, attacks, NRL responded by integrating InfraLynx architecture into two Highly Mobile Multipurpose Wheeled Vehicles to provide an IP satellite-enabled system with multiple telephone lines, high-speed network access, private cellular and radio interoperability, and radio frequency cross-banding capabilities. This allowed first responders to communicate when local infrastructure is destroyed, as was the case with the World Trade Center, or when the infrastructure is completely saturated, as was the case at the Pentagon. InfraLynx platform variations were delivered to U.S. Northern Command (NORTHCOM), the Federal Emergency Management Agency, the Marine Corps, the Air Force, and others.

More recently, NRL developed the reconfigurable-while-in-operation Software Reprogrammable Payload (SRP). SRP offers cost savings to communications, intelligence, surveillance, and reconnaissance payloads by solving the problem once with a single software infrastructure-and-hardware architecture that can be hosted on land, sea, air, and space platforms.

IMPACT

The Federal Office of Domestic Preparedness adopted InfraLynx and began a program to increase the awareness of this technology. InfraLynx was deployed to the 2002 Winter Olympics, weapons of mass destruction training exercises, and Super Bowl XXXVII, as well as the Democratic National Convention and the G8 Summit in 2004. In 2005, NORTHCOM deployed its own InfraLynx asset, which was the first to reestablish communications after Hurricane Katrina. In 2009, InfraLynx was a key communications element in a nuclear-weapons-incident exercise. InfraLynx was successfully transitioned to Honeywell International, Inc.

PRIMARY REFERENCE DOCUMENTS

- MOA between the U.S. Air Force and NRL for the Development of the IDM, December 5, 1990.
- MATT Certification Approval, NSA R091819 (December 1993).
- SSD-S-AA800 Prime Item Development Specification for the JCIT
- U.S. Patent Application 10/691,643, "Infrastructure Linkage and Augmentation System (InfraLynx)," October 2003.
- Dixit, J., "So That a Disaster Doesn't Become a Communications Disaster," *New York Times*, (September 12, 2002), 7.

HYPERSENSPECTRAL IMAGER FOR TACTICAL AND ENVIRONMENTAL USES

ACHIEVEMENT

The F/A-18 SHARed Reconnaissance Pod (SHARP) is a digital reconnaissance system developed by NRL to replace the aging, film-based F-14 Tactical Airborne Reconnaissance Pod System (TARPS). SHARP provides high-resolution visible and infrared digital imagery from medium- and high-altitude cameras. The system is controlled by the NRL-developed Reconnaissance Management System to enable real-time compression, onboard storage and manipulation, and off-board dissemination to ground and sea-based forces in real time via wideband radio links. NRL-developed ground station technology is used to receive and exploit the SHARP imagery. SHARP includes day/night imaging, in-cockpit image review and exploitation, precision geocoordinate determination for targeting applications, and manual or automatic mission execution. The multifunctional technology is adaptable to manned or unmanned platforms.

NRL has also developed hyperspectral imaging technologies, which have been used to study the environment and to detect man-made objects to defeat concealment and camouflage techniques. NRL developed the first gimbal-stabilized shortwave hyperspectral imager designed for long-range operation. The Long-Range Oblique Hyperspectral Sensor (MX-20SW) resulted in the transition of capabilities into operational use in 2010 in Afghanistan via the Radiant Falcon program and in other locations worldwide.

Hyperspectral imaging technologies can also collect data with the resolution and fidelity necessary to address many aspects of the ocean environment that impact naval operations. NRL's Hyperspectral Imager for the Coastal Ocean (HICO) is a spaceborne sensor flown on the International Space Station (ISS). HICO demonstrated the utility of hyperspectral imaging for the study of the world's coastal oceans, lakes, and inland waterways. The sensor operated nearly continuously aboard the ISS from September 2009 through September 2014, collecting approximately 10,000 images and greatly exceeding the design lifetime.

IMPACT

The first SHARP production systems were installed on carrier-based F/A-18 aircraft and were deployed in Operation Iraqi Freedom, Operation Enduring Freedom, and Operation Tomodachi. NRL's prototype predecessor system, TARPS – Completely Digital, was also operationally deployed four times with F-14 squadrons on the USS *Kennedy*, the USS *Truman* (twice deployed), and the USS *Stennis* from 1999 to 2003. Front-line coalition forces received targeting imagery directly. The timelines of this imagery, as opposed to the three- to nine-day norm associated with predecessor imaging systems, was critical to advancing U.S. objectives and saving coalition lives. The SHARP program development outperformed “all previous joint service efforts to rapidly develop, prototype, and field affordable manned and unmanned imaging systems.”¹

PRIMARY REFERENCE DOCUMENTS

- Kent, D.C. “The SHARed Reconnaissance Pod (SHARP) Program,” in Airborne Reconnaissance XXV, Vol. 4492, *Proceedings of SPIE*, 2002, 42-52.
- Duncan, M.D., *et al.*, “Report on the SHARP Prototype Effort,” NRL Formal Report NRL/FR-MM/5633-01-10,015, December 17, 2001.
- Duncan, M.D., Kruer, M.R., Lee, J.N., and Linne von Berg, D.C., “Transforming Manned Recon: Navy Embraces Digital Imaging for Carrier-Based Fighters,” *Intelligence, Surveillance and Reconnaissance Journal*, May-June 2003, Vol. 2. No. 3, 15-22.
- Gao, B.C., *et al.*, Vicarious calibrations of HICO data acquired from the International Space Station. *Appl. Opt.* 51(14), 2012, 2559-2567.

¹ Johnson, J.M., USN (Ret.) and Lobb, M., USMC (Ret.), “Manned Reconnaissance Must Continue,” *U.S. Naval Institute Proceedings*, Vol. 129, No. 7 (July 2003), 36-38.

DRAGON EYE

ACHIEVEMENT

NRL, in collaboration with the Marine Corps Warfighting Laboratory, developed an affordable and expendable airborne sensor platform, Dragon Eye, to provide reconnaissance capabilities to small units of Marines, to assess battle damage, to detect threats over the next hill or around the next building, and to prevent casualties from friendly fire. Dragon Eye went from a paper sketch to an operational system in 30 months. Prototype evaluation began in 2001. Production aircraft were deployed in Iraq and Afghanistan by 2004.

Dragon Eye was developed as a follow-on effort to the Miniature Tactical Expendable (MITE) micro unmanned aerial vehicle effort within NRL. The MITE effort focused on the capabilities that a micro unmanned aerial vehicle could provide the warfighter, primarily in the areas of over-the-hill reconnaissance and close-in electronic warfare missions.

Dragon Eye consisted of a man-portable, 5.5 lb., hand-launched aerial vehicle with the radar signature of a bird. A miniature ground control station provided command and control and received the aircraft's video and GPS position. The vehicle flight characteristics permitted operational use in adverse weather conditions, and the autonomous flight capability allowed one-person operation.

IMPACT

Dragon Eye was successfully transitioned to the Marine Corps Systems Command, and preproduction units were deployed with the 1st Marine Expeditionary Force in Iraq during Operation Iraqi Freedom (OIF). These units provided critical intelligence to American forces in the field. A post-OIF review from the 1st Marine Division noted that on-site intelligence delivered by Dragon Eye proved to be the conspicuous bright spot in overall OIF intelligence gathering.¹⁶⁵ Dragon Eye was mentioned in a *New York Times* front-page article about the U.S. Marines' fight for Falluja.¹⁶⁶ By 2010, a total of more than 1,300 Dragon Eye aircraft, designated RQ-14A, had been deployed.

In 2008, the Smithsonian National Air and Space Museum debuted an exhibit showcasing Dragon Eye, along with five other military unmanned aerial vehicles. Also on display were Dragon Eye's computer controls, a parts-and-tool kit, and a bungee-cord launching system.

PRIMARY REFERENCE DOCUMENTS

- Foch, R., "Affordably Expendable Unmanned Air Vehicles," White Paper prepared for the Secretary of the Navy, April 1999.
- Foch, R., Dahlburg, J., McMains, J. *et al.*, "Dragon Eye, an Airborne Sensor System for Small Units," AUVSI Unmanned Systems 2000, July 11-13, 2000, Orlando, Florida.
- Foch, R. *et al.*, "Dragon Eye Small UAV SECNAV Initiative Rapid Development Program," White Paper prepared for the Secretary of the Navy, March 2002.
- Kahn, A. and Kellogg, J., "A Low-Cost, Minimum-Complexity Altitude/Heading Hold Flight Control System," IEEE 21st Digital Avionics Conference, Oct. 2002.
- Klemm, F., "Dragon Eye—A Small UAV: From a Paper Sketch to an Operational System in 30 Months," June 7, 2010.

¹⁶⁵ Jaffe, G., "U.S. Intelligence in Iraq Comes Under Fire From Army, Marines," *The Wall Street Journal*, 8 December 2003, B2.

¹⁶⁶ Filkins, D., "In Falluja, Young Marines Saw the Savagery of an Urban War," *New York Times*, 21 November 2004, 1.

PULSED X-RAY RADIOGRAPHY

ACHIEVEMENT

NRL enabled breakthrough advances in pulsed X-ray radiography with its invention of the rod-pinch diode in the late 1970s. When a high-current pulse of electrons converges onto the tip of this small-diameter diode, it produces an extremely intense burst of X-rays unmatched by conventional sources. Since 2000, NRL has made significant progress in refining the original vacuum rod pinch. A second-generation version of the diode, the plasma-filled rod pinch, produces an extremely intense X-ray source with parameters previously thought to be impossible with conventional techniques.

IMPACT

NRL's patented device plays a vital role in the Department of Energy's Stockpile Stewardship Program, where it provides images of unprecedented resolution in dynamic experiments studying the performance and safety of nuclear weapons components. In particular, the program requires radiography sources to diagnose the performance of nuclear weapons components at extreme densities and pressures.

NRL's device was the X-ray source for the Cygnus generator used in an experiment at the Nevada Test Site that demonstrated a major leap in capability, leading the Los Alamos National Laboratory to state, "Many innovations have combined to lead to this leap in performance, but perhaps the most important has been the effective realization of the rod-pinch diode originally developed at NRL."¹⁶⁷

NRL scientists received two DOE Nuclear Weapons Program Awards of Excellence in 2002 and 2004 in recognition of this work.

PRIMARY REFERENCE DOCUMENTS

- U.S. Patent No. 4,213,073 to Mahaffey, R. A., Goldstein, S.A., Golden, and J., Cooperstein, G., "Rod Pinch Diode," July 15, 1980.
- Cooperstein, G., *et al.*, "Theoretical Modeling and Experimental Characterization of a Rod-Pinch Diode," *Physics of Plasmas* 8, 4618-4636 (2001).
- Weber, B.V., *et al.*, "Ultra-high Electron Beam Power and Energy Densities Using a Plasma-Filled Rod-Pinch Diode," *Phys. Plasmas* 11(5), May 2004.

¹⁶⁷ Fulton, R.D., Wilke, M.D., King, N.S.P., "Dynamic Materials Studies in Subcritical Experiments: Rocco, Mario, Vito, and Armando," Materials Studies Research Highlights (Physics Division: Los Alamos National Laboratory), February 2003, 26.

SILENT GUARDIAN: DNA MICROARRAY TECHNOLOGY

ACHIEVEMENT

Concerned about biological threats in the weeks surrounding the 2005 presidential inauguration, the assistant secretary of defense/nuclear, chemical, biological, ASD(NCB), directed that the Air Force surgeon general (AF/SG) and NRL operationally demonstrate a breakthrough biosurveillance technology developed by NRL for the Air Force's Epidemic Outbreak Surveillance (EOS) project. The technology, the Resequencing Pathogen Microarray (RPM), resulted from the progress made in long-term NRL basic research. RPM was a system that could identify up to 100 different pathogen species in a single test using genetic sequencing and new bioinformatics algorithms. The ASD(NCB) directed that the biosurveillance capability become operational in December 2004 and process up to 10,000 samples from military medical facilities across the National Capitol Region through January 2005.

The combined Silent Guardian team, comprising NRL scientists, Navy reservists, and U.S. Air Force staff, moved from routine laboratory research to full operational capability in less than six weeks. In samples collected from the active-duty military population, the team identified a full spectrum of circulating respiratory pathogens, often at the level of strains or individual variants (*e.g.*, influenza virus). Inactivated biothreat agents, spiked into blinded samples, were also detected. An operational throughput of 300 test results from patient samples within 24 hours was demonstrated.

IMPACT

The Silent Guardian demonstration used NRL technologies to provide broad-spectrum pathogen surveillance of the Washington, D.C., region during the weeks surrounding the 2005 presidential inauguration. Later results demonstrated identification of all pathogens at $\geq 98\%$ as compared to a battery of gold standard tests. The use of genetic sequences for broad-spectrum pathogen identification was a historical first, preceding the capabilities of "next-generation sequencing" technologies developed since 2005. Sample processing and bioinformatics algorithms developed during Silent Guardian remain in widespread use today.

NRL transferred RPM technology to TessArae, LLC in 2007, for which NRL was awarded a Federal Technology Transition award. The commercial RPM was used by the Navy during the initial identification of pandemic H1N1 influenza in 2009 at the US-Mexico border, and was approved by the U.S. Food and Drug Administration for H1N1 influenza diagnosis. High-multiplex polymerase chain reaction target amplification developed in Silent Guardian is part of current and future DoD programs of record for genetic sequence-based pathogen identification.

PRIMARY REFERENCE DOCUMENTS

- Memorandum from the Assistant to the Secretary of Defense (Nuclear, Chemical and Biological Programs), subj: "National Capital Region Microarray Biodefense Detection," November 2004.
- Lin, B. *et al.*, "Application of a Broad-Spectrum, Sequence-Based Pathogen Identification in an Urban Population," *PLoS ONE* 2(5):e419 (2007).

TACTICAL SATELLITE (TACSAT)

ACHIEVEMENT

By 2002, a variety of technical developments prompted NRL and the DOD Office of Force Transformation (OFT) to study the potential of tasking space assets for tactical operations. A number of emerging technologies and processes combined to make the OFT's Operationally Responsive Space (ORS) initiative a timely pursuit. For space assets to become operationally responsive in the event of sudden crises, rapidly deployable spacecraft must be available to support U.S. military operations anywhere on Earth, adaptable to payload and orbital constraints.

ORS ran a series of experiments, with NRL serving as the program manager for TacSat-1, the first experiment of the initiative, which served as the pathfinder for a series of experiments. TacSat-2 and TacSat-3 were Air Force-led with multiple NRL experiments aboard, and were launched in 2006 and 2009. NRL was the program manager for Navy's TacSat-4 spacecraft, which launched in 2011. It operated until February 2013. TacSat-4's mission was to augment operational communications. It provided ten UHF channels allowing communication on the move, data exfiltration, and Blue Force tracking. The unique orbit augmented geosynchronous communications by providing near-global, but not continuous, coverage. The Virtual Mission Operations Center tasking system allowed tactical tasking and dynamic reallocation, within 24 hours, to different theaters worldwide when unexpected operations or natural events occur.

IMPACT

The TacSat program put new capabilities into the hands of operational users in order to advance technologies and concepts of operations, as well as to provide operational value. In particular, TacSat-4 demonstrated that small satellites can provide SATCOM services to naval and joint military forces, and to civil defense agencies using their standard equipment, in high latitudes and geographically denied locales. TacSat-4 was a smaller, cheaper satellite that could be launched in geosynchronous or nongeosynchronous orbit to augment coverage or to provide coverage outside the area covered by geosynchronous satellites.

Trident Warrior 2012 (TW-12) was the capstone experiment for TacSat-4. TW12 established that TacSat-4 was capable of providing UHF and data support to operational users including communication on the move to the warfighter. It provided reliable IP connectivity for voice and data communications. Insights on the utilization of a satellite in a nongeosynchronous orbit were obtained, including antenna setup for communication windows determined by the orbit. The key point is that a small constellation of TacSat-4-class spacecraft would offer significant military utility for UHF satellite communication augmentation in the high northern latitudes to partially fill northern latitude communication gaps.

PRIMARY REFERENCE DOCUMENTS

- Hurley, M., Hauser, J., Felt, R., and Duffey, T., "Microsatellite Deployment on Demand," paper for AIAA-LA Section/SSTC Responsive Space Conference, 2003.
- Weldy, K., *et al.*, "TacSat-4 Mission and the Implementation of Bus Standards", paper for AIAA-Utah State Small Satellite Conference, 2008.
- Sandhoo, G., *et al.*, "Standards for Responsive Small Satellites," Proceedings of the 4S Symposium—Small Satellites Systems and Services," Noordwijk, Netherlands, May 26-30, 2008.
- Anderson, M. *et al.*, "Tactical Satellite 4 (TacSat-4) Joint Military Utility Assessment (JMUA) Final Report", November 1, 2012
- Henderson, B., Jolly, H.S., and Marchetti, C. Col CAN, "The TTRDP Project on Small Satellite Military Utility Final Report" TTRDP-SSMU-2014-7-ALL-2.0-U, September 15, 2014.

PERSONAL PROTECTIVE EQUIPMENT AND INJURY BIOMECHANICS

ACHIEVEMENT

QuadGard Body Armor — By 2005 nearly two-thirds of the wounds sustained by U.S. troops in Iraq and Afghanistan were to the extremities, with 6 percent of the wounded requiring amputations.¹⁶⁸ Medical personnel reported that fragments about the size of a pencil eraser caused most of these wounds, typically from improvised explosive devices (IEDs). QuadGard was the result of a rapid-response program to protect soldiers and Marines from the severe limb injuries caused by IEDs. NRL led a government-university-industry team to develop flexible, lightweight tactical garments that provide blast protection to arms, shoulders, legs, hips, and buttocks. Weighing only 10 pounds, the body armor incorporated new ballistic materials and designs determined after exhaustive studies that balanced vulnerability to injury and amputation against factors such as weight, flexibility, and comfort.

GelMan Head Protection — NRL developed a system to test the effects of blasts or impacts on live brain cells within an anthropomorphic human head surrogate. The cells are contained within a sealed cell pack that allows the cells to be removed from the laboratory environment and tested under real conditions, such as during training courses with live blast events. The anthropomorphic head allows for the determination of the effect of protective headgear, such as helmets, on cell response to blast or impact. The cell cultures are primary mouse cortex neurons grown in a 3D collagen hydrogel to mimic their native environment. The GelMan-Head system consists of a plastic human skull mounted to a standard Hybrid III neck. The “brain” comprises two pieces. The rear section contains a pocket to hold the cell pack, while the front portion of the “brain” mimics the properties of gray matter. The skull/brain/cell pack system can be fitted with helmets or other protective gear.

IMPACT

QuadGard transitioned from concept to combat use in only 17 months and was immediately fielded by U.S. Marine units in Iraq, followed soon after by Navy Seabees. Additional sets were provided to the Army and the Air Force for testing and evaluation purposes. The potential operational uses of the body armor include convoy crews, checkpoint duty, security operations, roadside patrols, explosive ordnance reconnaissance, and forward-deployed medical personnel.

The GelMan system provided the first method for exposing brain cells to blast events under realistic conditions and represents a novel method of determining the mechanisms by which blast events can alter the biology of the brain. It also offers potential for a biological component to helmet performance testing.

PRIMARY REFERENCE DOCUMENTS

- Matic, P. and Hubler, G., “Report on Limb Protection Options for CY2004 Marine Corps Deployments to Operation Iraqi Freedom,” White Paper prepared for the Chief of Naval Research, February 25, 2004.
- Rupert, N.L., *et al.*, “QuadGard Limb Protection Program,” *Proceedings of Personal Armor Systems Symposium*, Leeds, England, Sept. 19-22, 2006, Seabolt, Ipswich, UK (2006).
- O’Shaughnessy, T.J., McCulloch, R., Bagchi, A., Simmonds, K., Full head surrogate with live neurons for helmet testing and evaluation. U.S. Patent 9,395,265 issued July 19, 2016.
- O’Shaughnessy, T.J., *et al.*, Modular system for evaluating helmet and suspension materials for protection of neural cells from simulated trauma. U.S. Patent 9,488,547 issued November 8, 2016.

¹⁶⁸ Matic, P. and Hubler, G.K., “Extreme Armor,” *Armed Forces Journal* (February 2005), 49.

RAPID-CURE CORROSION-CONTROL COATINGS

ACHIEVEMENT

NRL pioneered, developed, and commercialized durable rapid-cure coatings designed for harsh environments. Such coating systems reduced a three-coat painting process to a single-coat process and offer a nearly instant “walk-on time” and a rapid return to service, typically in minutes, not hours or days, as with other systems. Superior chemical resistance also makes it suitable for the interior and the exterior of shipboard tanks for fresh water and seawater, fuel, and waste. Added benefits are low environmental impact and longer times between repainting. Typical recoat times for legacy materials were 3–5 years. These new, solvent-free coating systems are expected to have a 20-year service life.

The novel coatings emerged from NRL’s basic research program. NRL’s long-term relationships with the Naval Sea Systems Command (NAVSEA) and with the paint and coatings industry allowed NAVSEA to catalyze the development of these novel coating systems and to get them into service. This is significant, as corrosion costs the DOD more than \$20 billion per year.¹⁶⁹ In 2009, Vice Admiral Kevin M. McCoy of NAVSEA stated, “by September 2009, there will not be a seawater tank painted on a U.S. Navy ship that’s not rapid-cure, single-coat process ... We’re doing that on submarines, on aircraft carriers and on surface ships, and we’re already seeing the savings coming from that.” The single-coat process on one submarine alone saves “well over \$100,000.”¹⁷⁰

IMPACT

NRL’s high-performance corrosion-control coatings have revolutionized tank refurbishment by reducing a three-coat painting process to a single-coat process and by reducing total production time by more than 80% with rapid-cure technology. After over 70 successful demonstrations across 18 platforms, the rapid-cure coatings were mandated for use in all seawater ballast tanks.

According to NAVSEA, the potential fleetwide cost savings over the coatings’ expected 20-year life cycle is \$1.8 billion.¹⁷¹ Total savings reach nearly \$2 billion when combining projected savings from the use of NRL-developed remote tank inspection and monitoring systems, which reduce the time and expense of inspecting the tanks. In 2012, the NRL team was recognized with the Office of Naval Research Prize for Affordability for their development of rapid-cure single-coat tank coatings.¹⁷² This technology, which has been implemented fleetwide, continues to make a significant contribution toward reducing the total costs associated with corrosion control for U.S. Navy ships and submarines.

PRIMARY REFERENCE DOCUMENTS

- Webb, A.A., *et al.*, “Reducing corrosion control costs with rapid-cure coatings,” *2007 NRL Review*, 63–69 (2007).
- Webb, A.A., Slebodnick, P.F., Martin, J.R., Kennedy, W., “Application of Rapid Cure Coatings in Shipboard Tanks for Maintenance Cost Reduction”, *American Society of Naval Architects Conference*, Norfolk VA, September 19, 2007.

¹⁶⁹ GAO-14-337R: *Defense Infrastructure: DOD’s 2013 Facilities Corrosion Study Addressed Reporting Elements*, (27 March 2014), 1.

¹⁷⁰ Greenwood, C., “Navy Puts Use of Single-Coat System on a Fast Track”, *CorrDefense: DoD News about Preserving Military Assets* (Summer 2009).

¹⁷¹ *Ibid.*

¹⁷² NRL Press Release, “NRL Scientists Recognized for Cost-Saving Paints,” 5 June 2013.

STRUCTURAL ACOUSTICS

ACHIEVEMENT

NRL developed structural acoustics (SA)-based sonar technology for search and identification of underwater targets. This new approach has significant advantages over conventional acoustic techniques that rely on kinematic analysis of the scattered returns in the case of anti-submarine warfare (ASW), or the formation of high-resolution images in the case of mine countermeasures (MCM). Also referred to as Acoustic Color, this new automated target recognition (ATR) technology uses machine learning and a diverse set of “fingerprints” leading to high probability of detection and classification, low false alarm rates, longer range operation leading to wide-area coverage, and low-frequency sediment penetration leading to the potential buried target prosecution.

SA-based sonar processing has been inserted into a deployed ASW sonar. NRL led a successful rapid response project to apply Acoustic Color to the SQQ-89 sonar system installed on Arleigh Burke-class destroyers. Funded as part of a “Speed to Fleet” initiative, NRL completed the algorithm modifications, software engineering, and at-sea demonstrations in fleet operations within 18 months. An at-sea demonstration was carried out aboard the destroyer USS *Fitzgerald* in May 2015.

NRL has also applied this technique to mine hunting using new broadband acoustic sources on autonomous underwater vehicles. NRL’s Low Frequency Broadband (LFBB) technology addresses the Navy’s need to reliably detect and identify undersea volume and bottom mines in high-clutter environments with low false alarm rates. The Knifefish system is a part of the MCM mission package targeted to reduce risks to personnel by operating in potential minefield regions as an off-board sensor, allowing host ships to remain at safe distances outside minefield boundaries.

IMPACT

Modern diesel submarines operating in shallow water, on or near the bottom, pose a challenge to the U.S. Navy. NRL’s technology provides high-performance detection and classification of these difficult targets using an automated approach to achieve target-clutter separation, enhancing the Navy’s ability to conduct undersea warfare without creating an entirely new system. NRL was able to reuse all of the SQQ-89 hardware and much of the existing software of this major fleet system. This provided a low-cost, quick, and successful response to a fleet concern that emerged rapidly. NRL’s new technology for the SQQ-89 sonar is also expected to be effective against the emerging threat from unmanned underwater vehicles.

NRL’s Knifefish system, using LFBB technology, addresses the Navy’s need to reliably detect and identify undersea volume and bottom mines in high-clutter environments with low false alarm rates.

PRIMARY REFERENCE DOCUMENTS

- Waters, Z.J. and Houston, B.H., “Structural Acoustics Based Detection and Classification Techniques for Surface Combatant Sonars”, NDIA Joint Undersea Warfare Technology Spring Conference, San Diego, CA, March 31-April 1, 2015
- Waters, Z.J., *et al.*, “Chief of Naval Operations, Speed-to-Fleet Effort: Structural Acoustics Detection & Classification for the AN/SQQ-89 Surface Combatant Sonar,” NRL Formal Report, NRL/FR/7130—10,300 (2018).
- Houston, B.H., *et al.*, “Low Frequency Broadband Mine Identification, November 2006, March 2007, May 2007 Trial Report (Corpus Christi),” NRL Report, NRL/FR/7130—10-10,190 (2011).

FREE SPACE OPTICS COMMUNICATION

ACHIEVEMENT

Free-space optics (FSO) communication is the use of modulated light to transmit data through the air, similar to the use of wireless radio. The idea to use lasers as the light source for such communications has existed almost since the development of lasers themselves in the 1960s. It was not until the explosion of commercial terrestrial fiber-optic technologies and components in the early 2000s that the technology became mature enough to support implementation of communications in free space. Even with the rapid maturation of the optical communication components, commercial adoption of FSO has been limited to short distances between fixed sites using manual alignment of the optical terminals to establish a link.

Recognizing the potential application of FSO communications for tactical employment, NRL started two applied research programs in the late 1990s examining gigabit-class FSO, and also a low size, weight, and power (SWaP) FSO technology using modulating retroreflectors. NRL established a test range and began collecting extensive optical propagation data in a maritime environment to ensure the technology would be viable for naval employment.

The research efforts culminated in a demonstration at sea in the Trident Warrior 2006 exercise aboard the USS *Bonhomme Richard* and the USS *Denver* with first-generation systems using manual pointing and automated tracking. Two years later, second-generation terminals, with much lower SWaP, were used in exercise Trident Warrior 2008. In 2010, NRL commenced the Tactical Line of Sight Optical Networks (TALON) project to develop a third generation of FSO technology specifically focused on a Marine Corps need for modular, compact, affordable FSO terminals. These third-generation systems were delivered in 2013, culminating in demonstration of a 50 km link at China Lake, California, in 104°F conditions — a first for tactical FSO in an eye-safe, affordable form.

In 2016, NRL continued its work on third-generation systems to fully automate the pointing/acquisition/tracking process to support field use by operational personnel. This effort was funded by proceeds from the third Advanced Wideband Spectrum auction that resulted in the loss of significant amounts of dedicated military radio spectrum, severely affecting the USMC's ability to conduct large-scale training exercises. Proving the military utility of the FSO communications with operational Marines led to funding for design and delivery of fourth-generation systems. These efforts are resulting in a game-changing capability that forms a foundation for future expansion to other platforms and operational environments.

IMPACT

NRL research in FSO communications has generated the data to support sound decisions about operational employment, operational concepts, and acquisition of the technology for tactical use. The goal has been developing and verifying performance of a fieldable prototype. The advantages of using optical links to augment existing RF communications include low probability of detection, low probability of interception, an anti-jam nature, and potential for very high data rates.

PRIMARY REFERENCE DOCUMENTS

- Burris, H.R., *et al.*, "Latest Results From the 32 km Maritime Lasercom Link at the Naval Research Laboratory, Chesapeake Bay Lasercom Test Facility," Proceedings of the SPIE - The International Society for Optical Engineering 5793, 209-219 (2005).
- Rabinovich, W.S., *et al.*, "Free-Space Optical Communications Research and Demonstrations at the U.S. Naval Research Laboratory," *Applied Optics* 54, F189-F200 (2015).

GLOBAL OCEAN FORECAST SYSTEM

ACHIEVEMENT

The Global Ocean Forecast System (GOFS) is the U.S. Navy's global ocean prediction system. It runs daily at Commander, Naval Meteorology and Oceanography Command (CNMOC) production centers. The system depicts the location of mesoscale features, such as oceanic eddies and fronts (i.e., the “ocean weather”) and provides accurate three-dimensional ocean temperature, salinity, and current structure to the fleet. The first global system was declared operational in February 2006 as GOFS 2.0 and was based on two NRL-developed ocean models, the Navy Layered Ocean Model (NLOM) and the Navy Coastal Ocean Model (NCOM). Satellite altimeter data was assimilated into high-horizontal-resolution NLOM and its sea surface height and observed sea surface temperatures were used to create synthetic temperature and salinity profiles projected downward into the ocean interior of NCOM.

GOFS 3.0 became operational in 2013 and represented a next-generation forecast system based on the HYbrid Coordinate Ocean Model (HYCOM) developed under an Office of Naval Research-sponsored consortium between NRL and academia. HYCOM is unique in that it allows a truly general vertical coordinate, which extends the geographic range of applicability of traditional isopycnic coordinate circulation models toward shallow coastal seas and unstratified parts of the global ocean. It maintains the significant advantages of an isopycnal model in stratified regions while allowing more vertical resolution near the surface and in shallow coastal areas, hence providing a better representation of the upper ocean physics. GOFS 3.1 was declared operational in 2018 with three new capabilities: a) increased vertical resolution to better resolve the upper ocean, b) two-way coupling between HYCOM and the Los Alamos National Laboratory-developed Community Ice Code (CICE), and c) improved synthetic profile projection into the ocean interior. CICE provides prediction of the cryosphere that includes sea ice concentration, thickness, and drift forecasts. Lastly, GOFS 3.5 was developed and includes astronomical tidal forcing that produces internal ocean waves at tidal frequencies important to the submarine community.

IMPACT

GOFS provides the Navy with a first look of the three-dimensional ocean environment “anywhere, anytime” across the global ocean. These environmental fields are also used to provide real-time predictions of derived acoustic parameters including sound speed and sonic layer depth. In addition, GOFS provides boundary conditions for higher-resolution regional/coastal models. Ocean forecasts are valuable for tactical planning, optimum-track ship routing, search-and-rescue operations, long-range weather prediction, and the location of high-current shear zones.

GOFS also provides forecasts of sea ice extent and thickness in the Arctic and the Antarctic. The sea ice environment in the Arctic Ocean has become increasingly important for strategic and economic reasons over the past decade, given the diminishing trend in year-to-year sea ice extent and thickness and the potential summertime opening of the Northwest Passage and Siberian sea routes. Fractures, leads and polynya forecasts are also valuable to the naval submarine community.

PRIMARY REFERENCE DOCUMENTS

- Rhodes, R.C., *et al.*, “Navy Real-time Global Modeling Systems”, *Oceanography*, 15(1):29-43, 2001.
- Metzger, E.J., *et al.*, “US Navy Operational Global Ocean and Arctic Ice Prediction Systems”, *Oceanography* 27(3):32–43, 2014.

REGIONAL TROPICAL CYCLONE PREDICTION SYSTEMS

ACHIEVEMENT

NRL's Coupled Ocean/Atmosphere Mesoscale Prediction System–Tropical Cyclone (COAMPS-TC¹⁷³) is a regional prediction system designed to generate five-day forecasts of tropical cyclone (TC) track, intensity, and structure. The development of the deterministic COAMPS-TC system began in 2010, and it was implemented operationally at Fleet Numerical Meteorology and Oceanography Center (FNMOC) in 2013. In 2020, the COAMPS-TC Ensemble Prediction System (EPS) was implemented at FNMOC, becoming the first operational high-resolution ensemble-based probabilistic TC prediction system in the world. The COAMPS-TC deterministic system and COAMPS-TC EPS have now supported operations for the Navy and the DoD worldwide for a decade.

COAMPS-TC is a highly specialized version of COAMPS, which has been the Navy's operational regional prediction system since 1998. It is a dynamical model, simulating the three-dimensional state of the atmosphere for the TC vortex and the surrounding region, using high-resolution storm-centered moving nested grids. COAMPS-TC uses special algorithms to represent key physical processes in TCs such as surface drag that occurs at high wind speeds, cloud microphysics appropriate for eyewall convection, and heating from turbulent dissipation. The atmospheric component of COAMPS-TC is coupled to the NRL Coastal Ocean Model (NCOM) to facilitate feedbacks between the atmosphere and the ocean, which are crucial for accuracy TC in intensity prediction.

COAMPS-TC has been upgraded yearly and model performance has dramatically improved. An evaluation of operational forecasts in 2022 revealed that deterministic COAMPS-TC track and intensity predictions are competitive with, and in some aspects superior to, the other leading TC forecast models worldwide. Operational forecasts of hurricanes Laura (2020), Ida (2021), and Ian (2022), all of which had devastating impacts on the U.S. Gulf Coast, highlighted the capability of deterministic and ensemble COAMPS-TC systems to accurately predict these rapidly intensifying TCs, which have been a major scientific challenge.

COAMPS-TC has supported numerous ONR-sponsored observational field campaigns: Tropical Cyclone Structure (2008), Impacts of Typhoons on the Ocean in the Pacific (2010), Tropical Cyclone Intensity (2015-2016), and Tropical Cyclone Rapid Intensification (2020-2022).

IMPACT

Tropical cyclone forecasts produced from COAMPS-TC are routinely used by the DoD Joint Typhoon Warning Center and the NOAA National Hurricane Center and are distributed to DoD commands around the world to support mission planning, ship and aircraft operations, and hazardous weather avoidance. The COAMPS-TC forecasts and system are also used by academic and research institutions worldwide.

PRIMARY REFERENCE DOCUMENTS

- Doyle, J.D., Jin, Y., Hodur, R., Chen, S., Moskaitis, J.R., Wang, S., Hendricks, E.A., Jin, H., Smith, T.A., 2014: Tropical cyclone prediction using COAMPS-TC. *Oceanography*, **27**, 92-103.
- Komaromi, W.A., Reinecke, P.A., Moskaitis, J.R., Doyle, J.D., 2021: The Naval Research Laboratory's Coupled Ocean–Atmosphere Mesoscale Prediction System–Tropical Cyclone Ensemble (COAMPS-TC Ensemble). *Wea. Forecasting*, **36**, 499-517.

¹⁷³ COAMPS-TC is a registered trademark of the Naval Research Laboratory.

WINDSAT SPACEBORNE POLARIMETRIC MICROWAVE RADIOMETER

ACHIEVEMENT

NRL's WindSat is the first satellite-based polarimetric microwave radiometer. It was launched in 2003 as the primary payload on the DoD's Coriolis satellite. WindSat's mission was to test and fully evaluate the viability of using passive polarimetric radiometry to retrieve the ocean surface wind vector (wind speed and direction) from space. WindSat also measures sea surface temperature, total precipitable water, integrated cloud liquid water, rain rate over the ocean, soil moisture, and sea ice. Operating over multiple frequencies and polarizations, the radiometer measures microwave energy emitted from the ocean surface. NRL developed ground-processing algorithms to convert these raw data into useful environmental intelligence products. WindSat provided valuable operational data from 2005 through the end of its mission in 2020.

Winds over the ocean affect nearly every aspect of naval operations, including ship routing, carrier operations, and search and rescue. Global ocean winds also provide essential information for short-term weather forecasts and warnings, nowcasting, and climatological and oceanographic studies. For these reasons, the global ocean wind vector had been designated as one of the top meteorological measurement requirements of the Oceanographer of the Navy. WindSat successfully demonstrated the ocean wind vector measurement capability and became a pathfinder for future national weather satellites. In addition, WindSat opened up the field of polarimetric radiometry. One discovery was the relatively strong cross-correlation signals when viewing the ice sheets of Greenland and Antarctica. This offers a potential, new technique for characterizing these environmentally critical regions.

The National Research Council judged Coriolis (Air Force)-Windsat (Navy) to be a model of interagency cooperation in satellite development. NRL developed WindSat for the Navy and the National Polar-orbiting Operational Environmental Satellite System Integrated Program Office. Developed for Navy battlespace environment needs, NRL's proof-of-concept system filled a gap in critical meteorological needs as the U.S. military awaits launch of the Weather System Follow-on Microwave satellite.

IMPACT

In more than 17 years on orbit, WindSat far exceeded its original mission objectives. WindSat data was ingested into the Navy Global Environmental Model, as well as civilian numerical weather models of NOAA and the UK Meteorology Office. The Joint Typhoon Warning Center and the National Hurricane Center used WindSat data to improve monitoring and forecasting of tropical cyclones. More accurate forecasts save the U.S. Navy millions of dollars annually in storm preparations and avoidance by the fleet.

PRIMARY REFERENCE DOCUMENTS

- Gaiser, P.W. *et al.*, "The WindSat Spaceborne Polarimetric Microwave Radiometer: Sensor Description and Early Orbit Performance", *IEEE Trans. on Geosci. and Remote Sensing*, vol. 42, no. 11, 2347-2361, 2004.
- Bettenhausen, M.H. *et al.*, "A Nonlinear Optimization Algorithm for WindSat Wind Vector Retrievals," *IEEE Trans. on Geosci. and Remote Sensing*, vol. 44, no. 3, 597-610, 2006.
- Li, L., *et al.*, "WindSat Passive Microwave Polarimetric Signatures of the Greenland Ice Sheet," *IEEE Trans. on Geosci. and Remote Sensing*, vol. 46, no. 9, 2622-2631, 2008.

HYDROGEN FUEL CELLS FOR UNMANNED SYSTEMS

ACHIEVEMENT

NRL has made significant contributions to the field of hydrogen fuel cells and to their application as high-energy-density sources for unmanned systems. Fuel cells electrochemically convert hydrogen fuel and oxygen in air into electricity and water. NRL has also played a critical role in developing novel electrocatalysts for hydrogen fuel cells and methods for their operation in sulfur-rich environments that would otherwise result in catastrophic poisoning. In parallel with these fundamental studies, NRL enabled the first successful flight of a fuel cell-powered unmanned aerial vehicle (UAV).

Based on the UAV's flight time of over 3 hours, NRL began in 2006 to develop a concept for a submarine-launched unmanned aerial vehicle, the XFC, to be powered by a fuel cell that provides over 6 hours' endurance. A hydrogen fuel cell was key to the XFC mission, as a battery-powered vehicle would lack sufficient energy for acceptable endurance, and a combustion engine-powered vehicle would create an unacceptable signature and would be difficult to launch from a torpedo tube. The XFC is on track for use by the U.S. Navy.

NRL pushed the envelope on the endurance achieved with fuel cell-powered small UAVs. With the ONR-funded Ion Tiger research vehicle, NRL demonstrated a 26-hour flight using compressed hydrogen fuel in 2009, and then a 48-hour flight using cryogenic hydrogen in 2013. Both are unofficial world records for endurance. NRL has developed its own fuel cell system to support Group 1 and 2 UAVs (up to ~100lbs), which has been demonstrated in commercial UAVs and is being licensed by a U.S. industrial partner. NRL has also teamed with General Motors since 2010 to demonstrate that automotive hydrogen fuel cells can be effectively used for air-independent propulsion of a large unmanned undersea vehicle.¹⁷⁴

IMPACT

NRL created a new type of propulsion for UAVs, the hydrogen fuel cell, which is capable of long endurance and low signature. These are benefits not provided by the limited endurance of batteries or the acoustic footprint of combustion engines. Fuel cells provide a path to long-endurance missions for unmanned systems because of the high energy of hydrogen in combination with the high efficiency of the electrochemical fuel cell. The Navy is well poised to develop this clean, stealthy technology for its next-generation systems.

PRIMARY REFERENCE DOCUMENTS

- Garsany, Y., Baturina, O., Swider-Lyons, K., "Impact of Sulfur Dioxide on the Oxygen Reduction Reaction on Platinum/Vulcan Carbon," *J. Electrochem. Soc.*, 154 (2007) B670-B675.
- Garsany, Y., *et al.*, "Experimental Methods for Quantifying the Activity of Electrocatalysts for the Oxygen Reduction Reaction" *Anal. Chem.* 82 (2010) 6321–6328.
- Swider-Lyons, K., *et al.*, "Hydrogen Fuel Cells for Small Unmanned Air Vehicles," *ECS Trans.* 64(3), 963-972 (2014).
- Swider-Lyons, K., Deitz, D., "Hydrogen Fuel Cells for Unmanned Undersea Vehicle Propulsion," *ECS Trans.* 75:479-489 (2016).
- Stroman, R.O, *et al.*, "Liquid Hydrogen Storage for UAVs: Final Report of the Ion Tiger Cryogenic Fuel Tank Program", NRL Formal Report 6113—14-10,252, August 23, 2014.

¹⁷⁴ GM News Release, "GM and U.S. Navy Collaborating on Fuel Cell-Powered Underwater Unmanned Vehicles", 23 June 2016.

TOPSIDE CAMOUFLAGE AND NONSKID DECK COATINGS

ACHIEVEMENT

Legacy epoxy-based nonskid coatings and silicone alkyd-based topside coatings used by the Navy are degraded quickly by UV exposure and have a relatively short life cycle, up to 2 years and 3 years, respectively. This degradation results in corrosion seepage, chemical contamination, loss of abrasive profile and even delamination that may act as foreign object debris (FOD) for aircraft.

In response, NRL developed and transitioned both two-component (2K) and single-component (1K, all-in-one-can) polysiloxane-based coatings. In the case of nonskid deck coatings, the coatings possess greater external durability, color retention, and resistance to moisture, hydrocarbons, and detergents. Significantly, a single formulation can be rolled or sprayed for flight decks and walkways of both surface ships and submarines. The coating has been qualified by NAVSEA and approved for fleet usage.

Likewise, standard Navy haze gray silicone alkyds have been used on the topsides of Navy surface ships for about 50 years. A weakness of these surface treatments is susceptibility to staining from running rust and soot. NRL has synthesized a novel organosilane polymer that enabled formulation of a 1K polysiloxane system. It provides greater exterior durability (i.e., retention of visual camouflage), improved chemical resistance and cleanability, and enhanced corrosion resistance than both silicone alkyds and recently qualified commercial 2K polysiloxane coatings. It is also easily applied with brush or roller by sailors.

IMPACT

Polysiloxane coatings are now mandated by NAVSEA for use in surface ship freeboard and topside superstructure applications. The technology demonstrates both reduced acquisition costs (28% reduction in installed cost) and extended life cycle performance (3–5 times). This has enabled a culture change in sailor maintenance workload. In 2016, a full ship application on the USS *Mahan* (DDG 72) showed a 34-fold reduction in sailor workload relative to legacy coated areas. In addition, the single-component polysiloxane coating was sailor-applied (typically a depot-level activity) on the entire exterior freeboard (~105,000 sq. ft.) of the USS *Essex* (LHD-2) in 2017. The cost for sailors to apply the coating was less than \$100K, a cost avoidance of more than \$900K compared to depot costs.

PRIMARY REFERENCE DOCUMENTS

- U.S. Patent 9,139,753 to Iezzi, E. B. Single-Component Moisture-Curable Coatings Based on N-Substituted Urea Polymers with Extended Chains and Terminal Alkoxysilanes, Sept. 22, 2015.
- U.S. Patent 9,006,307 to Iezzi, E., Martin, J., and Slebodnick, P., Direct to Metal and Exterior Durable Non-Skid Coatings, April 14, 2015.
- Martin, J., Lemieux, E., Iezzi, E.B., Tagert, J., Wegand, J., and Slebodnick, P., “High-Durability Organosiloxane Nonskid Coatings,” *NRL Review*, 2011, 140-142.
- Iezzi, E., Martin, J., Slebodnick, P., Wegand, J., Lemieux, E., Tagert, J., “Single-Component Polysiloxane Coating for Navy Topsides”, The Society for Protective Coatings (SSPC) Conference 2013 - Military Coatings Session, San Antonio, TX, January 14-17, 2013.
- Iezzi, E., Tagert, J. “Single-Component Polysiloxane Topcoats for Navy Surface Ships”, *Journal of Protective Coatings & Linings (JPCL)*, November 26-31, 2016.
- Iezzi, E., Tagert, J., Martin, J., Slebodnick, P., and Wegand, J., “Gaining Traction: Low VOC and Sprayable Siloxane Non-Skid/Non-Slip Coating for the U.S. Navy & Non-Military Markets,” *Journal of Protective Coatings & Linings (JPCL)*, 36-41, November 2014.

FLYING SQUIRREL

ACHIEVEMENT

Flying Squirrel is an NRL-developed software application suite that provides real-time discovery, analysis, and mapping of IEEE 802.11a/b/g/n wireless networks and is also capable of scanning for Bluetooth devices. With the advantages that wireless technologies provide, many organizations are seeking the means to securely integrate wireless capabilities into their networks. In an effort to standardize wireless security for the purpose of detecting, and thus deterring, unauthorized wireless activity, the DoD's Enterprise-Wide Solutions Steering Group (ESSG) identified the need to enhance network security through the employment of a Wireless Discovery Device capability. In 2006, the ESSG selected Flying Squirrel as the approved DoD tool for wireless discovery and mapping application.

In order to meet a follow-on requirement for continuous monitoring for threats, a variant of Flying Squirrel called Orb-weaver was developed to fulfill this requirement using multiple fixed sensors. Small fixed-sensor deployments, such as single rooms, to numerous sensor deployments on a large campus, provides continuous wireless monitoring and geolocation for Wi-Fi, cellular, and Bluetooth devices to promote compliance with organizational policies such as a "no-cellphone" policy. Orb-weaver helps combat the exfiltration of classified and sensitive information over wireless signals by insiders, foreign intelligence activities, and other rogue actors.

IMPACT

Flying Squirrel and Orb-weaver have been adopted and are currently employed throughout the DoD, the intelligence community, federal agencies, and law enforcement, all with a combination of shared goals to detect and geolocate any wireless technology. The U.S. Army's "Wireless Security Standards" explicitly name Flying Squirrel to perform monthly wireless assessment scans. In the case of overseas deployments, Flying Squirrel is used for Blue Force protection, ensuring an improved security posture for any forward-deployed units. Law enforcement utilizes Flying Squirrel to detect and geolocate criminal activity, using the results in criminal investigation and prosecution.

PRIMARY REFERENCE DOCUMENTS

- "Flying Squirrel Wireless Discovery & Mapping Application", Available: <https://www.nrl.navy.mil/itd/chacs/5545/flying-squirrel> [Accessed: 22- Jan- 2023].
- "Wireless Security Standards", "Information Assurance Best Business Practice (IA BBP)", U.S. Army CIO/G-6 Cybersecurity Directorate, Version 4.0, June 26, 2013.

HIGH-TEMPERATURE NONSKID DECKING

ACHIEVEMENT

With the advent of vertical landing and take-off aircraft such as the Joint Strike Fighter (F-35), amphibious landings were anticipated to result in on-deck temperatures high enough to incinerate legacy organic nonskid materials. This was observed during Demonstration Testing #1 (DT-1) on the USS *Wasp* in 2011. In response, NRL developed Thermal Spray Nonskid (TSN), which is an inorganic nonskid decking that is a robotically applied coating using arc-wire thermal spray processes of commercially available hybrid aluminum/ceramic feedstock. NRL developed and validated the surface preparation and the relationships of application parameters to performance, and conducted the engineering to integrate thermal spray devices with deck rastering robotics. The resulting systems were tested in scaled jet nozzles with no degradation or erosion through 200 simulated vertical landing cycles. This was later demonstrated shipboard and showed no degradation through hundreds of vertical landings and multiple deployments on the USS *Wasp*.

Ultimately, this system was used to solve a flight deck readiness issue caused by operations of MV-22 and AV-8B aircraft on forward-deployed amphibious-class ships. The issue was elevated to the Marine Corps Commandant and the Chief of Naval Operations (CNO) because of several AV-8B engine casualties and curtailed flight operations resulting from foreign object debris caused by failing nonskid coatings. TSN was shown to be a viable solution to the flight deck readiness problem. In 2014, at the direction of Fleet Forces Command, NRL led the rapid transition of this technology to the amphibious-class fleet. As neither the NAVSEA acquisition processes nor the industrial base were mature enough to support this state-of-the-art process, NRL has spanned the gap as the primary technical expertise to execute the installation of this system on over 125,000 ft² on nine ships as of 2020 — USS *Wasp* is programmed to have TSN reapplied after 10 years of service and USS *Bougainville* (under construction) is scheduled for application in FY24.

IMPACT

The development and rapid transition of thermal spray nonskid coating to the amphibious-class fleet resolved a CNO priority for a flight deck readiness problem that was curtailing flight operations and was resulting in AV-8B engine casualties.¹⁷⁵ NRL has been widely recognized for this technological development through several awards and commendations from the under secretary of defense (research and engineering), USFF N43, NAVSEA 00, PEO Ships and NAVSEA 05. As noted by the program manager of PMS377, “The integration of the MV-22 and the F35B onto large deck amphibious ships has posed numerous technical challenges ... application of TSN is currently the only way to mitigate these issues.”¹⁷⁶

PRIMARY REFERENCE DOCUMENTS

- Wegand, J., *et al*, “Status of High Temperature Resistant Thermal Spray Nonskid Coatings within the U.S. Navy,” DoD – Allied Nations Technical Corrosion Conference Pittsburgh, PA, 2015.
- Spicer, C, Miller, C., Tagert, C., Eppard, S., Wegand J. and Alley, E., “Development of Test Method for Evaluating Nonskid Performance for Vertical Take-Off and Landing Aircraft Service Environment,” SSPC 2018 Conference Proceedings, 2018.

¹⁷⁵ “Large Deck - Flight Deck Materiel, Readiness OPT Report (19SEP2014)” by the Office of the Chief of Naval Operations, Expeditionary Warfare Division (OPNAV 95).

¹⁷⁶ Letter of Appreciation to NRL’s TSN team for the application of TSN on LHA 7 (2018).

NULKA OFFBOARD COUNTERMEASURE SYSTEM

ACHIEVEMENT

NRL, in partnership with the Australian Defence Science and Technology Organisation, developed Nulka, a quick-reaction offboard electronic countermeasure decoy to defeat anti-ship missiles (ASMs). In 1986, the U.S. and Australia signed an agreement to undertake full-scale collaborative development of the Nulka concept. Nulka faced many hurdles — technical, managerial and political — before it became the state-of-the-art ship-protection system that is now deployed on U.S. and Australian warships.

The project that led to the Nulka decoy originated in Australia in the early 1970s, leveraging NRL's pioneering work on off-board decoys during the 1960s and the early 1970s. For example, NRL's Tactical Electronic Warfare Division had undertaken numerous studies on the use of off-board decoys for warship protection, had investigated a wide range of decoy concepts, and had fostered exploratory development of high-performance, low-cost electronic components and devices that could sustain the challenging maritime environment and deployment concepts. By 1995, U.S. Navy fleet commanders were convinced of the system's value. In 1996, the U.S. and Australia began joint production of the Nulka decoys. The early involvement of industry, coupled with the partnership between Australia and the U.S., were key reasons Nulka entered full rate production in 1999.

Nulka is now deployed on numerous Australian and U.S. warships under a program costing around \$1 billion. That it took close to 40 years after Nulka was conceptualized testifies to the complexity of the project, which was surmounted by determination and the unique collaborative relationships between the two countries' R&D and acquisition communities.

IMPACT

The Nulka decoy system is an integral part of the self-defense system against active RF ASM threats on most U.S. and Australian warships. Its incorporation into a layered defense system is essential in providing ship survivability under high-stress conditions in the littoral and open-ocean environments. Because of the characteristics of the decoy payload and the system's fast reaction time, the Nulka system is highly effective against ASMs. The system is effective over a full 360 degrees around the defended ship. The effectiveness of the decoy is independent of ship maneuvers even in the most extreme environmental conditions.

Nulka continues to be one of the most effective surface ship EW systems in existence today, protecting forward-deployed forces serving on U.S. Navy and Australian platforms around the world.

PRIMARY REFERENCE DOCUMENTS

- Gambling, D., Crozier, M., and Northam, D., *NULKA : A Compelling Story* (ISBN: 9780987544704), © Commonwealth of Australia 2013, First published in 2013 by the Defence Science and Technology Organisation, Canberra ACT 2600.
- Lockheed Martin, *Nulka Brochure*, 2007.

ONION ROUTING, TOR, AND ONION SERVICES

ACHIEVEMENT

The original Internet and original Web protocols were designed without security in mind. NRL invented onion routing as a way to “peel off” and separate identification from routing for Internet connections. Onion routing provides confidentiality and authentication of the route that connections take between client and server. It was developed by NRL to protect American intelligence communications online.¹⁷⁷

NRL research on onion routing and onion services has been ongoing since 1995. In 2004, NRL released Tor (*The* onion router, so named to distinguish the NRL original from imitators). In addition, Tor introduced onion services. Reachable via an IETF-reserved top-level domain, *.onion*, these offer authentication and confidentiality of site address lookup, as well as self-authenticating addresses. Unlike ordinary domain names, they are resistant to the many hijacking and man-in-the-middle attacks that have affected sites protected merely by the TLS-certificate and HTTPS encryption infrastructure. In 2016, PrivCount was released. PrivCount has given network researchers, network defenders, and law enforcement a more accurate picture of network usage than was previously possible while reducing the risk to users from either data gathering or the release of resulting statistics.

IMPACT

The public Tor network has grown steadily, currently protecting millions of daily users via a global network comprising thousands of onion routers, transiting an average combined 130 Gbit/sec. Onion service adoption also continues growing. Both Facebook and the *New York Times* offer onion services for improved availability and protection of users wishing to access their sites. Internet services and technology are also increasingly available via onion services, including the DuckDuckGo search engine.

While there are criminal elements operating in the “dark web” that use this technology, among Tor’s many legitimate users include the military, journalists, whistle-blowers, victims of domestic abuse, and dissidents suffering under authoritarian regimes.¹⁷⁸ Tor’s recognitions include the Electronic Frontier Foundation’s Pioneer Award, a USENIX Test of Time Award, and its creators were named to the list of 100 Global Thinkers of 2012 by the journal *Foreign Policy*.

PRIMARY REFERENCE DOCUMENTS

- Reed, M.G., Syverson, P.F., and Goldschlag, D.M., "Anonymous connections and onion routing," *IEEE Journal on Selected Areas in Communications* 16 (4), 482-494, May 1998.
- Dingledine, R., Mathewson N., and Syverson, P., "Tor: The Second-Generation Onion Router," *Proceedings of the 13th USENIX Security Symposium*, 303-319, August 2004.
- Jansen, R., and Johnson, A., "Safely Measuring Tor," *Proceedings of the 23rd ACM Conference on Computer and Communications Security (CCS '16)*, 1553-1567, October 2016.
- Goldschlag, D.M., Reed, M.G., and Syverson, P.F., "Hiding Routing Information," *Proceedings of the First International Workshop on Information Hiding*, 137-150, May 1996.
- U.S. Patent No. 6266704 to Reed, M.G., Syverson, P.F., and Goldschlag, D.M., "Onion routing network for securely moving data through communication networks," July 24, 2001.

¹⁷⁷ Lawrence, D., "The Inside Story of Tor, the Best Internet Anonymity Tool the Government Ever Built," *Bloomberg Businessweek*, (23 January 2014).

¹⁷⁸ Sardá T., "An Onion with Layers of Hope and Fear: A Cross-Case Analysis of the Media Representation of Tor Network Reflecting Theoretical Perspectives of New Technologies," *Security and Privacy* (2023).

TRANSPARENT ARMOR

ACHIEVEMENT

DoD spends tens of millions of dollars, and thousands of hours each year, replacing failed ballistic glass on tactical vehicles such as the High Mobility Multipurpose Wheeled Vehicle (HMMWV), the Medium Tactical Vehicle Replacement (MTVR), and others. In the majority of cases, the glass, also called transparent armor (TA), has not been damaged but the spall layer has delaminated, allowing water or dirt to infiltrate, making it difficult to safely operate the vehicle. This failure mode occurs across all armored vehicle platforms. TA lifetime is typically 3–5 years and replacement costs are \$1K–10K per window. A 2017 study of 1,000 Marine Corps vehicles showed that 60% of MTVRs and 70% of HMMWVs should have one or both windshields replaced to achieve full readiness.¹⁷⁹

From 2011 to 2013, NRL demonstrated the repair of TA at a fraction of the cost of a new part. These first studies demonstrated a range of repair methods, including both in frame and out of frame as well as using a traditional autoclave or a radio-frequency press. The bond strength and durability of the re-laminated parts were found to depend on the type of repair. Based on the success of that study, NRL continued to serve as the primary in-house technical expert for the Marine Corps PEO-Land Systems as the repair process has been refined and transitioned to industry partners. NRL supported final transition of the repair, serving as the subject-matter expert to oversee final demonstration and to develop the test plan. That test plan enabled the USMC chief engineer to sign a memo formally allowing relaminated TA as a source of transparent armor acquisition.

NRL is continuing to drive TA lifetime research, currently leading the federal government's largest testing and evaluation of TA with participation by every domestic manufacturer of TA. The data from this testing will enable prediction of TA lifetime so that parts can be purchased on a cost per year of expected life. NRL is directly advising both USMC and Army program offices on TA lifetime.

IMPACT

NRL's partnership with the Marine Corps PEO-Land System has changed TA from a short-lived, costly consumable to a repairable item and has dramatically shifted the economics of transparent armor. The immediate effect of the repair technology will be to enable increased vehicle readiness by allowing units to replace degraded TA at a much lower cost.

In 2018, NRL was recognized as part of a team that received the Navy "Innovation Excellence Acquisition Team of the Year Award" for developing a repair solution for delaminated TA, estimated to save the U.S. Marine Corps \$105 million over a five-year period.

PRIMARY REFERENCE DOCUMENTS

- Merrill, M. H., *et al.*, "Repair Methods for Delaminated Transparent Armor." NRL/MR/6350-14-9501, January 2014.
- Merrill, M. H. "Delamination in Transparent Armor: The Known Unknowns." Fall Technical Meeting of the Composites Consortium. Washington, DC. October 24-25, 2017.
- *Innovation Excellence Acquisition Team of the Year Award*, October 16, 2018.

¹⁷⁹ Pint, E., Fleming, J., Germanovich, G., Muggy, L., 2017. "Ballistic Glass Replacement Analysis." RAND National Defense Research Institute.

GALLIUM NITRIDE TRANSISTOR DEVELOPMENT

ACHIEVEMENT

NRL's research has been critical to the successful development and application of gallium nitride (GaN) as a next-generation material for semiconductors, which enable advanced high-power capability of radio-frequency transmitters for naval radar and electronic attack. As a semiconductor material, GaN offers many advantages over silicon, the previous industry standard, including higher voltage and power handling, greater efficiency, and improved thermal performance.

Beginning in the mid-1990s, NRL performed pioneering work related to the growth, processing, and practical implementations of GaN material and devices, particularly high-electron-mobility transistors (HEMTs). In 1995, NRL developed an ion-implant isolation technique that effectively defined active areas on the wafer that has become an industry standard for GaN microfabrication.

NRL also demonstrated the first AlGaIn/GaN HEMTs grown on a high-thermal-conductivity silicon carbide (SiC) substrate. This achievement is a key enabler for high-power devices and has been widely adopted by industry. In 2001, NRL identified trapping effects that were the primary inhibitors to AlGaIn/GaN HEMT large-signal performance and developed a surface passivation technique that significantly improved microwave power performance. The surface passivation technique is used today in every GaN transistor.

For over 25 years, NRL has made significant contributions to the development of GaN as a usable material for both defense and commercial applications. In addition to scientific breakthroughs, NRL researchers have provided the Navy and the DoD with subject-matter expertise, device evaluation, reliability testing, and failure analyses leading to the implementation of GaN technology in U.S. defense systems.

IMPACT

NRL's seminal work in the field of GaN materials and devices has laid the foundation for the use of these devices in a number of next-generation systems including the AN/SPY-6(V) Air and Missile Defense Radar that will be deployed on Flight III Arleigh Burke DDG-51 guided-missile destroyers, in active electronically steered arrays for the Next Generation Jammer, in the Kwajalein Atoll's Space Fence radar for space object identification and tracking, and the AN/TPS-80 Ground/Air Task Oriented Radar.

PRIMARY REFERENCE DOCUMENTS

- Binari, S.C., Dietrich, H.B., Kelner, G., Rowland, L.B., Doverspike, K., and Wickenden, D.K., "H, He, and N implant isolation of n-type GaN," *Journal of Applied Physics*, Vol. 78, No. 5, September 1995.
- Binari, S.C., Redwing, J.M., Kelner, G., and Kruppa, W., "AlGaIn/GaN HEMTs grown on SiC substrates," *Electronics Letters*, Vol. 33, No. 3, January 1997.
- Binari, S.C., *et al.*, "Trapping effects and microwave power performance in AlGaIn/GaN HEMTs," *IEEE Transactions on Electron Devices*, Vol. 48, No. 3, March 2001.
- Mittereder, J., Cronk, N., Binari, S., Ancona, M., Via, D., Heller, E., Tetlak, S., and Poling, B., "Accelerated Life Testing of Cree S-band GaN Technology," *NRL Memorandum Report* NRL/MR/6850—11-9345, September 2011

FIRST OPERATIONAL SHIPBOARD LASER WEAPON

ACHIEVEMENT

Challenges posed by asymmetric warfare and hypersonic missiles are placing new demands on the U.S. Navy. These threats create the need for defensive weapons that have a low cost per shot, offer a deep magazine, and are high-precision, high-speed, and compact in size. An early response to these warfighting requirements was the first operational shipboard laser weapon, the Laser Weapon System (LaWS).

The incoherent beam combining (IBC) concept that enabled LaWS was developed by NRL and Penn State University in 2006, eight years before the weapon system's deployment. The IBC concept provided a near-term path to a laser weapon and allowed the Navy to be the first service to field an operational laser weapon. NRL pioneered the use of single-mode fiber lasers with very good optical beam quality to extend the effective range of incoherently combined lasers. NRL carried out a proof-of-concept demonstration from 2007 to 2008 at the Naval Surface Warfare Center - Dahlgren Division and the Starfire Optical Range in New Mexico. LaWS was a solid-state fiber laser (SSFL) compact enough to be installed on ships as small as the LCS class. SSFLs are relatively low-maintenance, have a low operating cost, and place less demand on the ship's power supply. In addition, they are easier to cool, provide good beam quality, and can achieve up to 35% power output efficiency relative to the power provided to the system (higher-than-average efficiency compared to other lasers at the time).¹⁸⁰

In 2014, LaWS was installed aboard the USS *Ponce* (Afloat Forward Staging Base (I)-15) to test the viability of directed energy weapons in an operational environment. It was soon declared an operational asset and the ship's commander was given permission to defend the ship with the weapon.

IMPACT

Each shot from the prototype laser costs 59 cents. In contrast, the Standard Missile-2, a common surface-to-air weapon, costs the Navy roughly \$400,000 per missile.¹⁸¹ However, the impact of LaWS extends well beyond cost. LaWS was considered effective against a range of threats including unmanned aerial vehicles, slow-moving helicopters, rigid-hull inflatable boats, fast patrol craft, and multiple small boats in swarm-attack formations. With lasers supplementing missiles and other shipboard weapons, ships will also be able to remain at sea longer. The success of the LaWS program has spurred several high-energy-laser development programs across the Department of the Navy.

PRIMARY REFERENCE DOCUMENTS

- Sprangle, P., "Incoherent Combining of High-Power Fiber Lasers for Long Range DE Applications," 2006 *Solid State and Diode Laser Technology Review* (June 2006)
- NRL Memorandum Report NRL/MR/6790-06-8963; also *J. Directed Energy*, 2, 273 (2007)
- Sprangle, P., Peñano, J., Hafizi, B., Ting, A., and Fischer, R., U.S. Patent #7,970,040, "Apparatus for Incoherent Combining of High Power Lasers for Long-Range Directed-Energy Applications" (June 28, 2011)
- Sprangle, P., Hafizi, B., and Ting, A., "NRL and the Development of the Laser Weapon System", *Future Force Magazine*, vol. 2 (Winter 2015), 18.

¹⁸⁰ LaGrone, S., "US Navy Allowed to Use Persian Gulf Laser for Defense," *USNI News* (10 December 2014).

¹⁸¹ Barnes, J., "Navy Tests Laser Weapon on Drones, Boats" *Wall Street Journal*, (9 December 2014).